

PL-L Long 4-Pin Base

PL-L 18W/830/4P

Philips Linear Compact Fluorescent Lamps offer designers, specifiers and end-users new levels of efficiencies and versatility in sizes, configurations and application possibilities. With so many elegant fixtures available to complement their small size, high light output and advanced technology, Philips Energy Advantage lamps are fast becoming the preferred choice when maximum effciency and sleek design solutions are required.

Product data

General Information

Cap-Base Life To 50% Failures (Nom) Life To 50% Failures Preheat (Nom)

• Light Technical

Color Code Initial lumen (Nom) Color Designation Lumen Maintenance 10000 h (Nom) Lumen Maintenance 2000 h (Nom) Lumen Maintenance 5000 h (Nom) Chromaticity Coordinate X (Nom) Chromaticity Coordinate Y (Nom) Correlated Color Temperature (Nom) Luminous Efficacy (rated) (Nom) Color Rendering Index (Nom)

830 [CCT of 3000K] 1200 lm Warm White (WW) 92 % 94 % 93 % 440

2G11 [2G11]

15000 h

20000 h

• Operating and Electrical Power (Rated) 18.0 W (Nom) Lamp Current (Nom) 0.375 A 58 V Voltage (Nom)


- Controls and Dimming Dimmable Yes
- Mechanical and Housing Bulb Finish Silicon Cap-Base Information 4P
- Product Data

Order product name	F
EAN/UPC - Product	0
Order code	3
Numerator - Quan-	1
tity Per Pack	
Numerator - Packs	2
per outer box	
Material Nr. (12NC)	9
Net Weight (Piece)	6
ILCOS Code	F

60.900 g FSD-18/30/1B-E-2G11




Dimensional drawing




PL-L 18VV/830/4P Silicon						
	Product	D	D1	С		
	PL-L 18W/830/4P	39.0 mm	18.0 mm	226.6 mm		

2G11, 4P



Photometric data





© 2015 Philips Lighting Holding B.V. All rights reserved.

Specifications are subject to change without notice. Trademarks are the property of Koninklijke Philips N.V. (Royal Philips) or their respective owners.

www.philips.com/lighting