

SUPPLEMENTAL BRAKE ALERT PROGRAMMING GUIDE

THESE INSTRUCTIONS PROVIDE SUPPLEMENTAL INFORMATION FOR TAIL LIGHTS WITH THE SECOND GENERATION PROGRAMMING INTERFACE "PI2" WHICH FEATURES 10 USER-SELECTABLE BRAKE ALERT PATTERNS!

SELECTING FROM THE DIFFERENT BRAKE ALERT PATTERNS IS ACHIEVED BY ACCESSING THE PROGRAMMING INTERFACE AS DESCRIBED IN THE INSTALLATION INSTRUCTIONS THAT SHIPPED WITH YOUR TAIL LIGHT, AND ARE DOWNLOADABLE ON THE RESPECTIVE PRODUCT PAGE AT WWW.CUSTOMLED.COM.

THE FOLLOWING TABLE CONTAINS DESCRIPTIONS OF THE INDIVIDUAL BRAKE ALERT PATTERNS THAT ARE USER-SELECTABLE THROUGH THE PROGRAMMING INTERFACE.

| PATTERN NUMBER | BRAKE ALERT PATTERN DESCRIPTION |
|----------------|---|
| 1 | FOUR FLASHES, THEN SOLID |
| 2 | FOUR FLASHES, SOLID FOR 3 SECONDS, REPEAT |
| 3 | SEVEN FLASHES, THEN SOLID |
| 4 | SEVEN FLASHES, SOLID FOR 3 SECONDS, REPEAT |
| 5 | QUAD STROBE, SOLID FOR 1 SECOND, QUAD STROBE, THEN SOLID |
| 6 | QUAD STROBE, SOLID FOR 1 SECOND, QUAD STROBE, SOLID FOR 3 SECONDS, REPEAT |
| 7 | STROBE MODE CYCLE (ONLY RED), THEN SOLID |
| 8 | STROBE MODE CYCLE (ONLY RED), SOLID 3 SECONDS, REPEAT |
| 9 | FACTORY DEFAULT: 4 QUICK STROBES, THEN SOLID |
| 10 | 10 QUICK STROBES, THEN SOLID |
| 11 | CONSTANT STROBES (AS LONG AS BRAKES ARE APPLIED) |
| 12 | NO BRAKE ALERT, SOLID RED |