

Black Crow Studios Radical in Sage Panel A Installation Tips



Panel Size: 53"w x 120"h

Horiz Repeat: 26.5"

Vert Repeat: 21"

- We **strongly** recommend hiring a professional wallpaper installer to install the panels.
- We suggest using Roman Pro 870 wallpaper paste (see product list for application)
- Multiple panels are printed on one continuous roll of paper. Be sure that each panel ordered is inspected and accounted for.*
- Trim white space found on sides, top, and bottom of each panel before installation.
- There is no overlap between panels. Install each panel edge-to-edge.

*If flaws are found in the print, please contact Black Crow Studios immediately at (562) 628-8539 **before** installation. Black Crow Studios is not responsible once paper is adhered to the wall.

BLACK CROW STUDIOS

RECOMMENDED INSTALLATION PRODUCTS

PRIMER

Applying primer before installing wall covering will help seal the walls, protect from moisture, and prevent the walls from soaking in adhesive.

New walls should be primed with a high quality acrylic or latex wall covering primer. An oil-based primer may be used in areas with high water traffic. If an oil-based primer exists otherwise, always apply a coat of acrylic or latex primer before installing wall covering.

PREFERRED PRIMER PRODUCTS:

ROMAN PRO-977 - All purpose pigmented acrylic primer/sealer. Particularly good for bare drywall and promotes strippability. Can be used on most surfaces.

ROMAN PRO-935 - Premium clear acrylic primer that promotes ultimate adhesion for difficult surfaces.

ROMAN ECO-988 - Pigmented primer for use in high humidity areas where mold or mildew can occur and permeability is a factor. May contribute to awarding LEED points.

PREFERRED ADHESIVE PRODUCTS:

ROMAN PRO-870 - Commercial grade clear adhesive that promotes strippability over bare drywall.

ROMAN PRO-838 - Cost effective commercial grade clear adhesive designed for contractors.

ROMAN ECO-888 - Clear wallpaper adhesive for use in high humidity areas where mold or mildew can occur and permeability is required. May contribute to awarding LEED points.

