PENDANTS:	one
MOUNTING:	metal mounting plate 115mm (4.5") in diameter
LAMPING:	1.5w LED or 10w xenon
INSTALLATION:	threaded on - wall or ceiling mount
MATERIALS:	blown glass, stainless steel hardware, electrical components, silicone gasket, metal mounting plate
WEIGHT:	approx. 2.7kg (6lb)
POWER SUPPLIES:	remote mounted (power supply housed within junction box). Power supplies included

DESCRIPTION

The 'sp' designation in this variation on the 73 refers to it being surface-mounted, with a mounting plate large enough to cover a standard North American junction box. This surface light has a paintable 115mm (4.5") in diameter mounting plate designed to be mounted on walls as well as ceilings. It is also IP65 designated meaning that the 73sp can be used outdoors and in other wet environments.

The 73 is formed by blowing liquid glass into a folded and highly heat-resistant ceramic fabric vessel. The resulting shape has a formal and textural expression intuitively associated with fabric, which becomes permanent and rigid as it cools. Each 73 is completely unique in proportion, size and shape.

NOTES

+ Purchase replacement lamps online at www.bocci.com/shop/bulbs

+ Unless otherwise noted when ordering, all fixtures will be outfitted to be xenon compatible

+ Unless otherwise specified, a single class 2 power supply will be sent for every 5 xenon fixtures or every 12 LED fixtures

±260 - 400 (10.5" - 15.7")

±75-150 (3"-6")

115 (4.5")

US Patent # D762,323 S
EU Patent # 002633230-0001 - 0003

Made in Vancouver, Canada

Vancouver
sales@bocci.com
www.bocci.com

Berlin
europe@bocci.com
www.bocci.com

CE

c(UL)us
LISTED
LOW VOLTAGE LUMINAIRE
E476186

(WET LOCATION)
SURFACE LIGHT - PAINTABLE LARGE PLATE

73sp PRODUCT SPECIFICATION

approx. 2.7kg (6lb)

BOCCI

1

Directly mounted to a junction box.

Note: Up to 5 surface mounted lights may be connected to a single power supply.

Xenon (110V) or LED: connect the black wire to live wire and white wire to neutral wire.

Xenon (230V): connect black wire to brown wire and white wire to blue wire.

2

Join power supply wiring to cover plate wiring using connectors provided.

Tuck wiring into wall opening.

Peal back the silicone ring to affix the cover plate with fasteners provided. To achieve the optimal waterproof seal, the silicon ring should completely cover the fasteners.

Turn power to fixture on.

Bocci LED or xenon lamps included.

Plug the lamp into the socket. Ensure power to lamp is working correctly.

Note: when using a dimmer use only low voltage electronic dimmer.

3

Paint over the cover plate to match the wall finish.

Note: as an option, drywall putty or paintable silicone can be used to smooth the transition between the edge of the cover plate and the wall. Use paintable silicone for outdoor installation.

4

Attach the attachment plate with fasteners provided.

5

Gently thread glass pendant onto back plate.

6

Clean fingerprints from surfaces.

For additional assistance, please contact Bocci:

Vancouver
sales@bocci.com
www.bocci.com

Berlin
europe@bocci.com
www.bocci.com

US Patent # D762,323 S
EU Patent # 002633230-0001
- 0003

Made in Vancouver, Canada

LOW VOLTAGE LUMINAIRE
E476186

SURFACE LIGHT - PAINTABLE LARGE PLATE

73sp PRODUCT INSTALLATION INSTRUCTIONS

BOCCI