

m o o o i

Non Random

BERTJAN POT




Old ladies call them neatly coiled balls of yarn, Kids talk about soap bubbles hanging from lightbulbs. Some say they are there to light up Arabian nights, Moooi says they're Non Random Lights.

Detailing



Non Random does not shine a random light: the production of its shape is, unlike the Random Light, completely mechanically pre-programmed.

Colours



Black

White

Non Random / Non Random D48

Dimensions

48cm | 18.9"



Product

WIDTH 48cm | 18.9"

HEIGHT 54cm | 21.3"

DEPTH 48cm | 18.9"

DIAMETER 48cm | 18.9"

WEIGHT NETTO 1.5kg | 3.31lbs

Packaging

WIDTH 55cm | 21.7"

HEIGHT 63cm | 24.8"

CUBAGE 0.19m³ | 6.73ft³

LENGTH 55cm | 21.7"

WEIGHT 3.7kg | 8.16lbs

Technical CCC

MATERIAL

Sphere from fiberglass with epoxy resin, powder coated aluminium cap, anodized aluminium reflector

ENERGY LABEL

A++ to E

LIGHTSOURCE TYPE

Incandescent

SHAPE

Globe

FREQUENCY

50/60

LAMPHOLDER

E27

CABLE LENGTH

400cm | 157.5"; 1000cm | 393.7"

LIGHT DIRECTION

All directions

INSTALLATION REQUIRED

Yes

NUMBER OF LIGHTSOURCES

1

INPUT VOLTAGE

220-240V

MAX POWER CONSUMPTION

60W

RECOMMENDED LIGHTSOURCE

CABLE COLOUR

Black

CANOPY

Pebble, Pebble II Black, ABS, Pebble II White, ABS

DIMMING & LIGHTING CONTROL

Mains dimmable with compatible light source

See last page for more information about the dimming possibilities.

Technical CE

MATERIAL

Sphere from fiberglass with epoxy resin, powder coated aluminium cap, anodized aluminium reflector

ENERGY LABEL

A++ to E

LIGHTSOURCE TYPE

Incandescent

SHAPE

Globe

FREQUENCY

50/60

LAMPHOLDER

E27

CABLE LENGTH

400cm | 157.5"; 1000cm | 393.7"

LIGHT DIRECTION

All directions

INSTALLATION REQUIRED

Yes

NUMBER OF LIGHTSOURCES

1

INPUT VOLTAGE

220-240V

MAX POWER CONSUMPTION

60W

RECOMMENDED LIGHTSOURCE**CABLE COLOUR**

Black

CANOPY

Pebble, Pebble II Black, ABS, Pebble II White, ABS

DIMMING & LIGHTING CONTROL

Mains dimmable with compatible light source

See last page for more information about the dimming possibilities.



*Technical UL***MATERIAL**

Sphere from fiberglass with epoxy resin, powder coated aluminium cap, anodized aluminium reflector

ENERGY LABEL

A++ to E

LIGHTSOURCE TYPE

Incandescent

SHAPE

Globe

FREQUENCY

50/60

LAMPHOLDER

E26

CABLE LENGTH

400cm | 157.5"; 1000cm | 393.7"

LIGHT DIRECTION

All directions

INSTALLATION REQUIRED

Yes

NUMBER OF LIGHTSOURCES

1

INPUT VOLTAGE

110-130V

MAX POWER CONSUMPTION

60W

CABLE COLOUR

Black

CANOPY

Chrome Canopy

DIMMING & LIGHTING CONTROL

Mains dimmable with compatible light source



See last page for more information about the dimming possibilities.



Non Random / Non Random D71

Dimensions

71cm | 28"



Product

WIDTH 71cm | 28"
HEIGHT 70cm | 27.6"
DEPTH 71cm | 28"
DIAMETER 71cm | 28"
WEIGHT NETTO 1.5kg | 3.31lbs

Packaging

WIDTH 75cm | 29.5"
HEIGHT 82cm | 32.3"
CUBAGE 0.46m³ | 16.29ft³
LENGTH 75cm | 29.5"
WEIGHT 6kg | 13.23lbs

Technical CCC

MATERIAL

Sphere from fiberglass with epoxy resin, powder coated aluminium cap, anodized aluminium reflector

ENERGY LABEL

A++ to E

LIGHTSOURCE TYPE

Incandescent

SHAPE

Globe

FREQUENCY

50/60

LAMPHOLDER

E27

CABLE LENGTH

400cm | 157.5"; 1000cm | 393.7"

LIGHT DIRECTION

All directions

INSTALLATION REQUIRED

Yes

NUMBER OF LIGHTSOURCES

1

INPUT VOLTAGE

220-240V

MAX POWER CONSUMPTION

60W

RECOMMENDED LIGHTSOURCE

CABLE COLOUR

Black

CANOPY

Pebble, Pebble II Black, ABS, Pebble II White, ABS

DIMMING & LIGHTING CONTROL

Mains dimmable with compatible light source

See last page for more information about the dimming possibilities.

Technical CE

MATERIAL

Sphere from fiberglass with epoxy resin, powder coated aluminium cap, anodized aluminium reflector

ENERGY LABEL

A++ to E

LIGHTSOURCE TYPE

Incandescent

SHAPE

Globe

FREQUENCY

50/60

LAMPHOLDER

E27

CABLE LENGTH

400cm | 157.5"; 1000cm | 393.7"

LIGHT DIRECTION

All directions

INSTALLATION REQUIRED

Yes

NUMBER OF LIGHTSOURCES

1

INPUT VOLTAGE

220-240V

MAX POWER CONSUMPTION

60W

RECOMMENDED LIGHTSOURCE**CABLE COLOUR**

Black

CANOPY

Pebble, Pebble II Black, ABS, Pebble II White, ABS

DIMMING & LIGHTING CONTROL

Mains dimmable with compatible light source

See last page for more information about the dimming possibilities.



*Technical UL***MATERIAL**

Sphere from fiberglass with epoxy resin, powder coated aluminium cap, anodized aluminium reflector

ENERGY LABEL

A++ to E

LIGHTSOURCE TYPE

Incandescent

SHAPE

Globe

FREQUENCY

50/60

LAMPHOLDER

E26

CABLE LENGTH

400cm | 157.5"; 1000cm | 393.7"

LIGHT DIRECTION

All directions

INSTALLATION REQUIRED

Yes

NUMBER OF LIGHTSOURCES

1

INPUT VOLTAGE

110-130V

MAX POWER CONSUMPTION

60W

CABLE COLOUR

Black

CANOPY

Chrome Canopy

DIMMING & LIGHTING CONTROL

Mains dimmable with compatible light source

See last page for more information about the dimming possibilities.



Dimming & Lighting Control

Mains dimmable with compatible light source

Compatible models: Non Random D48 CE, Non Random D48 UL, Non Random D71 CE, Non Random D71 UL
