

Random Floor Lamp II

BERTJAN POT




A floor lamp is one of the most versatile lighting solutions to have in your home. Especially one that diffuses light in all directions, lighting up every dark corner. The Random Floor Lamp II holds the same simplicity and lightness as the rest of its family members. Beautifully transparent and 'light'.

Detailing



Because of how they're made, every Random Light is unique and never completely round.

Colours




Black

White

Random Floor Lamp II / Medium Ball

Dimensions

Ø80cm | 31.5"



Product

WIDTH 80cm | 31.5"
HEIGHT 80cm | 31.5"
DEPTH 80cm | 31.5"
DIAMETER 80cm | 31.5"
WEIGHT NETTO 0.1kg | 0.22lbs

Packaging

WIDTH 87cm | 34.3"
HEIGHT 88cm | 34.6"
CUBAGE 0.67m³ | 23.52ft³
LENGTH 87cm | 34.3"
WEIGHT 7kg | 15.43lbs

Technical


MATERIAL

Sphere from fiberglass with epoxy resin, powder coated steel base

Random Floor Lamp II / Medium Base

Dimensions

Ø80cm | 31.5"



Ø202cm | 79.5"

Product

WIDTH 80cm | 31.5"
HEIGHT 202cm | 79.5"
DEPTH 80cm | 31.5"
DIAMETER 80cm | 31.5"
WEIGHT NETTO 6.7kg | 14.77lbs

Packaging

WIDTH 42cm | 16.5"
HEIGHT 215cm | 84.6"
CUBAGE 0.38m³ | 13.39ft³
LENGTH 42cm | 16.5"
WEIGHT 10.5kg | 23.15lbs

Technical CE

MATERIAL

Sphere from fiberglass with epoxy resin, powder coated steel base

ENERGY LABEL

A++ to E

LIGHTSOURCE TYPE

Incandescent

LIGHTSOURCE INCLUDED

Yes

DIAMETER SHADE

80cm | 31.5"

FREQUENCY

50/60

LAMPHOLDER

E27

LIFETIME

50000 hours

PLUG TYPE

Europlug (Type-C)

SWITCH

In line slide dimmer with on/off switch

CRI

90

LIGHT OUTPUT

800 lm

EFFICIENCY

32 lm/W

NUMBER OF LIGHTSOURCES

1

INPUT VOLTAGE

220-240V

MAX POWER CONSUMPTION

25W

RECOMMENDED LIGHTSOURCE

25W MAX type G, 10W LED light included

CABLE COLOUR

Black

CABLE LENGTH

300cm | 118.1"

COLOUR TEMPERATURE

2700 K

LIGHT DIRECTION

All directions

EEI

0.39

DIMMING & LIGHTING CONTROL

Dimmer on power cord

See last page for more information about the dimming possibilities.*Technical UL***MATERIAL**

Sphere from fiberglass with epoxy resin, powder coated steel base

ENERGY LABEL

A++ to E

LIGHTSOURCE TYPE

Incandescent

LIGHTSOURCE INCLUDED

Yes

NUMBER OF LIGHTSOURCES

1

DIAMETER SHADE

80cm | 31.5"

INPUT VOLTAGE

100-120V

FREQUENCY

50/60

MAX POWER CONSUMPTION

25W

LAMPHOLDER

E26

RECOMMENDED LIGHTSOURCE

25W MAX type G, 10W LED light included

LIFETIME

50000 hours

CABLE COLOUR

Black

PLUG TYPE

US plug (Type A)

SWITCH

In line slide dimmer with on/off switch

CRI

90

LIGHT OUTPUT

800 lm

EFFICIENCY

32 lm/W

CABLE LENGTH

300cm | 118.1"

COLOUR TEMPERATURE

2700 K

LIGHT DIRECTION

All directions

EEI

0.39

DIMMING & LIGHTING CONTROL

Dimmer on power cord

See last page for more information about the dimming possibilities.



Random Floor Lamp II / Small Ball

Dimensions

Ø50cm | 19.7"



Product

WIDTH 50cm | 19.7"

HEIGHT 50cm | 19.7"

DEPTH 50cm | 19.7"

DIAMETER 50cm | 19.7"

WEIGHT NETTO 0.1kg | 0.22lbs

Packaging

WIDTH 51cm | 20.1"

HEIGHT 53cm | 20.9"

CUBAGE 0.14m³ | 4.87ft³

LENGTH 51cm | 20.1"

WEIGHT 2kg | 4.4lbs

Technical

MATERIAL

Sphere from fiberglass with epoxy resin, powder coated steel base

Random Floor Lamp II / Small Base

Dimensions

Ø50cm | 19.7"



Ø187cm | 73.6"

Product

WIDTH 50cm | 19.7"

HEIGHT 187cm | 73.6"

DEPTH 50cm | 19.7"

DIAMETER 50cm | 19.7"

WEIGHT NETTO 6.4kg | 14.11lbs

Packaging

WIDTH 42cm | 16.5"

HEIGHT 197cm | 77.6"

CUBAGE 0.35m³ | 12.27ft³

LENGTH 42cm | 16.5"

WEIGHT 9.5kg | 20.94lbs

Technical CE

MATERIAL

Sphere from fiberglass with epoxy resin, powder coated steel base

ENERGY LABEL

A++ to E

LIGHTSOURCE INCLUDED

Yes

DIAMETER SHADE

50cm | 19.7"

FREQUENCY

50/60

LAMPHOLDER

E27

LIFETIME

50000 hours

PLUG TYPE

Europlug (Type-C)

SWITCH

In line slide dimmer with on/off switch

CRI

90

LIGHT OUTPUT

800 lm

LIGHTSOURCE TYPE

Incandescent

NUMBER OF LIGHTSOURCES

1

INPUT VOLTAGE

220-240V

MAX POWER CONSUMPTION

25W

RECOMMENDED LIGHTSOURCE

25W MAX type G, 10W LED light included

CABLE COLOUR

Black

CABLE LENGTH

300cm | 118.1"

COLOUR TEMPERATURE

2700 K

LIGHT DIRECTION

All directions

EEI

0.39

EFFICIENCY

32 lm/W

DIMMING & LIGHTING CONTROL

Dimmer on power cord

See last page for more information about the dimming possibilities.*Technical UL***MATERIAL**

Sphere from fiberglass with epoxy resin, powder coated steel base

ENERGY LABEL

A++ to E

LIGHTSOURCE TYPE

Incandescent

LIGHTSOURCE INCLUDED

Yes

NUMBER OF LIGHTSOURCES

1

DIAMETER SHADE

50cm | 19.7"

INPUT VOLTAGE

100-120V

FREQUENCY

50/60

MAX POWER CONSUMPTION

25W

LAMPHOLDER

E26

RECOMMENDED LIGHTSOURCE

25W MAX type C, 10W LED light included

LIFETIME

50000 hours

CABLE COLOUR

Black

PLUG TYPE

US plug (Type A)

CABLE LENGTH

300cm | 118.1"

SWITCH

In line slide dimmer with on/off switch

COLOUR TEMPERATURE

2700 K

CRI

90

LIGHT DIRECTION

All directions

LIGHT OUTPUT

800 lm

EEI

0.39

EFFICIENCY

32 lm/W

DIMMING & LIGHTING CONTROL

Dimmer on power cord

See last page for more information about the dimming possibilities.

Dimming & Lighting Control

Dimmer on power cord

Compatible models: Medium Base CE, Medium Base UL UL, Small Base CE CE, Small Base UL UL
