FLOS Ktribe F2 (Halogen), Transparent - Specification Sheet by Philippe Starck, 2007

| Mounting | Free Standing |
|-----------------------------------|--|
| Lamp (Bulb) Description | 1 x 150W T-10 Medium Frosted Halogen (Included) |
| Environment | Indoor - Dry Location |
| Dimming | Dimmable |
| Finish | Transparent |
| Technical and Product Description | KTRIBE F2 floor lamp providing diffused lighting. Base, rod support and diffuse support in die-cast, polished and chrome-plated Zamak alloy. Rod in polishe aluminum. Injection-molded PC (polycarbonate) opal inner diffuser and suppor for the lamp-holder. Outer diffusers in transparent PMM (polymethylmethacrylate), silver or bronze on the inner surface, by vacuu |

120

IP20



| Voltage | |
|-----------|--|
| Switching | |

IP Rating

Physical

Cord Length (inches) Construction Material Weight

79" - Black Aluminum, Plastic 14.70 lbs

0-100% dimmer installed on the cord

aluminum coating. Injection-molded PC (polycarbonate) upper ring, completely


transparent, or transparent brown for the outer bronze diffuser.





FU630500 Transparent

Dimensional Image



Certifications



Lamping (Bulb)



150W T-10 Medium Frosted Halogen

Lamping (Bulb)



LED018 PRO-T38LED 14W 120V E26 2700K DIMM - 1800Im - CRI80 Additional

Lamping (Bulb)



LED031 PRO-T38LED 14W 120V E26 3000K Dimmable - 1800lm - CRI80- Additional