

**Britemax Pro Max**

Version number: GHS 1.0

Date of compilation: 2016-04-19

**SECTION 1: Identification****1.1 Product identifier**Trade name **Britemax Pro Max****1.2 Relevant identified uses of the substance or mixture and uses advised against**

Relevant identified uses Vehicle polishing compound

**1.3 Details of the supplier of the safety data sheet**

Transco Blanx Ltd. t/a Britemax  
Unit 18 Lambs Business Park  
Terracotta Road  
South Godstone  
Surrey  
RH9 8LJ  
United Kingdom  
Tel: +44 (0)1342 893015  
sales@britemax.co.uk

**1.4 Emergency telephone number**

Emergency information service USA 1.800.535.5053, INTL 1.352.323.3500

**SECTION 2: Hazard(s) identification****2.1 Classification of the substance or mixture**

Classification acc. to OSHA "Hazard Communication Standard" (29 CFR 1910.1200)

Section	Hazard class	Category	Hazard class and category	Hazard statement
A.3	serious eye damage/eye irritation	2	Eye Irrit. 2	H319
A.4S	skin sensitization	1	Skin Sens. 1	H317
A.10	aspiration hazard	1	Asp. Tox. 1	H304

For full text of abbreviations: see SECTION 16.

**2.2 Label elements**

Labelling acc. to OSHA "Hazard Communication Standard" (29 CFR 1910.1200)

- Signal word danger

- Pictograms

GHS07, GHS08



- Hazard statements

H304 May be fatal if swallowed and enters airways.  
H317 May cause an allergic skin reaction.  
H319 Causes serious eye irritation.

- Precautionary statements

P261 Avoid breathing dust/fume/gas/mist/vapors/spray.  
P264 Wash thoroughly after handling.  
P272 Contaminated work clothing must not be allowed out of the workplace.  
P280 Wear protective gloves/eye protection/face protection.  
P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/doctor/physician.  
P302+P352 IF ON SKIN: Wash with plenty of water.  
P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

## Britemax Pro Max

Version number: GHS 1.0

Date of compilation: 2016-04-19

### - Precautionary statements

P321	Specific treatment (see on this label).
P331	Do NOT induce vomiting.
P333+P313	If skin irritation or rash occurs: Get medical advice/attention.
P337+P313	If eye irritation persists: Get medical advice/attention.
P362+P364	Take off contaminated clothing and wash it before reuse.
P405	Store locked up.
P501	Dispose of contents/container in accordance with local/regional/national/international regulations.

### - Hazardous ingredients for labelling

Distillates (petroleum), hydrotreated light, CMIT/MIT mixture

### 2.3 Other hazards

Special danger of slipping by leaking/spilling product.







## SECTION 3: Composition/information on ingredients

### 3.1 Substances

Not relevant (mixture)

### 3.2 Mixtures

Description of the mixture

Name of substance	Identifier	Wt%	Classification acc. to GHS	Pictograms
Distillates (petroleum), hydrotreated light	CAS No 64742-47-8	10 - < 25	Flam. Liq. 4 / H227 Asp. Tox. 1 / H304	
Alcohols, C9-11 ethoxylated	CAS No 68439-46-3	1 - < 5	Acute Tox. 4 / H302 Acute Tox. 4 / H312 Eye Dam. 1 / H318	 
CMIT/MIT mixture	CAS No 55965-84-9	< 1	Acute Tox. 3 / H301 Acute Tox. 3 / H311 Acute Tox. 3 / H331 Skin Corr. 1B / H314 Eye Dam. 1 / H318 Skin Sens. 1 / H317	  

For full text of abbreviations: see SECTION 16.

## SECTION 4: First-aid measures

### 4.1 Description of first-aid measures

#### General notes

Do not leave affected person unattended. Remove victim out of the danger area. Keep affected person warm, still and covered. Take off immediately all contaminated clothing. In all cases of doubt, or when symptoms persist, seek medical advice. In case of unconsciousness place person in the recovery position. Never give anything by mouth.

#### Following inhalation

If breathing is irregular or stopped, immediately seek medical assistance and start first aid actions. Provide fresh air.

#### Following skin contact

Wash with plenty of soap and water.

**Britemax Pro Max**

Version number: GHS 1.0

Date of compilation: 2016-04-19

## Following eye contact

Remove contact lenses, if present and easy to do. Continue rinsing. Irrigate copiously with clean, fresh water for at least 10 minutes, holding the eyelids apart.

## Following ingestion

Rinse mouth with water (only if the person is conscious). Do NOT induce vomiting.

**4.2 Most important symptoms and effects, both acute and delayed**

Symptoms and effects are not known to date.

**4.3 Indication of any immediate medical attention and special treatment needed**

none

**SECTION 5: Fire-fighting measures****5.1 Extinguishing media**

## Suitable extinguishing media

Water spray, BC-powder, Carbon dioxide (CO<sub>2</sub>)

## Unsuitable extinguishing media

Water jet

**5.2 Special hazards arising from the substance or mixture**

## Hazardous combustion products

Nitrogen oxides (NO<sub>x</sub>)

**5.3 Advice for firefighters**

In case of fire and/or explosion do not breathe fumes. Co-ordinate firefighting measures to the fire surroundings. Do not allow firefighting water to enter drains or water courses. Collect contaminated firefighting water separately. Fight fire with normal precautions from a reasonable distance.

**SECTION 6: Accidental release measures****6.1 Personal precautions, protective equipment and emergency procedures**

## For non-emergency personnel

Remove persons to safety.

## For emergency responders

Wear breathing apparatus if exposed to vapors/dust/aerosols/gases.

**6.2 Environmental precautions**

Keep away from drains, surface and ground water. Retain contaminated washing water and dispose it.

**6.3 Methods and material for containment and cleaning up**

## Advices on how to contain a spill

Covering of drains

## Advices on how to clean up a spill

Wipe up with absorbent material (e.g. cloth, fleece). Collect spillage: Sawdust, Kieselgur (diatomite), Sand, Universal binder

## Appropriate containment techniques

Use of adsorbent materials.

## Other information relating to spills and releases

Place in appropriate containers for disposal. Ventilate affected area.

## Britemax Pro Max

Version number: GHS 1.0

Date of compilation: 2016-04-19

### 6.4 Reference to other sections

Hazardous combustion products: see section 5. Personal precautions: see section 8. Incompatible materials: see section 10. Disposal considerations: see section 13.

## SECTION 7: Handling and storage

### 7.1 Precautions for safe handling

Recommendations

- Measures to prevent fire as well as aerosol and dust generation  
Use local and general ventilation. Use only in well-ventilated areas.

Advice on general occupational hygiene

Wash hands after use. Do not to eat, drink and smoke in work areas. Remove contaminated clothing and protective equipment before entering eating areas. Never keep food or drink in the vicinity of chemicals. Never place chemicals in containers that are normally used for food or drink. Keep away from food, drink and animal feedingstuffs.

### 7.2 Conditions for safe storage, including any incompatibilities

Control of the effects

Protect against external exposure, such as  
Frost

### 7.3 Specific end use(s)

See section 16 for a general overview.

## SECTION 8: Exposure controls/personal protection

### 8.1 Control parameters

Occupational exposure limit values (Workplace Exposure Limits)								
Country	Name of agent	CAS No	Identifier	TWA [ppm]	TWA [mg/m <sup>3</sup> ]	STEL [ppm]	STEL [mg/m <sup>3</sup> ]	Source
US	alpha-alumina	1344-28-1	PEL		15			29 CFR OSHA
US	alpha-alumina	1344-28-1	PEL		5			29 CFR OSHA
US	glycerin (mist)	56-81-5	PEL		15			29 CFR OSHA
US	glycerin (mist)	56-81-5	PEL		5			29 CFR OSHA

Notation

STEL short-term exposure limit: a limit value above which exposure should not occur and which is related to a 15-minute period unless otherwise specified

TWA time-weighted average (long-term exposure limit): measured or calculated in relation to a reference period of 8 hours time-weighted average

Relevant DNELs of components of the mixture						
Name of substance	CAS No	End-point	Threshold level	Protection goal, route of exposure	Used in	Exposure time
Alcohols, C9-11 ethoxylated	68439-46-3	DNEL	2,080 mg/kg	human, dermal	worker (industry)	chronic - systemic effects
Alcohols, C9-11 ethoxylated	68439-46-3	DNEL	294 mg/m <sup>3</sup>	human, inhalatory	worker (industry)	chronic - systemic effects

## Britemax Pro Max

Version number: GHS 1.0

Date of compilation: 2016-04-19

Relevant PNECs of components of the mixture						
Name of substance	CAS No	End-point	Threshold level	Organism	Environmental compartment	Exposure time
Alcohols, C9-11 ethoxylated	68439-46-3	PNEC	0.1038 mg/l	aquatic organisms	freshwater	short-term (single instance)
Alcohols, C9-11 ethoxylated	68439-46-3	PNEC	0.1038 mg/l	aquatic organisms	marine water	short-term (single instance)
Alcohols, C9-11 ethoxylated	68439-46-3	PNEC	1.4 mg/l	microorganisms	sewage treatment plant (STP)	short-term (single instance)
Alcohols, C9-11 ethoxylated	68439-46-3	PNEC	13.7 mg/kg	benthic organisms	sediment	short-term (single instance)
Alcohols, C9-11 ethoxylated	68439-46-3	PNEC	13.7 mg/kg	pelagic organisms	sediment	short-term (single instance)
Alcohols, C9-11 ethoxylated	68439-46-3	PNEC	1 mg/kg	terrestrial organisms	soil	short-term (single instance)
Alcohols, C9-11 ethoxylated	68439-46-3	PNEC	0.014 mg/l	aquatic organisms	water	continuous

### 8.2 Exposure controls

#### Appropriate engineering controls

General ventilation.

#### Individual protection measures (personal protective equipment)

##### Eye/face protection

Wear eye/face protection.

##### Skin protection

##### - Hand protection

Wear suitable gloves. Chemical protection gloves are suitable, which are tested according to EN 374. Check leak-tightness/impermeability prior to use. In the case of wanting to use the gloves again, clean them before taking off and air them well. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

##### - Other protection measures

Take recovery periods for skin regeneration. Preventive skin protection (barrier creams/ointments) is recommended. Wash hands thoroughly after handling.

##### Respiratory protection

In case of inadequate ventilation wear respiratory protection.

##### Environmental exposure controls

Use appropriate container to avoid environmental contamination. Keep away from drains, surface and ground water.

**Britemax Pro Max**

Version number: GHS 1.0

Date of compilation: 2016-04-19

**SECTION 9: Physical and chemical properties****9.1 Information on basic physical and chemical properties****Appearance**

Physical state	liquid (viscous)
Color	off-white
Odor	fruity

**Other safety parameters**

pH (value)	8 - 8.5
Melting point/freezing point	not determined
Initial boiling point and boiling range	100 °C
Flash point	>100 °C at 101.3 kPa >212 °F at 1 atm
Evaporation rate	not determined
Flammability (solid, gas)	not relevant (fluid)

**Explosive limits**

- Lower explosion limit (LEL)	2.7 vol%
- Upper explosion limit (UEL)	19 vol%

Vapor pressure	31.69 hPa at 25 °C
Density	0.4036 g/ml
Vapor density	this information is not available
Relative density	1.28 (water = 1)
Solubility(ies)	not determined

**Partition coefficient**

- n-octanol/water (log KOW)	this information is not available
-----------------------------	-----------------------------------

Auto-ignition temperature	311 °C
Viscosity	not determined
Explosive properties	none
Oxidizing properties	none

## Britemax Pro Max

Version number: GHS 1.0

Date of compilation: 2016-04-19

### 9.2 Other information

Solvent content	64.21 %
Solid content	35.78 %
Temperature class (USA, acc. to NEC 500)	T2 (maximum permissible surface temperature on the equipment: 300° C)

## SECTION 10: Stability and reactivity

### 10.1 Reactivity

Concerning incompatibility: see below "Conditions to avoid" and "Incompatible materials".

### 10.2 Chemical stability

See below "Conditions to avoid".

### 10.3 Possibility of hazardous reactions

No known hazardous reactions.

### 10.4 Conditions to avoid

There are no specific conditions known which have to be avoided.

### 10.5 Incompatible materials

Oxidizers

### 10.6 Hazardous decomposition products

Reasonably anticipated hazardous decomposition products produced as a result of use, storage, spill and heating are not known. Hazardous combustion products: see section 5.

## SECTION 11: Toxicological information

### 11.1 Information on toxicological effects

Test data are not available for the complete mixture.

#### Classification procedure

The method for classification of the mixture is based on ingredients of the mixture (additivity formula).

#### Classification acc. to OSHA "Hazard Communication Standard" (29 CFR 1910.1200)

#### Acute toxicity

Shall not be classified as acutely toxic.

Acute toxicity estimate (ATE) of components of the mixture			
Name of substance	CAS No	Exposure route	ATE
Alcohols, C9-11 ethoxylated	68439-46-3	oral	1,200
Alcohols, C9-11 ethoxylated	68439-46-3	dermal	2,000
CMIT/MIT mixture	55965-84-9	oral	100
CMIT/MIT mixture	55965-84-9	dermal	300
CMIT/MIT mixture	55965-84-9	inhalation: vapor	3

#### Skin corrosion/irritation

Shall not be classified as corrosive/irritant to skin.

**Britemax Pro Max**

Version number: GHS 1.0

Date of compilation: 2016-04-19

**Serious eye damage/eye irritation**

Causes serious eye irritation.

**Respiratory or skin sensitization**

May cause an allergic skin reaction.

**Germ cell mutagenicity**

Shall not be classified as germ cell mutagenic.

**Carcinogenicity**

Shall not be classified as carcinogenic.

**Reproductive toxicity**

Shall not be classified as a reproductive toxicant.

**Specific target organ toxicity - single exposure**

Shall not be classified as a specific target organ toxicant (single exposure).

**Specific target organ toxicity - repeated exposure**

Shall not be classified as a specific target organ toxicant (repeated exposure).

**Aspiration hazard**

May be fatal if swallowed and enters airways.

**SECTION 12: Ecological information****12.1 Toxicity**

Shall not be classified as hazardous to the aquatic environment.

**12.2 Persistence and degradability**

Data are not available.

**12.3 Bioaccumulative potential**

Data are not available.

**12.4 Mobility in soil**

Data are not available.

**12.5 Results of PBT and vPvB assessment**

Data are not available.

**12.6 Other adverse effects****SECTION 13: Disposal considerations****13.1 Waste treatment methods****Sewage disposal-relevant information**

Do not empty into drains. Avoid release to the environment. Refer to special instructions/safety data sheets.

**Waste treatment of containers/packages**

Completely emptied packages can be recycled. Handle contaminated packages in the same way as the substance itself.

**Relevant provisions relating to waste****List of wastes**

Not assigned



### Remarks

Please consider the relevant national or regional provisions. Waste shall be separated into the categories that can be handled separately by the local or national waste management facilities.

### SECTION 14: Transport information

- 14.1 UN number** not subject to transport regulations
- 14.2 UN proper shipping name** not relevant
- 14.3 Transport hazard class(es)**  
Class -
- 14.4 Packing group** not relevant
- 14.5 Environmental hazards**
- 14.6 Special precautions for user**  
There is no additional information.
- 14.7 Transport in bulk according to Annex II of MARPOL and the IBC Code**  
The cargo is not intended to be carried in bulk.

### SECTION 15: Regulatory information

**15.1 Safety, health and environmental regulations specific for the product in question**

**National regulations (United States)**

**SARA TITLE III (Superfund Amendment and Reauthorization Act)**

- List of Extremely Hazardous Substances (40 CFR 355) (EPCRA Section 302 and 304)  
none of the ingredients are listed

**California Environmental Protection Agency (Cal/EPA): Proposition 65 Chemicals known to the State to cause cancer or reproductive toxicity** none of the ingredients are listed

**Industry or sector specific available guidance(s)**

**NPCA-HMIS® III**

Hazardous Materials Identification System. American Coatings Association.

Category	Rating	Description
Chronic	*	chronic (long-term) health effects may result from repeated overexposure
Health	2	temporary or minor injury may occur
Flammability	1	material that must be preheated before ignition can occur
Physical hazard	0	material that is normally stable, even under fire conditions, and will not react with water, polymerize, decompose, condense, or self-react. Non-explosive
Personal protective equipment	-	

**NFPA® 704**

National Fire Protection Association: Standard System for the Identification of the Hazards of Materials for Emergency Response (United States).

## Britemax Pro Max

Version number: GHS 1.0

Date of compilation: 2016-04-19

Category	Degree of hazard	Description
Flammability	1	material that must be preheated before ignition can occur
Health	0	material that, under emergency conditions, would offer no hazard beyond that of ordinary combustible material
Instability	0	material that is normally stable, even under fire conditions
Special hazard		

### 15.2 Chemical Safety Assessment

Chemical safety assessments for substances in this mixture were not carried out.

## SECTION 16: Other information, including date of preparation or last revision

### Abbreviations and acronyms

Abbr.	Descriptions of used abbreviations
29 CFR OSHA	29 CFR §1910.1001 - Occupational Safety and Health Standards: Toxic and Hazardous Substances (permissible exposure limits)
49 CFR US DOT	49 CFR § 40 U.S. Department of Transportation
Acute Tox.	acute toxicity
Asp. Tox.	aspiration hazard
ATE	Acute Toxicity Estimate
CAS	Chemical Abstracts Service (service that maintains the most comprehensive list of chemical substances)
DGR	Dangerous Goods Regulations (see IATA/DGR)
DNEL	Derived No-Effect Level
Eye Dam.	seriously damaging to the eye
Eye Irrit.	irritant to the eye
Flam. Liq.	flammable liquid
GHS	"Globally Harmonized System of Classification and Labelling of Chemicals" developed by the United Nations
HMIS	Hazardous Materials Identification System
IATA	International Air Transport Association
IATA/DGR	Dangerous Goods Regulations (DGR) for the air transport (IATA)
IMDG	International Maritime Dangerous Goods Code
MARPOL	International Convention for the Prevention of Pollution from Ships (abbr. of "Marine Pollutant")
NFPA® 704	National Fire Protection Association: Standard System for the Identification of the Hazards of Materials for Emergency Response (United States)
NPCA-HMIS® III	National Paint and Coatings Association: Hazardous Materials Identification System - HMIS® III, Third Edition
OSHA	Occupational Safety and Health Administration (United States)
PBT	Persistent, Bioaccumulative and Toxic
PEL	permissible exposure limit
PNEC	Predicted No-Effect Concentration
ppm	parts per million
RTECS	Registry of Toxic Effects of Chemical Substances (database of NIOSH with toxicological information)

**Britemax Pro Max**

Version number: GHS 1.0

Date of compilation: 2016-04-19

Abbr.	Descriptions of used abbreviations
Skin Corr.	corrosive to skin
Skin Irrit.	irritant to skin
Skin Sens.	skin sensitization
STEL	short-term exposure limit
TWA	time-weighted average
vPvB	very Persistent and very Bioaccumulative

**Key literature references and sources for data**

OSHA Hazard Communication Standard (HCS), 29 CFR 1910.1200.

Transport of dangerous goods by road or rail (49 CFR US DOT). International Maritime Dangerous Goods Code (IMDG). Dangerous Goods Regulations (DGR) for the air transport (IATA).

**Classification procedure**

Physical and chemical properties. The classification is based on tested mixture. Health hazards. Environmental hazards. The method for classification of the mixture is based on ingredients of the mixture (additivity formula).

**List of relevant phrases (code and full text as stated in chapter 2 and 3)**

Code	Text
H227	combustible liquid
H301	toxic if swallowed
H302	harmful if swallowed
H304	may be fatal if swallowed and enters airways
H311	toxic in contact with skin
H312	harmful in contact with skin
H314	causes severe skin burns and eye damage
H317	may cause an allergic skin reaction
H318	causes serious eye damage
H319	causes serious eye irritation
H331	toxic if inhaled

**Disclaimer**

This information is based upon the present state of our knowledge. This SDS has been compiled and is solely intended for this product.