

Briremax Pure Cut

Version number: GHS 1.0

Date of compilation: 2016-04-19

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name **Briremax Pure Cut**

1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses Vehicle polishing compound

1.3 Details of the supplier of the safety data sheet

Transco Blanx Ltd. t/a Briremax
 Unit 18 Lambs Business Park
 Terracotta Road
 South Godstone
 Surrey
 RH9 8LJ
 United Kingdom
 Tel: +44 (0)1342 893015
 sales@briremax.co.uk

1.4 Emergency telephone number

Emergency information service USA 1.800.535.5053, INTL 1.352.323.3500

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification acc. to GHS

Section	Hazard class	Category	Hazard class and category	Hazard statement
3.3	serious eye damage/eye irritation	2	Eye Irrit. 2	H319
3.4S	skin sensitisation	1	Skin Sens. 1	H317
3.10	aspiration hazard	1	Asp. Tox. 1	H304

For full text of abbreviations: see SECTION 16.

2.2 Label elements

Labelling

- Signal word danger

- Pictograms

GHS07, GHS08



- Hazard statements

- H304 May be fatal if swallowed and enters airways.
- H317 May cause an allergic skin reaction.
- H319 Causes serious eye irritation.

- Precautionary statements

- P261 Avoid breathing dust/fume/gas/mist/vapours/spray.
- P264 Wash thoroughly after handling.
- P272 Contaminated work clothing should not be allowed out of the workplace.
- P280 Wear protective gloves/protective clothing/eye protection/face protection.
- P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/doctor/physician.
- P302+P352 IF ON SKIN: Wash with plenty of water.
- P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Britemax Pure Cut

Version number: GHS 1.0

Date of compilation: 2016-04-19

- Precautionary statements

P321	Specific treatment (see on this label).
P331	Do NOT induce vomiting.
P333+P313	If skin irritation or rash occurs: Get medical advice/attention.
P337+P313	If eye irritation persists: Get medical advice/attention.
P362+P364	Take off contaminated clothing and wash it before reuse.
P405	Store locked up.
P501	Dispose of contents/container in accordance with local/regional/national/international regulations.

- Hazardous ingredients for labelling

Distillates (petroleum), hydrotreated light, CMIT/MIT mixture

2.3 Other hazards

Special danger of slipping by leaking/spilling product.





SECTION 3: Composition/information on ingredients

3.1 Substances

Not relevant (mixture)

3.2 Mixtures

Description of the mixture

Name of substance	Identifier	Wt%	Classification acc. to GHS	Pictograms
Distillates (petroleum), hydrotreated light	CAS No 64742-47-8	10 - < 25	Flam. Liq. 4 / H227 Asp. Tox. 1 / H304	
odorless mineral spirits	CAS No 64742-48-9	5 - < 10	Flam. Liq. 3 / H226 Skin Irrit. 2 / H315 STOT SE 3 / H336 Asp. Tox. 1 / H304	
Alcohols, C9-11 ethoxylated	CAS No 68439-46-3	1 - < 5	Acute Tox. 4 / H302 Acute Tox. 4 / H312 Eye Dam. 1 / H318	
CMIT/MIT mixture	CAS No 55965-84-9	< 1	Acute Tox. 3 / H301 Acute Tox. 3 / H311 Acute Tox. 3 / H331 Skin Corr. 1B / H314 Eye Dam. 1 / H318 Skin Sens. 1 / H317	

For full text of abbreviations: see SECTION 16.

Britemax Pure Cut

Version number: GHS 1.0

Date of compilation: 2016-04-19

SECTION 4: First aid measures**4.1 Description of first aid measures**

General notes

Do not leave affected person unattended. Remove victim out of the danger area. Keep affected person warm, still and covered. Take off immediately all contaminated clothing. In all cases of doubt, or when symptoms persist, seek medical advice. In case of unconsciousness place person in the recovery position. Never give anything by mouth.

Following inhalation

If breathing is irregular or stopped, immediately seek medical assistance and start first aid actions. Provide fresh air.

Following skin contact

Wash with plenty of soap and water.

Following eye contact

Remove contact lenses, if present and easy to do. Continue rinsing. Irrigate copiously with clean, fresh water for at least 10 minutes, holding the eyelids apart.

Following ingestion

Rinse mouth with water (only if the person is conscious). Do NOT induce vomiting.

4.2 Most important symptoms and effects, both acute and delayed

Symptoms and effects are not known to date.

4.3 Indication of any immediate medical attention and special treatment needed

none

SECTION 5: Firefighting measures**5.1 Extinguishing media**

Suitable extinguishing media

Water spray, Alcohol resistant foam, BC-powder, Carbon dioxide (CO₂)

Unsuitable extinguishing media

Water jet

5.2 Special hazards arising from the substance or mixture

Hazardous combustion products

Nitrogen oxides (NO_x), Carbon monoxide (CO), Carbon dioxide (CO₂)

5.3 Advice for firefighters

In case of fire and/or explosion do not breathe fumes. Co-ordinate firefighting measures to the fire surroundings. Do not allow firefighting water to enter drains or water courses. Collect contaminated firefighting water separately. Fight fire with normal precautions from a reasonable distance.

SECTION 6: Accidental release measures**6.1 Personal precautions, protective equipment and emergency procedures**

For non-emergency personnel

Remove persons to safety.

For emergency responders

Wear breathing apparatus if exposed to vapours/dust/spray/gases.

Britemax Pure Cut

Version number: GHS 1.0

Date of compilation: 2016-04-19

6.2 Environmental precautions

Keep away from drains, surface and ground water. Retain contaminated washing water and dispose it.

6.3 Methods and material for containment and cleaning up

Advices on how to contain a spill

Covering of drains

Advices on how to clean up a spill

Wipe up with absorbent material (e.g. cloth, fleece). Collect spillage: Sawdust, Kieselgur (diatomite), Sand, Universal binder

Appropriate containment techniques

Use of adsorbent materials.

Other information relating to spills and releases

Place in appropriate containers for disposal. Ventilate affected area.

6.4 Reference to other sections

Hazardous combustion products: see section 5. Personal protective equipment: see section 8. Incompatible materials: see section 10. Disposal considerations: see section 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Recommendations

- Measures to prevent fire as well as aerosol and dust generation

Use local and general ventilation. Use only in well-ventilated areas.

Advice on general occupational hygiene

Wash hands after use. Do not to eat, drink and smoke in work areas. Remove contaminated clothing and protective equipment before entering eating areas. Never keep food or drink in the vicinity of chemicals. Never place chemicals in containers that are normally used for food or drink. Keep away from food, drink and animal feedingsuffs.

7.2 Conditions for safe storage, including any incompatibilities

Control of effects

Protect against external exposure, such as

Frost

7.3 Specific end use(s)

See section 16 for a general overview.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limit values (Workplace Exposure Limits)								
Country	Name of agent	CAS No	Identifier	TWA [ppm]	TWA [mg/m ³]	STEL [ppm]	STEL [mg/m ³]	Source
CA	aluminium, insoluble compounds	1344-28-1	OEL (BC)		1			"BC Regulation"
CA	Aluminum oxide	1344-28-1	PEV/VE A		10			Regulation OHS
CA	Aluminum oxide (Alumina)	1344-28-1	OEL (AB)		10			OHS Code
CA	Glycerin	56-81-5	OEL (BC)		10			"BC Regulation"
CA	Glycerin	56-81-5	OEL (AB)		10			OHS Code
CA	Glycerin	56-81-5	OEL (BC)		3			"BC Regulation"

Britemax Pure Cut

Version number: GHS 1.0

Date of compilation: 2016-04-19

Occupational exposure limit values (Workplace Exposure Limits)								
Country	Name of agent	CAS No	Identifier	TWA [ppm]	TWA [mg/m ³]	STEL [ppm]	STEL [mg/m ³]	Source
CA	Glycerin (mist)	56-81-5	PEV/VE A		10			Regulation OHS
CA	Jet fuels	64742-47-8	OEL (BC)		200			"BC Regulation"

Notation

STEL short-term exposure limit: a limit value above which exposure should not occur and which is related to a 15-minute period unless otherwise specified

TWA time-weighted average (long-term exposure limit): measured or calculated in relation to a reference period of 8 hours time-weighted average

Relevant DNELs of components of the mixture						
Name of substance	CAS No	End-point	Threshold level	Protection goal, route of exposure	Used in	Exposure time
Alcohols, C9-11 ethoxylated	68439-46-3	DNEL	2,080 mg/kg	human, dermal	worker (industry)	chronic - systemic effects
Alcohols, C9-11 ethoxylated	68439-46-3	DNEL	294 mg/m ³	human, inhalatory	worker (industry)	chronic - systemic effects

Relevant PNECs of components of the mixture						
Name of substance	CAS No	End-point	Threshold level	Organism	Environmental compartment	Exposure time
Alcohols, C9-11 ethoxylated	68439-46-3	PNEC	0.1038 mg/l	aquatic organisms	freshwater	short-term (single instance)
Alcohols, C9-11 ethoxylated	68439-46-3	PNEC	0.1038 mg/l	aquatic organisms	marine water	short-term (single instance)
Alcohols, C9-11 ethoxylated	68439-46-3	PNEC	1.4 mg/l	microorganisms	sewage treatment plant (STP)	short-term (single instance)
Alcohols, C9-11 ethoxylated	68439-46-3	PNEC	13.7 mg/kg	benthic organisms	sediments	short-term (single instance)
Alcohols, C9-11 ethoxylated	68439-46-3	PNEC	13.7 mg/kg	pelagic organisms	sediments	short-term (single instance)
Alcohols, C9-11 ethoxylated	68439-46-3	PNEC	1 mg/kg	terrestrial organisms	soil	short-term (single instance)
Alcohols, C9-11 ethoxylated	68439-46-3	PNEC	0.014 mg/l	aquatic organisms	water	continuous

8.2 Exposure controls

Appropriate engineering controls

General ventilation.

Britemax Pure Cut

Version number: GHS 1.0

Date of compilation: 2016-04-19

Individual protection measures (personal protective equipment)

Eye/face protection

Wear eye/face protection.

Skin protection

- Hand protection

Wear suitable gloves. Chemical protection gloves are suitable, which are tested according to EN 374. Check leak-tightness/impermeability prior to use. In the case of wanting to use the gloves again, clean them before taking off and air them well. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

- Other protection measures

Take recovery periods for skin regeneration. Preventive skin protection (barrier creams/ointments) is recommended. Wash hands thoroughly after handling.

Respiratory protection

In case of inadequate ventilation wear respiratory protection.

Environmental exposure controls

Use appropriate container to avoid environmental contamination. Keep away from drains, surface and ground water.

SECTION 9: Physical and chemical properties**9.1 Information on basic physical and chemical properties****Appearance**

Physical state	liquid (viscous)
Colour	yellow
Odour	fruity

Other safety parameters

pH (value)	8 - 8.6 (25 °C)
Melting point/freezing point	not determined
Initial boiling point and boiling range	100 °C
Flash point	>100 °C at 101.3 kPa
Evaporation rate	not determined
Flammability (solid, gas)	not relevant (fluid)

Explosive limits

- Lower explosion limit (LEL)	0.7 vol%
- Upper explosion limit (UEL)	19 vol%
Vapour pressure	31.69 hPa at 25 °C
Density	1.2 - 1.25 g/cm ³ at 25 °C
Vapour density	this information is not available

Britemax Pure Cut

Version number: GHS 1.0

Date of compilation: 2016-04-19

Solubility(ies)

- Water solubility	miscible in any proportion
--------------------	----------------------------

Partition coefficient

- n-octanol/water (log KOW)	this information is not available
-----------------------------	-----------------------------------

Auto-ignition temperature	311 °C
---------------------------	--------

Viscosity	not determined
-----------	----------------

Explosive properties	none
----------------------	------

Oxidising properties	none
----------------------	------

9.2 Other information

Solvent content	64.84 %
-----------------	---------

Solid content	35.16 %
---------------	---------

Temperature class (USA, acc. to NEC 500)	T2 (maximum permissible surface temperature on the equipment: 300 °C)
--	---

SECTION 10: Stability and reactivity**10.1 Reactivity**

Concerning incompatibility: see below "Conditions to avoid" and "Incompatible materials".

10.2 Chemical stability

See below "Conditions to avoid".

10.3 Possibility of hazardous reactions

No known hazardous reactions.

10.4 Conditions to avoid

There are no specific conditions known which have to be avoided.

10.5 Incompatible materials

Oxidisers

10.6 Hazardous decomposition products

Reasonably anticipated hazardous decomposition products produced as a result of use, storage, spill and heating are not known. Hazardous combustion products: see section 5.

Britemax Pure Cut

Version number: GHS 1.0

Date of compilation: 2016-04-19

SECTION 11: Toxicological information**11.1 Information on toxicological effects**

Test data are not available for the complete mixture.

Classification procedure

The method for classification of the mixture is based on ingredients of the mixture (additivity formula).

Classification acc. to GHS**Acute toxicity**

Shall not be classified as acutely toxic.

Acute toxicity estimate (ATE) of components of the mixture			
Name of substance	CAS No	Exposure route	ATE
Alcohols, C9-11 ethoxylated	68439-46-3	oral	1,200
Alcohols, C9-11 ethoxylated	68439-46-3	dermal	2,000
CMIT/MIT mixture	55965-84-9	oral	100
CMIT/MIT mixture	55965-84-9	dermal	300
CMIT/MIT mixture	55965-84-9	inhalation: vapour	3

Skin corrosion/irritation

Shall not be classified as corrosive/irritant to skin.

Serious eye damage/eye irritation

Causes serious eye irritation.

Respiratory or skin sensitisation

May cause an allergic skin reaction.

Germ cell mutagenicity

Shall not be classified as germ cell mutagenic.

Carcinogenicity

Shall not be classified as carcinogenic.

Reproductive toxicity

Shall not be classified as a reproductive toxicant.

Specific target organ toxicity - single exposure

Shall not be classified as a specific target organ toxicant (single exposure).

Specific target organ toxicity - repeated exposure

Shall not be classified as a specific target organ toxicant (repeated exposure).

Aspiration hazard

May be fatal if swallowed and enters airways.

Britemax Pure Cut

Version number: GHS 1.0

Date of compilation: 2016-04-19

SECTION 12: Ecological information**12.1 Toxicity**

Harmful to aquatic life with long lasting effects. Shall not be classified as hazardous to the aquatic environment.

12.2 Persistence and degradability

Data are not available.

12.3 Bioaccumulative potential

Data are not available.

12.4 Mobility in soil

Data are not available.

12.5 Results of PBT and vPvB assessment

Data are not available.

12.6 Other adverse effects**SECTION 13: Disposal considerations****13.1 Waste treatment methods**

Sewage disposal-relevant information

Do not empty into drains. Avoid release to the environment. Refer to special instructions/safety data sheets.

Waste treatment of containers/packages

Completely emptied packages can be recycled. Handle contaminated packages in the same way as the substance itself.

Relevant provisions relating to waste

List of wastes

Not assigned

Remarks

Please consider the relevant national or regional provisions. Waste shall be separated into the categories that can be handled separately by the local or national waste management facilities.

SECTION 14: Transport information

14.1 UN number not subject to transport regulations

14.2 UN proper shipping name not relevant

14.3 Transport hazard class(es)

Class

-

14.4 Packing group not relevant

14.5 Environmental hazards

14.6 Special precautions for user

There is no additional information.

14.7 Transport in bulk according to Annex II of MARPOL and the IBC Code

The cargo is not intended to be carried in bulk.

Britemax Pure Cut

Version number: GHS 1.0

Date of compilation: 2016-04-19

SECTION 15: Regulatory information**15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture****National regulations (United States)****SARA TITLE III (Superfund Amendment and Reauthorization Act)**

- List of Extremely Hazardous Substances (40 CFR 355) (EPCRA Section 302)
none of the ingredients are listed

California Environmental Protection Agency none of the ingredients are listed
(Cal/EPA): Proposition 65 Chemicals known to the State to cause cancer or reproductive toxicity

Industry or sector specific available guidance(s)**NPCA-HMIS® III**

Hazardous Materials Identification System. American Coatings Association.

Category	Rating	Description
Chronic	/	none
Health	2	temporary or minor injury may occur
Flammability	1	material that must be preheated before ignition can occur
Physical hazard	0	material that is normally stable, even under fire conditions, and will not react with water, polymerise, decompose, condense, or self-react. Non-explosive
Personal protective equipment	-	

NFPA® 704

National Fire Protection Association: Standard System for the Identification of the Hazards of Materials for Emergency Response (United States).

Category	Degree of hazard	Description
Flammability	1	material that must be preheated before ignition can occur
Health	0	material that, under emergency conditions, would offer no hazard beyond that of ordinary combustible material
Instability	0	material that is normally stable, even under fire conditions
Special hazard		

15.2 Chemical Safety Assessment

Chemical safety assessments for substances in this mixture were not carried out.

Britemax Pure Cut

Version number: GHS 1.0

Date of compilation: 2016-04-19

SECTION 16: Other information**Abbreviations and acronyms**

Abbr.	Descriptions of used abbreviations
"BC Regulation"	OHS Regulation: Section 5.48 (British Columbia)
Acute Tox.	acute toxicity
Asp. Tox.	aspiration hazard
ATE	Acute Toxicity Estimate
CAS	Chemical Abstracts Service (service that maintains the most comprehensive list of chemical substances)
DGR	Dangerous Goods Regulations (see IATA/DGR)
DNEL	Derived No-Effect Level
Eye Dam.	seriously damaging to the eye
Eye Irrit.	irritant to the eye
Flam. Liq.	flammable liquid
GHS	"Globally Harmonized System of Classification and Labelling of Chemicals" developed by the United Nations
HMIS	Hazardous Materials Identification System
IATA	International Air Transport Association
IATA/DGR	Dangerous Goods Regulations (DGR) for the air transport (IATA)
IMDG	International Maritime Dangerous Goods Code
MARPOL	International Convention for the Prevention of Pollution from Ships (abbr. of "Marine Pollutant")
NFPA® 704	National Fire Protection Association: Standard System for the Identification of the Hazards of Materials for Emergency Response (United States)
NPCA-HMIS® III	National Paint and Coatings Association: Hazardous Materials Identification System - HMIS® III, Third Edition
OHS Code	Occupational Health and Safety Code: Occupational exposure limits for chemical substances (Alberta)
PBT	Persistent, Bioaccumulative and Toxic
PNEC	Predicted No-Effect Concentration
ppm	parts per million
Regulation OHS	Regulation respecting occupational health and safety: Permissible exposure values for airborne contaminants (Quebec)
RTECS	Registry of Toxic Effects of Chemical Substances (database of NIOSH with toxicological information)
Skin Corr.	corrosive to skin
Skin Irrit.	irritant to skin
Skin Sens.	skin sensitisation
STEL	short-term exposure limit
STOT SE	specific target organ toxicity - single exposure
TWA	time-weighted average
vPvB	very Persistent and very Bioaccumulative

Britemax Pure Cut

Version number: GHS 1.0

Date of compilation: 2016-04-19

Key literature references and sources for data

Hazardous Products Regulations (HPR).

UN Recommendations on the Transport of Dangerous Goods. International Maritime Dangerous Goods Code (IMDG).

Dangerous Goods Regulations (DGR) for the air transport (IATA).

Classification procedure

Physical and chemical properties. The classification is based on tested mixture. Health hazards. Environmental hazards. The method for classification of the mixture is based on ingredients of the mixture (additivity formula).

List of relevant phrases (code and full text as stated in chapter 2 and 3)

Code	Text
H226	flammable liquid and vapour
H227	combustible liquid
H301	toxic if swallowed
H302	harmful if swallowed
H304	may be fatal if swallowed and enters airways
H311	toxic in contact with skin
H312	harmful in contact with skin
H314	causes severe skin burns and eye damage
H315	causes skin irritation
H317	may cause an allergic skin reaction
H318	causes serious eye damage
H319	causes serious eye irritation
H331	toxic if inhaled
H336	may cause drowsiness or dizziness

Disclaimer

This information is based upon the present state of our knowledge. This SDS has been compiled and is solely intended for this product.