MATERIAL SAFETY DATA SHEET

PRODUCT: ASI 504

Suppliers Name: American Sealants, Inc. Telephone : (260) 489-0728
Address: 3806 Option Pass Fax: (260) 489-0519

Fort Wayne, IN 46818 Emergency: (800) 535-5053

(Infotrac)

Date Issued: November 2, 2011

Date Revised:

Section 1. Product Name

Product: Silicone Elastomer

Product Classification: One Component Silicone Rubber Compound

Section 2. Composition

Single or Mixture: Mixture

CAS Number	Wt %	Component Name
64742-46-7 17689-77-9	15.0 - 40.0 1.0 - 5.0	Hydotreated Middle Petroleum Distillates Ethyltriacetoxysilane
4253-34-3	1.0 - 5.0	Methyltriacetoxysilane

The above components are considered hazardous as defined in 29 CFR 1910.1200

Section 3. Hazards Identification

Acute Effects

Eye: Direct contact may cause moderate irritation.

Skin: May cause moderate irritation.

Inhalation: Material is not likely to present an inhalation hazard at ambient conditions. However, if material is heated or high vapor concentration is attained, central nervous system depression may occur, which is characterized by drowsiness,

dizziness, confusion or loss of coordination.

Oral: May cause vomiting.

Prolonged/Repeated Exposure Effects

Skin: Repeated or prolonged contact may cause defatting and drying of skin which may result in skin irritation and dermatitis.

Inhalation: No known applicable information.

Oral: No known applicable information.

Signs and Symptoms of Overexposure

No known applicable information.

Medical Conditions Aggravated by Exposure

No known applicable information.



The above listed potential effects of overexposure are based on actual data, results of studies performed upon similar compositions, component data and/or expert review of the product. Please refer to Section 11 for the detailed toxicology information.

Section 4. First Aid Measures

Eye: Immediately flush with water for 15 minutes. Get medical attention.

Skin: Remove from skin and wash thoroughly with soap and water or waterless cleanser. Get medical attention if irritation or other ill effects develop or persist.

Inhalation: Material is not likely to present an inhalation hazard at ambient conditions. If material is heated or vapor/mist/dust/fumes is generated, care should be taken to prevent inhalation. In case of exposure to vapor, move to fresh air.

Oral: Get medical attention. Do not induce vomiting.

Notes to Physician: Treat according to person's condition and specifics of exposure.

Section 5. Fire Fighting Measures

Flash Point: Not applicable

Autoignition Temperature: Not determined.

Flammability Limits in Air: Not determined.

Extinguishing Media: On large fires use dry chemical, foam or water spray. On small fires use carbon dioxide (CO2), dry chemical or water spray. Water can be used to cool fire exposed containers.

Fire Fighting Measures: Self-contained breathing apparatus and protective clothing should be worn in fighting large fires involving chemicals. Determine the need to evacuate or isolate the area according to your local emergency plan. Use water spray to keep fire exposed containers cool.

Unusual Fire Hazards: None.

Hazardous Decomposition: Thermal breakdown of this product during fire or very high heat conditions

Products may evolve the following hazardous decomposition products: Carbon oxides and traces of incompletely burned carbon compounds. Silicone dioxide. Formaldehyde.

Section 6. Accidental Release Measures

Containment/Clean up:

Observe all personal protection equipment recommendations described in Sections 5 and 8. Wipe up or scrape up and contain for salvage or disposal. Clean area as appropriate since spilled materials, even in small quantities, may present a slip hazard. Final cleaning may require use of steam, solvents or detergents. Dispose of saturated absorbant or cleaning materials appropriately, since spontaneous heating may occur. Local, state and federal laws and regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine which federal, state and local laws and regulations are applicable. Sections 13 and 15 of this MSDS provide nformation regarding certain federal and state requirements.

Note: See section 8 for Personal Protective Equipment for Spills.



Section 7. Handling and Storage

Use with adequate ventilation. Product evolves acetic acid (HOAc) when exposed to water or humid air. Provide ventilation during use to control HOAc within exposure guidelines or use respiratory protection. Avoid eye contact. Avoid skin contact. Do not take internally. Avoid breathing vapor. Keep container closed.

Use reasonable care and store away from oxidizing materials. Keep container closed and store away from water or moisture.

Section 8. Exposure Controls/Personal Protection

Component Exposure Limits

CAS Number	Component Name	Exposure Limits
64742-46-7	Hydrotreated middle	OSHA PEL(final rule) and ACGIH TLV for oil
	Petroleum distillates	mists: TWA 5mg/m3
17689-77-9	Ethyltriacetoxysilane	See acetic acid comments.
4253-34-3	Methyltriacetoxysilane	See acetic acid comments.

Acetic acid is formed upon contact with water or humid air. Provide adequate ventilation to control exposures within guidelines of OSHA PEL: TWA 10 ppm and ACGIH TLV: TWA 10 ppm, STEL 15 ppm.

Engineering Controls

Local Ventilation: Recommended. General Ventilation: Recommended.

Personal Protective Equipment for Routine Handling

Eyes: Use proper protection - safety glasses as a minimum.

Skin: Wash at mealtime and end of shift. Contaminated clothing and shoes should be removed as soon as practical

and thoroughly cleaned before reuse. Chemical protective gloves are recommended.

Suitable Gloves: Nitrile Rubber, Siyler Shield ®, 4H(R)

Inhalation: Use respiratory protection unless adequate local exhaust ventilation is provided or exposure assessment

demonstrates that exposures are within recommended exposure guidelines. IH personnel can assist in judging

the adequacy of existing engineering controls.

Suitable Respirator: Respiratory protection is not needed under ambient conditions. If vapor/mist/dust/fumes are generated when

material is heated or handled, the following is advised. General and local exhaust ventilation is recommended to maintain vapor exposures below recommended limits. Where concentrations are above recommended limits or are unknown, appropriate respiratory protection should be worn. Follow OSHA respirator regulations

(29 CFR 1910.134) and use NIOSH/MSHA approved respirators.

Personal Protective Equipment for Spills

Eyes: Use full face respirator.

Skin: Wash at mealtime and end of shift. Contaminated clothing and shoes should be removed as soon as practical

and thoroughly cleaned before reuse. Chemical protective gloves are recommended.

Inhalation/Suitable Respirator: Respiratory protection recommended. Follow OSHA Respirator Regulations (29 CFR 1910.134)

and use NIOSH/MHSA approved respirators. Protection provided by air purifying respirators against exposure

to any hazardous chemical is limited. Use a positive pressure air supplied respirator if there is any

potential for uncontrolled release, exposure levels are unknown, or any other circumstance where air purifying

respirators may not provide adequate protection.

Precautionary Measures: Avoid eye contact. Avoid skin contact. Do not take internally. Avoid breathing vapor. Keep container

closed. Use reasonable care.



Comments: Product evolves acetic acid (HOAc) when exposed to water or humid air. Provide ventilation during use to

control HOAc within exposure guidelines or use respiratory protection.

Note: These precautions are for room temperature handling. Use at elevated temperature or aerosol/spray applications may require added precautions.

Section 9. Physical and Chemical Properties

Physical Form: Paste

Color: See product name Odor: Acetic acid odor

Specific Gravity @ 25/C: 0.96

Viscosity:

Freezing/Melting Point:

Boiling Point:

Vapor Pressure @ 25/C:

Vapor Density:

Solubility in Water:

PH:

Volatile Content:

Viscosity:

Not determined.

Not determined.

Not determined.

Not determined.

Volatile Content:

Plash Point:

Not determined.

Volatile Content:

Not determined.

Volatile Content:

Viscosity:

Not determined.

Volatile Content:

Volatile Content:

Viscosity:

Not determined.

Volatile Content:

Viscosity:

Not determined.

Volatile Content:

V

Flash Point:
Autoignition Temperature:
Flammability Limits in Air:
Not determined.
Not determined.
Not determined.

Note: The above information is not intended for use in preparing product specifications.

Section 10. Stability and Reactivity

Chemical Stability: Stable.

Hazardous Polymerization: Hazardous polymerization will not occur.

Conditions to Avoid: None.

Materials to Avoid: Oxidizing material can cause a reaction. Water, moisture, or humid air can cause hazardous vapors

to form as described in Section 8.

Section 11. Toxicological Information

Special Hazard Information on Components

No known applicable information.

Section 12. Ecological Information

Environmental Fate and Distribution

Complete information is not yet available.

Environmental Effects

Complete information is not yet available.

Fate and Effects in Waste Water Treatment Plants

Complete information is not yet available.



Ecotoxicity Classification Criteria

Hazard Parameters (LC50 or EC50)	High	Medium	Low
Acute Aquatic Toxicity (mg/L)	<=1	>1 and <=100	>100
Acute Terrestrial Toxicity	<=100	>100 and <= 2000	>2000

This table is adapted from "Environmental Toxicology and Risk Assessment", ASTM STP 1179, p.34, 1993. This table can be used to classify the ecotoxicity of this product when ecotoxicity data is listed above. Please read the other information presented in the section concerning the overall ecological safety of this material.

Section 13. Disposal Consideration

RCRA Hazard Class (40 CFR 261)

When a decision is made to discard this material, as received, is it classified as a hazardous waste? No State or local laws may impose additional regulatory requirements regarding disposal.

Section 14. Transportation Information

DOT Road Shipment Information (49 CFR 172.101)

Not subject to DOT.

Ocean Shipment (IMDG)

Not subject to IMDG code.

Air Shipment (IATA)

Not subject to IATA regulations.

Section 15. Regulatory Information

Contents of this MSDS comply with the OSHA Hazard Communication Standard 29 CFR 1910.1200.

TSCA Status: All chemical substances in this material are included on or exempted from listing on the TSCA Inventory of Chemical Substances.

EPA SARA Title III Chemical Listings

Section 302 Extremely Hazardous Substances (40 CFR 355):

None

Section 304 CERCLA Hazardous Substances (40 CFR 302):

None.

Section 311/312 Hazard Class (40 CFR 370):

Acute: Yes Chronic: No Fire: No Pressure: No Reactive: No

Section 313 Toxic Chemicals (40 CFR 372):

None present or none present in regulated quantities.

Supplemental State Compliance Information



California

Warning: This product contains the following chemical(s) listed by the State of California under the Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65) as being known to cause cancer, birth defects or other reproductive harm.

None known.

Massachusetts

CAS Number	Wt %	Component Name
7631-86-9	7.0 - 13.0	Silica, amorphous

New Jersey

CAS Number	Wt %	Component Name
70131-67-8	> 60.0	Dimethyl siloxane, hydroxy-terminated
64742-46-7	15.0 - 40.0	Hydrotreated middle petroleum distillates
7631-86-9	7.0 - 13.0	Silica, amorphous
17689-77-9	1.0 - 5.0	Ethyltriacetoxysilane
4253-34-3	1.0 - 5.0	Methyltriacetoxysilane

Pennsylvania

CAS Number	Wt %	Component Name
70131-67-8	> 60.0	Dimethyl siloxane, hydroxy-terminated
64742-46-7	15.0 - 40.0	Hydrotreated middle petroleum distillates
7631-86-9	7.0 - 13.0	Silica, amorphous

Section 16. Other Information

HMIS III rating

Health: 2 Flammability: 1 Physical hazard: 0

HMIS uses a numbering scale ranging from 0 to 4 to indicate the degree of hazard. A value of zero means that the substance possesses essentially no hazard; a rating of four indicates high hazard.

For Industrial Use Only

This material safety data sheet is offered solely for your information, consideration and investigation. The data described in this MSDS consist of data on literature, our acquisitional data and analogical inference by data of similar chemical substance or product. American Sealants, Inc. provides no warranties, either express or implied, and assumes no responsibility for the accuracy or completeness of the data contained herein.