# SAFETY DATA SHEET

### 1. Identification

**Product number** 1000002384

**CAMIE 410 FOOD PROCESSORS SILICONE SPRAY Product identifier** 

Camie-Campbell, Inc. Company information 1005 S. Westgate Drive

Addison, IL 60101 United States

www.camie.com

1-866-836-8855

General Assistance 1-800-325-9572 Company phone

**Emergency telephone US Emergency telephone outside** 

1-952-852-4646

01 Version #

Recommended use LUBRICANT **Recommended restrictions** None known.

# 2. Hazard(s) identification

**Physical hazards** Flammable aerosols Category 1 **Health hazards** Acute toxicity, inhalation Category 4 Germ cell mutagenicity Category 1B Carcinogenicity Category 1B Aspiration hazard Category 1 **Environmental hazards** Hazardous to the aquatic environment, acute Category 3

hazard

Hazardous to the aquatic environment,

Category 3

long-term hazard

**OSHA** defined hazards Not classified.

Label elements



Signal word Danger

Extremely flammable aerosol. May be fatal if swallowed and enters airways. **Hazard statement** 

**Precautionary statement** 

Prevention Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Do not spray on an open

flame or other ignition source. Pressurized container: Do not pierce or burn, even after use.

Response If swallowed: Immediately call a poison center/doctor. Do NOT induce vomiting.

Storage Store locked up. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F. Dispose of contents/container in accordance with local/regional/national/international regulations. Disposal

Hazard(s) not otherwise

classified (HNOC)

None known.

Supplemental information None.

# 3. Composition/information on ingredients

# **Mixtures**

| Chemical name                      | Common name and synonyms | CAS number | %       |
|------------------------------------|--------------------------|------------|---------|
| Naphtha, Petroleum, Light Alkylate |                          | 64741-66-8 | 60 - 80 |
| Butane                             |                          | 106-97-8   | 20 - 40 |

Product name: CAMIE 410 FOOD PROCESSORS SILICONE SPRAY

| Chemical name                        | Common name and synonyms | CAS number | %       |
|--------------------------------------|--------------------------|------------|---------|
| Propane                              |                          | 74-98-6    | 10 - 20 |
| 2,2,4-Trimethylpentane               |                          | 540-84-1   | 0.1 - 1 |
| Other components below reportable le |                          | 2.5 - 10   |         |

<sup>\*</sup>Designates that a specific chemical identity and/or percentage of composition has been withheld as a trade secret.

### 4. First-aid measures

InhalationIf symptoms develop move victim to fresh air. Get medical attention if symptoms persist.Skin contactWash off with soap and water. Get medical attention if irritation develops and persists.

Eye contact Rinse with water. Get medical attention if irritation develops and persists.

Ingestion Call a physician or poison control center immediately. Do not induce vomiting. If vomiting occurs,

keep head low so that stomach content doesn't get into the lungs. Aspiration may cause

pulmonary edema and pneumonitis.

Most important symptoms/effects, acute and delayed

Direct contact with eyes may cause temporary irritation.

Indication of immediate medical attention and special treatment needed

Provide general supportive measures and treat symptomatically.

**General information** Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves.

5. Fire-fighting measures

Suitable extinguishing media

Powder. Water. Carbon dioxide (CO2).

Unsuitable extinguishing media

None known.

Specific hazards arising from the chemical

Contents under pressure. Pressurized container may explode when exposed to heat or flame.

Special protective equipment and precautions for firefighters

Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.

Fire-fighting equipment/instructions

Move containers from fire area if you can do so without risk. Use water spray to cool unopened containers. Containers should be cooled with water to prevent vapor pressure build up. For massive fire in cargo area, use unmanned hose holder or monitor nozzles, if possible. If not,

withdraw and let fire burn out.

Specific methods

Use standard firefighting procedures and consider the hazards of other involved materials. Move

container from fire area if it can be done without risk. Cool containers exposed to flames with water

until well after the fire is out. In the event of fire and/or explosion do not breathe fumes.

General fire hazards Extremely flammable aerosol.

### 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Keep out of low areas. Wear appropriate personal protective equipment. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Methods and materials for containment and cleaning up

Refer to attached safety data sheets and/or instructions for use. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. Stop leak if you can do so without risk. Move the cylinder to a safe and open area if the leak is irreparable. Isolate area until gas has dispersed. Collect spillage. Prevent entry into waterways, sewer, basements or confined areas. Following product recovery, flush area with water. For waste disposal, see section 13 of the SDS.

**Environmental precautions** 

Avoid release to the environment. Contact local authorities in case of spillage to drain/aquatic environment. Prevent further leakage or spillage if safe to do so. Do not contaminate water. Avoid discharge into drains, water courses or onto the ground.

# 7. Handling and storage

Precautions for safe handling

Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. All equipment used when handling the product must be grounded. Ground and bond containers when transferring material. Do not re-use empty containers. Use only in well-ventilated areas. Observe good industrial hygiene practices. Wash hands thoroughly after handling. Do not empty into drains.

Conditions for safe storage, including any incompatibilities

Store locked up. Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50°C/122°F. Do not puncture, incinerate or crush. Do not handle or store near an open flame, heat or other sources of ignition. This material can accumulate static charge which may cause spark and become an ignition source. Refrigeration recommended. Store away from incompatible materials (see Section 10 of the SDS). Level 3 Aerosol.

# 8. Exposure controls/personal protection

### Occupational exposure limits

| US. OSHA Table Z-1 Limits for A Components | Туре           | Value      |  |
|--|----------------|------------|--|
| Propane (CAS 74-98-6)                      | PEL            | 1800 mg/m3 |  |
| ,  |                | 1000 ppm   |  |
| US. ACGIH Threshold Limit Valu             | es             |            |  |
| Components                                 | Туре           | Value      |  |
| Butane (CAS 106-97-8)                      | STEL           | 1000 ppm   |  |
| US. NIOSH: Pocket Guide to Che             | emical Hazards |            |  |
| Components                                 | Туре           | Value      |  |
| Butane (CAS 106-97-8)                      | TWA            | 1900 mg/m3 |  |
|  |                | 800 ppm    |  |
| Propane (CAS 74-98-6)                      | TWA            | 1800 mg/m3 |  |

Biological limit values

No biological exposure limits noted for the ingredient(s).

Appropriate engineering controls

Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.

1000 ppm

### Individual protection measures, such as personal protective equipment

**Eye/face protection** Wear safety glasses with side shields (or goggles).

Hand protection Wear protective gloves.

Skin protection

**Other** Wear appropriate chemical resistant clothing.

Respiratory protection If permissible levels are exceeded use NIOSH mechanical filter / organic vapor cartridge or an

air-supplied respirator.

**Thermal hazards** Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations

When using, do not eat, drink or smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely

wash work clothing and protective equipment to remove contaminants.

### 9. Physical and chemical properties

**Appearance** 

Physical state
Form
Color
Not available.

Odor threshold
Not available.

Not available.

Not available.

Melting point/freezing point
Not available.

Initial boiling point and boiling Not available.

range

Flash point -156.0 °F (-104.4 °C) PROPELLANT estimated

Evaporation rate Not available.

Flammability (solid, gas) Not available.

Upper/lower flammability or explosive limits

Flammability limit - lower

1.3 % estimated

(%)

Flammability limit - upper

7.4 % estimated

(%)

Explosive limit - lower (%) Not available.

Explosive limit - upper (%) Not available.

Vapor pressure 39.7 psig @70F estimated

Vapor density Not available.

Relative density 0.674 g/cm3 estimated

Solubility(ies)

Solubility (water) Not available.

Partition coefficient Not available.

(n-octanol/water)

Auto-ignition temperature 806 °F (430 °C) estimated

**Decomposition temperature** Not available. **Viscosity** Not available.

Other information

Density0.67 g/cm3 estimatedHeat of combustion45.08 kJ/g estimatedHeat of combustion (NFPA45.08 kJ/g estimated

30B)

Percent volatile 34.04 % estimated Specific gravity 0.674 estimated VOC (Weight %) 94.89 % estimated

### 10. Stability and reactivity

**Reactivity**The product is stable and non-reactive under normal conditions of use, storage and transport.

Chemical stability Material is stable under normal conditions.

Possibility of hazardous Hazardous polymerization does not occur.

reactions

Conditions to avoidAvoid temperatures exceeding the flash point.Incompatible materialsStrong oxidizing agents. Fluorine. Chlorine. Nitrates.Hazardous decompositionNo hazardous decomposition products are known.

products

# 11. Toxicological information

### Information on likely routes of exposure

IngestionMay be fatal if swallowed and enters airways.InhalationMay be fatal if swallowed and enters airways.

**Skin contact** Not available.

Eye contact Direct contact with eyes may cause temporary irritation.

Symptoms related to the Direct contact with eyes may cause temporary irritation.

physical, chemical and toxicological characteristics

Information on toxicological effects

**Acute toxicity** May be fatal if swallowed and enters airways.

Components **Species Test Results** 

2,2,4-Trimethylpentane (CAS 540-84-1)

**Acute** 

Dermal

LD50 Rabbit > 2000 mg/kg, 24 Hours

Inhalation

LC50 Rat > 33.52 mg/l, 4 Hours

Butane (CAS 106-97-8)

Acute

Inhalation

LC50 Mouse 1237 mg/l, 120 Minutes

52 %, 120 Minutes

Rat 1355 mg/l

Naphtha, Petroleum, Light Alkylate (CAS 64741-66-8)

**Acute** 

Dermal

LD50 Rabbit > 1900 mg/kg, 24 Hours

Inhalation

LC50 Rat > 5020 mg/m3, 4 Hours

> 4980 mg/m3

> 4980 mg/m3, 4 Hours > 4.96 mg/l, 4 Hours

Oral

LD50 Rat 4820 mg/kg

Propane (CAS 74-98-6)

Acute

Inhalation

LC50 Mouse 1237 mg/l, 120 Minutes

52 %, 120 Minutes

Rat 1355 mg/l 658 mg/l/4h

Skin corrosion/irritation Prolonged skin contact may cause temporary irritation. Serious eye damage/eye Direct contact with eyes may cause temporary irritation.

irritation

Respiratory or skin sensitization

Respiratory sensitization Not available.

This product is not expected to cause skin sensitization. Skin sensitization

Germ cell mutagenicity No data available to indicate product or any components present at greater than 0.1% are

mutagenic or genotoxic.

Carcinogenicity This product is not considered to be a carcinogen by IARC, ACGIH, NTP, or OSHA.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed.

This product is not expected to cause reproductive or developmental effects. Reproductive toxicity

Specific target organ toxicity -

single exposure

Not classified.

Specific target organ toxicity -

repeated exposure

Not classified.

May be fatal if swallowed and enters airways. **Aspiration hazard** 

<sup>\*</sup> Estimates for product may be based on additional component data not shown.

# 12. Ecological information

Ecotoxicity Harmful to aquatic life with long lasting effects. Accumulation in aquatic organisms is expected.

Components Species Test Results

Naphtha, Petroleum, Light Alkylate (CAS 64741-66-8)

Aquatic

Algae IC50 Algae 30000 mg/L, 72 Hours

\* Estimates for product may be based on additional component data not shown.

**Persistence and degradability** No data is available on the degradability of this product.

Bioaccumulative potential No data available.

Partition coefficient n-octanol / water (log Kow)

Butane 2.89 Propane 2.36

Mobility in soil No data available.

Other adverse effects No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation

potential, endocrine disruption, global warming potential) are expected from this component.

# 13. Disposal considerations

**Disposal instructions**Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Contents

under pressure. Do not puncture, incinerate or crush. This material and its container must be disposed of as hazardous waste. Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose of contents/container in accordance with local/regional/national/international regulations.

Local disposal regulations

Dispose in accordance with all applicable regulations.

Hazardous waste code

The waste code should be assigned in discussion between the user, the producer and the waste

disposal company.

Waste from residues / unused

products

Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see:

Disposal instructions).

**Contaminated packaging** Empty containers should be taken to an approved waste handling site for recycling or disposal.

Since emptied containers may retain product residue, follow label warnings even after container is

emptied. Do not re-use empty containers.

# 14. Transport information

DOT

UN number UN1950

UN proper shipping name Aerosols, flammable

Transport hazard class(es)

Class 2.1 Subsidiary risk -Label(s) 2.1

Packing group Not applicable.

Special precautions for user Read safety instructions, SDS and emergency procedures before handling. Read safety

instructions, SDS and emergency procedures before handling.

Special provisions N82
Packaging exceptions 306
Packaging non bulk None
Packaging bulk None

This product meets the exception requirements of section 173.306 as a limited quantity and may be shipped as a limited quantity. Until 12/31/2020, the "Consumer Commodity - ORM-D" marking may still be used in place of the new limited quantity diamond mark for packages of UN 1950 Aerosols. Limited quantities require the limited quantity diamond mark on cartons after 12/31/20 and may be used now in place of the "Consumer Commodity ORM-D" marking and both may be displayed concurrently.

**IATA** 

UN number UN1950

UN proper shipping name Aerosols, flammable

Transport hazard class(es)

Class 2.1 Subsidiary risk -Label(s) 2.1 Packing group Not applicable.

**Environmental hazards** No. **ERG Code** 10L

Special precautions for user Read safety instructions, SDS and emergency procedures before handling. Read safety

instructions, SDS and emergency procedures before handling.

Other information

Passenger and cargo

aircraft

Allowed.

Cargo aircraft only Allowed.

Packaging Exceptions LTD QTY

**IMDG** 

UN number UN1950 UN proper shipping name AEROSOLS

Transport hazard class(es)

Class 2.1 Subsidiary risk -Label(s) 2.1

Packing group Not applicable.

**Environmental hazards** 

Marine pollutant No. EmS F-D, S-U

Special precautions for user Read safety instructions, SDS and emergency procedures before handling. Read safety

instructions, SDS and emergency procedures before handling.

Packaging Exceptions
Transport in bulk according to
Annex II of MARPOL 73/78 and

the IBC Code

LTD QTY
Not applicable.

DOT



IATA; IMDG



# 15. Regulatory information

**US federal regulations**This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication

Standard, 29 CFR 1910.1200.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

**CERCLA Hazardous Substance List (40 CFR 302.4)** 

2,2,4-Trimethylpentane (CAS 540-84-1) Listed.

SARA 304 Emergency release notification

Not regulated.

Product name: CAMIE 410 FOOD PROCESSORS SILICONE SPRAY Product #: 1000002384 Version #: 01 Issue date: 07-12-2015

### OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed.

### Superfund Amendments and Reauthorization Act of 1986 (SARA)

No

Hazard categories Immediate Hazard - Yes

Delayed Hazard - Yes Fire Hazard - Yes Pressure Hazard - No Reactivity Hazard - No

### SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous

chemical

# SARA 313 (TRI reporting)

Not regulated.

### Other federal regulations

### Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

2,2,4-Trimethylpentane (CAS 540-84-1)

### Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Butane (CAS 106-97-8) Propane (CAS 74-98-6)

Safe Drinking Water Act

Not regulated.

(SDWA)

### **US** state regulations

### **US. Massachusetts RTK - Substance List**

2,2,4-Trimethylpentane (CAS 540-84-1)

Butane (CAS 106-97-8) Propane (CAS 74-98-6)

# US. New Jersey Worker and Community Right-to-Know Act

2,2,4-Trimethylpentane (CAS 540-84-1)

Butane (CAS 106-97-8) Propane (CAS 74-98-6)

# US. Pennsylvania Worker and Community Right-to-Know Law

2,2,4-Trimethylpentane (CAS 540-84-1)

Butane (CAS 106-97-8) Propane (CAS 74-98-6)

### **US. Rhode Island RTK**

2,2,4-Trimethylpentane (CAS 540-84-1)

Butane (CAS 106-97-8) Propane (CAS 74-98-6)

### **US. California Proposition 65**

California Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65): This material is not known to contain any chemicals currently listed as carcinogens or reproductive toxins.

### **International Inventories**

| Country(s) or region | Inventory name   | On inventory (yes/no)* |
|----------------------|--|------------------------|
| Australia            | Australian Inventory of Chemical Substances (AICS)                     | Yes                    |
| Canada               | Domestic Substances List (DSL)   | Yes                    |
| Canada               | Non-Domestic Substances List (NDSL)                                    | No                     |
| China                | Inventory of Existing Chemical Substances in China (IECSC)             | Yes                    |
| Europe               | European Inventory of Existing Commercial Chemical Substances (EINECS) | Yes                    |
| Europe               | European List of Notified Chemical Substances (ELINCS)                 | No                     |
| Japan                | Inventory of Existing and New Chemical Substances (ENCS)               | Yes                    |
| Korea                | Existing Chemicals List (ECL)  | Yes                    |
| New Zealand          | New Zealand Inventory  | Yes                    |
| Philippines          | Philippine Inventory of Chemicals and Chemical Substances (PICCS)      | Yes                    |

Country(s) or region Inventory name On inventory (yes/no)\*

United States & Puerto Rico Toxic Substances Control Act (TSCA) Inventory

\*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s) A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

# 16. Other information, including date of preparation or last revision

07-12-2015 Issue date

Version # 01

Disclaimer The information in the sheet was written based on the best knowledge and experience currently

available. The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with

any other materials or in any process, unless specified in the text.

Product name: CAMIE 410 FOOD PROCESSORS SILICONE SPRAY

SDS US Product #: 1000002384 Version #: 01 Issue date: 07-12-2015