SAFETY DATA SHEET



1. Identification

in adminibution		
Product number	100002361	
Product identifier	CAMIE 363 HIGH STRENGTH FAST TACK	SPRAY ADHESIVE
Company information	Camie-Campbell, Inc. 1005 S. Westgate Drive Addison, IL 60101 United States www.camie.com	
Company phone	General Assistance 1-800-325-9572	
Emergency telephone US	1-866-836-8855	
Emergency telephone outside US	1-952-852-4646	
Version #	01	
Recommended use	ADHESIVE	
Recommended restrictions	None known.	
2. Hazard(s) identification		
Physical hazards	Flammable aerosols	Category 1

Physical hazards	Flammable aerosols	Category 1
Health hazards	Skin corrosion/irritation	Category 2
	Serious eye damage/eye irritation	Category 2A
	Reproductive toxicity (fertility)	Category 2
	Specific target organ toxicity, single exposure	Category 3 narcotic effects
	Specific target organ toxicity, repeated exposure	Category 2
	Aspiration hazard	Category 1
Environmental hazards	Not classified.	
OSHA defined hazards	Not classified.	

Label elements



Signal word	Danger
Hazard statement	Extremely flammable aerosol. May be fatal if swallowed and enters airways. Causes skin irritation. Causes serious eye irritation. May cause drowsiness or dizziness. May cause damage to organs through prolonged or repeated exposure.
Precautionary statement	
Prevention	Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Do not breathe mist or vapor. Wash thoroughly after handling. Use only outdoors or in a well-ventilated area. Wear protective gloves/protective clothing/eye protection/face protection.
Response	If swallowed: Immediately call a poison center/doctor. If on skin: Wash with plenty of water. If inhaled: Remove person to fresh air and keep comfortable for breathing. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If exposed or concerned: Get medical advice/attention. Call a poison center/doctor if you feel unwell. Specific treatment (see this label). Do NOT induce vomiting. If skin irritation occurs: Get medical advice/attention. If eye irritation persists: Get medical advice/attention. Take off contaminated clothing and wash before reuse.
Storage	Store in a well-ventilated place. Keep container tightly closed. Store locked up. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.

None.

3. Composition/information on ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number	%
Acetone		67-64-1	20 - 40
Dimethyl Ether		115-10-6	10 - 20
n-Hexane		110-54-3	10 - 20
Propane		74-98-6	10 - 20
2-Methylpentane		107-83-5	2.5 - 10
3-Methylpentane		96-14-0	1 - 2.5
Other components below reportable leve	els		20 - 40

*Designates that a specific chemical identity and/or percentage of composition has been withheld as a trade secret.

4. First-aid measures

Inhalation	Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/physician if you feel unwell.
Skin contact	Take off immediately all contaminated clothing. Remove contaminated clothing. Rinse skin with water/shower. If skin irritation occurs: Get medical advice/attention. Wash contaminated clothing before reuse. Wash clothing separately before reuse.
Eye contact	Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.
Ingestion	Call a physician or poison control center immediately. Rinse mouth. Do not induce vomiting. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs.
Most important symptoms/effects, acute and delayed	Causes serious eye irritation. Irritation of nose and throat. Aspiration may cause pulmonary edema and pneumonitis. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Vapors have a narcotic effect and may cause headache, fatigue, dizziness and nausea. Skin irritation. May cause redness and pain. Prolonged exposure may cause chronic effects.
Indication of immediate medical attention and special treatment needed	Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.
General information	Take off all contaminated clothing immediately. IF exposed or concerned: Get medical advice/attention. If you feel unwell, seek medical advice (show the label where possible). Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Show this safety data sheet to the doctor in attendance. Wash contaminated clothing before reuse.
5. Fire-fighting measures	
Suitable extinguishing media	Alcohol resistant foam. Water fog. Dry chemical powder. Carbon dioxide (CO2).
Unsuitable extinguishing media	Do not use water jet as an extinguisher, as this will spread the fire.
Specific hazards arising from the chemical	Contents under pressure. Pressurized container may explode when exposed to heat or flame. During fire, gases hazardous to health may be formed.
Special protective equipment and precautions for firefighters	Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.
Fire-fighting equipment/instructions	Move containers from fire area if you can do so without risk. Containers should be cooled with water to prevent vapor pressure build up. For massive fire in cargo area, use unmanned hose holder or monitor nozzles, if possible. If not, withdraw and let fire burn out.
Specific methods	Use standard firefighting procedures and consider the hazards of other involved materials. Move containers from fire area if you can do so without risk. In the event of fire and/or explosion do not breathe fumes.

General fire hazards Extremely flammable aerosol.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures	Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Keep out of low areas. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Wear appropriate protective equipment and clothing during clean-up. Do not breathe mist or vapor. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.
Methods and materials for containment and cleaning up	Refer to attached safety data sheets and/or instructions for use. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Eliminate all ignition sources (no smoking, flares, sparks or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. Stop leak if you can do so without risk. Move the cylinder to a safe and open area if the leak is irreparable. Cover with plastic sheet to prevent spreading. Absorb in vermiculite, dry sand or earth and place into containers. Prevent entry into waterways, sewer, basements or confined areas. Following product recovery, flush area with water.
	Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination. For waste disposal, see section 13 of the SDS.
Environmental precautions	Environmental manager must be informed of all major releases. Avoid release to the environment. Inform appropriate managerial or supervisory personnel of all environmental releases. Prevent further leakage or spillage if safe to do so. Avoid discharge into drains, water courses or onto the ground.
7. Handling and storage	
Precautions for safe handling	Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. Avoid contact with skin, eyes and clothing. All equipment used when handling the product must be grounded. Use non-sparking tools and explosion-proof equipment. Do not re-use empty containers. Do not breathe mist or vapor. Avoid contact with eyes, skin, and clothing. Avoid prolonged exposure. Use only in well-ventilated areas. Should be handled in closed systems, if possible. Pregnant or breastfeeding women must not handle this product. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Avoid release to the environment. Observe good industrial hygiene practices.
Conditions for safe storage,	Level 2 Aerosol.
including any incompatibilities	Store locked up. Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50°C/122 °F. Do not puncture, incinerate or crush. Do not handle or store near an open flame, heat or other sources of ignition. This material can accumulate static charge which may cause spark and become an ignition source. Store in a well-ventilated place. Refrigeration recommended. Store away from incompatible materials (see Section 10 of the SDS).

8. Exposure controls/personal protection

US. OSHA Specifically Regulated Components	Туре	Value	
Dimethyl Ether (CAS 115-10-6)	STEL	2 ppm	
,	TWA	0.75 ppm	
US. OSHA Table Z-1 Limits for Air	Contaminants (29 CFR 1910.	1000)	
Components	Туре	Value	
Acetone (CAS 67-64-1)	PEL	2400 mg/m3	
		1000 ppm	
n-Hexane (CAS 110-54-3)	PEL	1800 mg/m3	
		500 ppm	
Propane (CAS 74-98-6)	PEL	1800 mg/m3	
,		1000 ppm	
US. ACGIH Threshold Limit Value	S		
Components	Туре	Value	
2-Methylpentane (CAS 107-83-5)	STEL	1000 ppm	

TWA 500 ppm 3Methylpentane (CAS STEL 1000 ppm 96-14-0) TWA 500 ppm 96-14-0) TWA 500 ppm Acetone (CAS 67-64-1) STEL 750 ppm Dimethyl Ether (CAS Ceiling 0.3 ppm Dimethyl Ether (CAS Ceiling 0.3 ppm TIS-10-6) TWA 500 ppm Dimethyl Ether (CAS Ceiling 0.1 ppm Components Type Value Acetone (CAS 67-64-1) TWA 50 ppm Dimethyl Ether (CAS Ceiling 0.1 ppm TIS-10-6) TWA 0.016 ppm n-Hexane (CAS 110-54-3) TWA 180 mg/m3 Dimethyl Ether (CAS Ceiling 0.01 ppm Us. Workplace Environmental Exposure Level (WEEL) Guides Tool0 ppm Components TWA 1880 mg/m3 Components Value 1000 ppm Dimethyl Ether (CAS TWA 1880 mg/m3 115-10-6) 1000 ppm 1000 ppm togigal limit values	US. ACGIH Threshold Lin Components		vpe	١	/alue
Acetone (CAS 67-64-1) TWA 500 ppm Dimethyl Ether (CAS Celling 0.3 ppm Dimethyl Ether (CAS Celling 0.3 ppm US, NIOSH: Pocket Guide to Chemical Hazards 500 ppm Components Type Value Acetone (CAS 67-64-1) TWA 590 mg/m3 Dimethyl Ether (CAS Celling 0.1 ppm Dimethyl Ether (CAS Celling 0.1 ppm 115-10-6) TWA 0.016 ppm n-Hexane (CAS 110-54-3) TWA 0.016 ppm n-Hexane (CAS 110-54-3) TWA 1800 mg/m3 Components Type Value Dimethyl Ether (CAS TWA 1800 mg/m3 115-10-6) TWA 1800 mg/m3 US. Workplace Environmental Exposure Lavel (WEEL) Guides Components Components Type Value Dimethyl Ether (CAS TWA 1880 mg/m3 115-10-6) 1000 ppm 1000 ppm US. Workplace Environmental Exposure Lavel (WEEL) Guides Soponpm Components Value Determinant Specimen ACEID Biological Exposure Indices Components Sampling Time ACEID Horehold Limit Values Schorekalt Sin designation n-Hexane (CAS 110-54-3) <td></td> <td></td> <td></td> <td></td> <td>••</td>					••
Dimetryl Ether (CAS 115-10-6) n-Hexane (CAS 110-54-3) US. NIOSH: Pocket Guide to Chemical Hazards Components Acetone (CAS 67-64-1) TWA Acetone (CAS 67-64-1) TWA Acetone (CAS 67-64-1) TWA Acetone (CAS 67-64-1) TWA TWA Ceiling 0.1 ppm TWA 0.016 ppm n-Hexane (CAS 110-54-3) TWA 1800 mg/m3 50 ppm Propane (CAS 74-98-6) TWA 1800 mg/m3 1000 ppm Propane (CAS 74-98-6) TWA 1800 mg/m3 1000 ppm US. Workplace Environmental Exposure Level (WEEL) Guides Components Type Value Dimetryl Ether (CAS TWA 1800 mg/m3 1000 ppm 1000 ppm US. Workplace Environmental Exposure Level (WEEL) Guides Components Type Value Dimetryl Ether (CAS TWA Acetone (CAS 67-64-1) So ppm TWA Acetone (CAS 67-64-1) So pgm TWA Acetone (CAS 67-64-1) So mg/l Acetone (CAS 67-64-1) So mg/l Acetone (CAS 110-54-3) Can be absorbed through the skin. US ACGIH Threshold Limit Values: Skin protection Chemical respirator with organic vapor cartridge and full facepiece. Hand protection Chemical respirator with organic vapor cartridge and full facepiece. Respiratory protection Chemical respirator with organic vapor cartridge and full facepiece. Components Carbone Limit or a spirator with organic vapor cartridge and full facepiece. Carbone Cimical respirator with organic vapor cartridge and full facepiece. Carbone Cimical respirator with organic vapor cartridge and full facepiece. Carbone Cimical respirator with organic vapor cartridge and full facepiece. Carbone Cimical respirator with organic vapor cartridge and full facepiece. Carbone Cimical respirator with organic vapor cartridge and full facepiece. Carbone Cimical respirator with organic vapor cartridge and full facepiece. Carbone Cimical respirator with organic vapor cartridge and full facepiece.		ST	ſEL	7	750 ppm
n-Hexane (CAS 110-54-3) TWA 50 ppm US. NIOSH: Pocket Guide to Chemical Hazards Components Type Value Acetone (CAS 67-64-1) TWA 590 mg/m3 250 ppm Dimethyl Ether (CAS 115-10-6) TWA 0.016 ppm n-Hexane (CAS 110-54-3) TWA 180 mg/m3 Propane (CAS 74-98-6) TWA 1800 mg/m3 1000 ppm Propane (CAS 74-98-6) TWA 1800 mg/m3 1000 ppm US. Workplace Environmental Exposure Level (WEEL) Guides Components Type Value Dimethyl Ether (CAS 74-98-6) TWA 1800 mg/m3 1000 ppm US. Workplace Environmental Exposure Level (WEEL) Guides Components Type Value Dimethyl Ether (CAS 74-98-6) TWA 1800 mg/m3 115-10-6) 1000 ppm US. Workplace Environmental Exposure Level (WEEL) Guides Components Type Value Dimethyl Ether (CAS 74-98-6) TWA 1880 mg/m3 115-10-6) 1000 ppm US. Workplace Environmental Exposure Indices Components Value Determinant Specime Speci					••
Components Type Value Acetone (CAS 67-64-1) TWA 590 mg/m3 Dimethyl Ether (CAS Ceiling 0.1 ppm 115-10-6) TWA 0.016 ppm n-Hexane (CAS 110-54-3) TWA 0.016 ppm Propane (CAS 74-98-6) TWA 1800 mg/m3 US. Workplace Environmental Exposure Lovel (WEEL) Guides Towa 1800 mg/m3 Components Type Value Value Dimethyl Ether (CAS TWA 1880 mg/m3 1000 ppm Odgical limit values Acceline (WEEL) Guides Towa 1000 ppm Acceline (CAS 67-64-1) 50 mg/l Acetone Urine • Acceline (CAS 67-64-1) 50 mg/l Acetone Urine • Acceline (CAS 67-64-1) 50 mg/l Acetone Urine • n-Hexane (CAS 110-54-3) 0.4 mg/l 2.5-Hexanedio Urine • * - For sampling details, please see the source document. Source absorbed through the skin. US AcGIH Threshold Limit Values: Skin designation n-Hexane (CAS 110-54-3) Can be abso		ΤV	VA	5	50 ppm
Acetone (CAS 67-64-1) TWA 590 mg/m3 Dimethyl Ether (CAS Ceiling 0.1 ppm 115-10-6) TWA 0.016 ppm n-Hexane (CAS 110-54-3) TWA 180 mg/m3 Propane (CAS 74-98-6) TWA 1800 mg/m3 Stopper TWA 1800 mg/m3 Dimethyl Ether (CAS TWA 1880 mg/m3 115-10-6) 1000 ppm 1000 ppm logical limit values Acetone Urine * Accione (CAS 67-64-1) 50 mg/l Acetone Urine * n-Hexane (CAS 110-54-3) 0.4 mg/l 2,5-Hexanedio Urine * n-Hexane (CAS 110-54-3) 0.4 mg/l 2,5-Hexanedio Urine * vertidering Carlo e absorbed through the skin. * * OS - California OELs: Skin designation n-Hexane (CAS 110-54-3) Carlo e absorbed through the skin. US - California OELs: Skin designation n-Hexane (CAS 110-54-3) Carlo e ab	US. NIOSH: Pocket Guide	to Chemical Hazard	ls		
Dimethyl Ether (CAS Ceiling 0.1 ppm Dimethyl Ether (CAS Ceiling 0.1 ppm In15-10-6) TWA 0.016 ppm n-Hexane (CAS 110-54-3) TWA 1800 mg/m3 Propane (CAS 74-98-6) TWA 1800 mg/m3 1000 ppm 1000 ppm 1000 ppm US. Workplace Environmental Exposure Level (WEEL) Guides Value Value Components TWA 1880 mg/m3 115-10-6) 1000 ppm 1000 ppm Value Determinant Specimen Acetone (CAS 67-64-1) 50 mg/l 2.6 -Hexanedio n-Hexane (CAS 110-54-3) 0.4 mg/l 2.6 -Hexanedio urine * * * n-Hexane (CAS 110-54-3) 0.4 mg/l 2.6 -Hexanedio US - California OELs: Skin designation * * n-Hexane (CAS 110-54-3) Can be absorbed through the skin. US - California OELs: Skin designation * * n-Hexane (CAS 110-54-3) Can be absorbed through the skin. US - California OELs: Skin designation * * n-Hexane (CAS 110-54-3) Can be absorbed through the skin. US - California OELs: Skin designation * * n-Hexane (CAS 110-54-3) Can be absorbed through the skin. </td <td>Components</td> <td>Ту</td> <td>/pe</td> <td>۱</td> <td>/alue</td>	Components	Ту	/pe	۱	/alue
Dimethyl Ether (CAS Ceiling 0.1 ppm 115-10-6) TWA 0.016 ppm n-Hexane (CAS 110-54-3) TWA 180 mg/m3 Propane (CAS 74-98-6) TWA 1800 mg/m3 US, Workplace Environmental Exposure Level (WEEL) Guides 1000 ppm Components Type Value Dimethyl Ether (CAS TWA 1880 mg/m3 115-10-6) 1000 ppm 1000 ppm Components Value 1000 ppm Components Value 1000 ppm Components Value 1000 ppm Acctone (CAS 67-64-1) 50 mg/l Acetone Urine * n-Hexane (CAS 110-54-3) 0.4 mg/l 2,5-Hexanedio n, without hydrolysis * * * - For sampling details, please see the source document. Source guidelines * * US - California OELs: Skin designation n-Hexane (CAS 110-54-3) Can be absorbed through the skin. US ACGIH Threshold Limit values: Skin designation n-Hexane (CAS 110-54-3) Can be absorbed through the skin. US ACGIH Threshold Limit values: Skin designation n-Hexane (CAS 110-54-3) Can be absorbed through the skin. US ACGIH Threshold Limit	Acetone (CAS 67-64-1)	ΤV	VA		•
n-Hexane (CAS 110-54-3) TWA 180 mg/m3 50 ppm Propane (CAS 74-98-6) TWA 1800 mg/m3 1000 ppm US. Workplace Environmental Exposure Level (WEEL) Guides Components Type Value Dimethyl Ether (CAS 115-10-6) 1000 ppm logical limit values ACGIH Biological Exposure Indices Components Value Determinant Specime Sampling Time Acetone (CAS 67-64-1) 50 mg/l Acetone Urine • n-Hexane (CAS 110-54-3) 0.4 mg/l 2.5-Hexanedio n, without hydrolysis * * - For sampling details, please see the source document. osure guidelines US - California OELS: Skin designation n-Hexane (CAS 110-54-3) Can be absorbed through the skin. US ACGIH Threshold Limit Values: Skin designation n-Hexane (CAS 110-54-3) Can be absorbed through the skin. VS ACGIH Threshold Limit Values: Skin designation n-Hexane (CAS 110-54-3) Can be absorbed through the skin. US ACGIH Threshold Limit Values: Skin designation n-Hexane (CAS 110-54-3) Can be absorbed through the skin. The propriate engineering trols california of the skin altorne levels below recommended exposure limits. If exposure limits and emergence shower must be available when handling this product. vidual protection measures, such as personal protective equipment Explosion-proof general and local exposure limits. If exposure limits and emergence shower must be available when handling this product. vidual protection measures, such as personal protective equipment Explosion-protection the skin and protective equipment Explosion-protective equipment Explosion-protective equipment Explosion-protective expropriate chemical resistant clothing. Use of an impervious apron is recommended. Skin protection Chemical respirator with organic vapor cartridge and full facepiece.		Ce	eiling		••
Propane (CAS 74-98-6) TWA 50 ppm 1800 mg/m3 1000 ppm US. Workplace Environmental Exposure Level (WEEL) Guides Components Type Value Dimethyl Ether (CAS 115-10-6) TWA 1880 mg/m3 1000 ppm Oddel limit values ACGIH Biological Exposure Indices Components Value 1000 ppm Ogical limit values ACGIH Biological Exposure Indices Components Value Determinant Specimen Sampling Time Accetone (CAS 67-64-1) 50 mg/l Acetone Urine * -n-Hexane (CAS 110-54-3) 0.4 mg/l 2,5-Hexanedio n, without hydrolysis * * * - For sampling details, please see the source document. Urine * * osure guidelines US - California OELs: Skin designation n-Hexane (CAS 110-54-3) Can be absorbed through the skin. US ACGIH Threshold Limit Values: Skin designation n-Hexane (CAS 110-54-3) Can be absorbed through the skin. roprizate engineering trols Explosion-proof general and local exhaust ventilation. Good general ventilation (typically 10 ai changes per hour) should be used. Ventilation are should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering contrast bo maintain airborne levels below recommended exposure limits. If exposure limits have not beer established, maintain airborne levels bolow recommended exposure limits. If exposure limits have not beer established, maintain airborne levels bolow recommended exposure limits. If exposure limits have not beer esta		ΤV	VA	C).016 ppm
Propane (CAS 74-98-6) TWA 1800 mg/m3 1000 ppm US. Workplace Environmental Exposure Level (WEEL) Guides Components Type Value Dimethyl Ether (CAS TWA 1880 mg/m3 1000 ppm ogical limit values TWA 1880 mg/m3 1000 ppm Accine (CAS 67-64-1) 50 mg/l Acetone Urine * Accone (CAS 67-64-1) 50 mg/l Acetone Urine * -n-Hexane (CAS 110-54-3) 0.4 mg/l 2,5-Hexanedio urine * -n-Hexane (CAS 110-54-3) 0.4 mg/l 2,5-Hexanedio urine * vg/rclysis * - For sampling details, please see the source document. * * osure guidelines US - California OELs: Skin designation - * * -n-Hexane (CAS 110-54-3) Can be absorbed through the skin. US ACGIH Threshold Limit Values: Skin designation - * - -n-Hexane (CAS 110-54-3) Can be absorbed through the skin. Can be absorbed through the skin. US ACGIH Threshold Limit Values: Skin designation - - - - - - - - - - - - <td< td=""><td>n-Hexane (CAS 110-54-3)</td><td>ΤV</td><td>VA</td><td></td><td>•</td></td<>	n-Hexane (CAS 110-54-3)	ΤV	VA		•
US. Workplace Environmental Exposure Level (WEEL) Guides Components Type Value Dimethyl Ether (CAS Type Value Dimethyl Ether (CAS TWA 1880 mg/m3 115-10-6) Gogical limit values ACGIH Biological Exposure Indices Components Value Determinant Specimen Sampling Time Accetone (CAS 67-64-1) 50 mg/l Accetone Urine * n-Hexane (CAS 110-54-3) 0.4 mg/l 2,5-Hexanedio Urine * n-Hexane (CAS 110-54-3) Can be absorbed through the skin. US - California OELs: Skin designation n-Hexane (CAS 110-54-3) Can be absorbed through the skin. US ACGIH Threshold Limit Values: Skin designation n-Hexane (CAS 110-54-3) Can be absorbed through the skin. ropriate engineering trols changes per hour) should be used. Ventilation. Good general ventilation (typically 10 ai changes per hour) should be used. Ventilation. Good general ventilation (typically 10 ai changes per hour) should be used. Ventilation cother engineering controls to maintain airborne levels to an acceptable level. Eye wash facilities and emergence shower must be available when handling this product. vidual protection measures, such as personal protective equipment Eyelface protection Wear appropriate chemical resistant gloves. Skin protection Mand protection Wear appropriate chemical resistant gloves. Skin protection Mear appropriate chemical resistant clothing. Use of an impervious apron is recommended. Skin protection Respiratory protection Chemical respirator with organic vapor cartridge and full facepiece.		_			••
Components Type Value Dimethyl Ether (CAS TWA 1880 mg/m3 115-10-6) 1000 ppm ogical limit values ACGH Biological Exposure Indices Components Value Determinant Specimen Sampling Time Acctone (CAS 67-64-1) 50 mg/l Acetone Urine * -n-Hexane (CAS 110-54-3) 0.4 mg/l 2,5-Hexanedio n, without hydrolysis Urine * * - For sampling details, please see the source document. Ourine * * OSA CGIH Threshold Limit Values: Skin designation n-Hexane (CAS 110-54-3) Can be absorbed through the skin. US ACGIH Threshold Limit Values: Skin designation n-Hexane (CAS 110-54-3) Can be absorbed through the skin. US ACGIH Threshold Limit Values: Skin designation n-Hexane (CAS 110-54-3) Can be absorbed through the skin. Explosion-proof general and local exhaust ventilation. Good general ventilation (typically 10 ai changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not beer established, maintain airborne levels to an acceptable level. Eye wash facilities and emergenc shower must be available when handling this product. V	Propane (CAS 74-98-6)	TV	VA		•
115-10-6) 1000 ppm ogical limit values ACGIH Biological Exposure Indices Components Value Determinant Specimen Sampling Time Acetone (CAS 67-64-1) 50 mg/l Acetone Urine * n-Hexane (CAS 110-54-3) 0.4 mg/l 2,5-Hexanedio n, without hydrolysis Urine * * - For sampling details, please see the source document. ourine * * osure guidelines US - California OELs: Skin designation n-Hexane (CAS 110-54-3) Can be absorbed through the skin. US ACGIH Threshold Limit Values: Skin designation n-Hexane (CAS 110-54-3) Can be absorbed through the skin. ropriate engineering trols Explosion-proof general and local exhaust ventilation, cood general ventilation (typically 10 ai changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not beer established, maintain airborne levels to an acceptable level. Eye wash facilities and emergenc shower must be available when handling this product. vidual protection measures, such as personal protective equipment Eye/face protection Chemical respirator with organic vapor cartridge and full facepiece. Kan protection Wear appropriate chemical resistant clothing. Use of an impervious apron		-	· ·	١	/alue
1000 ppm Ogical limit values ACGIH Biological Exposure Indices Components Value Determinant Specimen Sampling Time Acetone (CAS 67-64-1) 50 mg/l Acetone Urine * Acetone (CAS 10-54-3) 0.4 mg/l 2,5-Hexanedio n, without hydrolysis Urine * * - For sampling details, please see the source document. Urine * * osure guidelines US - California OELs: Skin designation n-Hexane (CAS 110-54-3) Can be absorbed through the skin. US ACGIH Threshold Limit Values: Skin designation n-Hexane (CAS 110-54-3) Can be absorbed through the skin. vorporiate engineering trols Explosion-proof general and local exhaust ventilation, cood general ventilation (typically 10 ai changes per hour) should be used. Ventilation ace should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits have not beer established, maintain airborne levels below recommended exposure limits. If exposure limits have not beer established, maintain airborne levels to an acceptable level. Eye wash facilities and emergenc shower must be available when handling this product. vidual protection Mear appropriate chemical resistant gloves. Skin protection Wear appropriate chemical resistant gloves.	Dimethyl Ether (CAS	ΤV	VA	1	880 mg/m3
Odjcal limit values ACGIH Biological Exposure Indices Components Value Determinant Specimen Sampling Time Acetone (CAS 67-64-1) 50 mg/l Acetone Urine * n-Hexane (CAS 110-54-3) 0.4 mg/l 2,5-Hexanedio Urine * n-Hexane (CAS 110-54-3) 0.4 mg/l 2,5-Hexanedio Urine * source guidelines US - California OELs: Skin designation * * n-Hexane (CAS 110-54-3) Can be absorbed through the skin. US ACGIH Threshold Limit Values: Skin designation n-Hexane (CAS 110-54-3) Can be absorbed through the skin. US ACGIH Threshold Limit Values: Skin designation n-Hexane (CAS 110-54-3) Can be absorbed through the skin. Us ACGIH Threshold Limit Values: Skin designation n-Hexane (CAS 110-54-3) Can be absorbed through the skin. Us ACGIH Science in the skin designation or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not beer established, maintain airborne levels below recommended exposure limits. If exposure limits have not beer established, maintain airborne levels below recommended exposure limits. If exposure limits have not beer established, maintain airborne levels below recommended exposure limits. If exposure limits have not beer established, maintain airborne levels to an acceptable l					
n-Hexane (CAS 110-54-3) 0.4 mg/l 2,5-Hexanedio Urine * n, without hydrolysis * - For sampling details, please see the source document. osure guidelines US - California OELs: Skin designation n-Hexane (CAS 110-54-3) Can be absorbed through the skin. US ACGIH Threshold Limit Values: Skin designation n-Hexane (CAS 110-54-3) Can be absorbed through the skin. US ACGIH Threshold Limit Values: Skin designation n-Hexane (CAS 110-54-3) Can be absorbed through the skin. ropriate engineering trols Explosion-proof general and local exhaust ventilation. Good general ventilation (typically 10 ail changes per hour) should be used. Ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not beer established, maintain airborne levels to an acceptable level. Eye wash facilities and emergenc shower must be available when handling this product. vidual protection measures, such as personal protective equipment Eye/face protection Measures, such as personal protective equipment Eye/face protection Wear appropriate chemical resistant gloves. Skin protection Other Wear appropriate chemical resistant clothing. Use of an impervious apron is recommended. Skin protection Respiratory protection Chemical respirator with organic vapor cartridge and full facepiece.	115-10-6) ogical limit values				000 ppm
osure guidelines US - California OELs: Skin designation n-Hexane (CAS 110-54-3) US ACGIH Threshold Limit Values: Skin designation n-Hexane (CAS 110-54-3) Can be absorbed through the skin. US ACGIH Threshold Limit Values: Skin designation n-Hexane (CAS 110-54-3) Can be absorbed through the skin. propriate engineering trols Explosion-proof general and local exhaust ventilation. Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not beer established, maintain airborne levels to an acceptable level. Eye wash facilities and emergence shower must be available when handling this product. vidual protection measures, such as personal protective equipment Eye/face protection Chemical respirator with organic vapor cartridge and full facepiece. Hand protection Wear appropriate chemical resistant gloves. Skin protection Wear appropriate chemical resistant clothing. Use of an impervious apron is recommended. Skin protection Chemical respirator with organic vapor cartridge and full facepiece. Respiratory protection Chemical respirator with organic vapor cartridge and full facepiece.	115-10-6) ogical limit values ACGIH Biological Exposu Components	re Indices Value		Specimen	Sampling Time
US - California OELs: Skin designation n-Hexane (CAS 110-54-3) Can be absorbed through the skin. US ACGIH Threshold Limit Values: Skin designation n-Hexane (CAS 110-54-3) Can be absorbed through the skin. ropriate engineering trols Explosion-proof general and local exhaust ventilation. Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not beer established, maintain airborne levels below recommended exposure limits. If exposure limits have not beer established, maintain airborne levels to an acceptable level. Eye wash facilities and emergence shower must be available when handling this product. vidual protection measures. User appropriate chemical resistant gloves. Skin protection Wear appropriate chemical resistant clothing. Use of an impervious apron is recommended. Skin protection Chemical respirator with organic vapor cartridge and full facepiece. Skin protection Chemical respirator with organic vapor cartridge and full facepiece. Skin protection Chemical respirator with organic vapor cartridge and full facepiece. Skin protection Chemical respirator with organic vapor cartridge and full facepiece. Skin protection Chemical respirator with organic vapor cartridge and full facepiece.	115-10-6) ogical limit values ACGIH Biological Exposu Components Acetone (CAS 67-64-1)	re Indices Value 50 mg/l	Acetone 2,5-Hexanedio n, without	1 Specimen Urine	Sampling Time
n-Hexane (CAS 110-54-3)Can be absorbed through the skin.US ACGIH Threshold Limit Values: Skin designationCan be absorbed through the skin.n-Hexane (CAS 110-54-3)Can be absorbed through the skin.ropriate engineering trolsExplosion-proof general and local exhaust ventilation. Good general ventilation (typically 10 ai changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not beer established, maintain airborne levels to an acceptable level. Eye wash facilities and emergence shower must be available when handling this product.vidual protection measures, Hand protectionChemical respirator with organic vapor cartridge and full facepiece.Kin protection OtherWear appropriate chemical resistant clothing. Use of an impervious apron is recommended.Skin protection Respiratory protectionChemical respirator with organic vapor cartridge and full facepiece.	115-10-6) logical limit values ACGIH Biological Exposu Components Acetone (CAS 67-64-1) n-Hexane (CAS 110-54-3)	Tre Indices Value 50 mg/l 0.4 mg/l	Acetone 2,5-Hexanedio n, without hydrolysis	1 Specimen Urine	Sampling Time
US ACGIH Threshold Limit Values: Skin designation n-Hexane (CAS 110-54-3)Can be absorbed through the skin.propriate engineering trolsExplosion-proof general and local exhaust ventilation. Good general ventilation (typically 10 ain changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not beer established, maintain airborne levels to an acceptable level. Eye wash facilities and emergence shower must be available when handling this product.vidual protection measures, such as personal protective equipmentChemical respirator with organic vapor cartridge and full facepiece.Kin protection OtherWear appropriate chemical resistant gloves.Use of an impervious apron is recommended.Skin protection Respiratory protectionChemical respirator with organic vapor cartridge and full facepiece.	115-10-6) logical limit values ACGIH Biological Exposu Components Acetone (CAS 67-64-1) n-Hexane (CAS 110-54-3) * - For sampling details, ple	Tre Indices Value 50 mg/l 0.4 mg/l	Acetone 2,5-Hexanedio n, without hydrolysis	1 Specimen Urine	Sampling Time
n-Hexane (CAS 110-54-3)Can be absorbed through the skin.propriate engineering trolsExplosion-proof general and local exhaust ventilation. Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not beer established, maintain airborne levels to an acceptable level. Eye wash facilities and emergence shower must be available when handling this product.vidual protection measures, such as personal protective equipmentChemical respirator with organic vapor cartridge and full facepiece.Kin protection OtherWear appropriate chemical resistant gloves.Skin protection Respiratory protectionChemical respirator with organic vapor cartridge and full facepiece.Respiratory protection Respiratory protectionChemical respirator with organic vapor cartridge and full facepiece.	115-10-6) logical limit values ACGIH Biological Exposu Components Acetone (CAS 67-64-1) n-Hexane (CAS 110-54-3) * - For sampling details, ple osure guidelines	Tre Indices Value 50 mg/l 0.4 mg/l ase see the source d	Acetone 2,5-Hexanedio n, without hydrolysis	1 Specimen Urine	Sampling Time
trolschanges per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not beer established, maintain airborne levels to an acceptable level. Eye wash facilities and emergence shower must be available when handling this product.vidual protection measures, such as personal protective equipment Eye/face protection Hand protectionChemical respirator with organic vapor cartridge and full facepiece.Skin protection OtherWear appropriate chemical resistant gloves.Skin protection Skin protectionWear appropriate chemical resistant clothing. Use of an impervious apron is recommended.Skin protection Chemical respirator with organic vapor cartridge and full facepiece.Chemical respirator with organic protection OtherChemical respirator with organic protection Chemical resistant clothing. Use of an impervious apron is recommended.Skin protection Respiratory protectionChemical respirator with organic vapor cartridge and full facepiece.	 115-10-6) logical limit values ACGIH Biological Exposu Components Acetone (CAS 67-64-1) n-Hexane (CAS 110-54-3) * - For sampling details, ple osure guidelines US - California OELs: Skin n-Hexane (CAS 110-54 	Tre Indices Value 50 mg/l 0.4 mg/l ase see the source d n designation 4-3)	Acetone 2,5-Hexanedio n, without hydrolysis ocument. Can be	1 Specimen Urine Urine	Sampling Time * *
Eye/face protectionChemical respirator with organic vapor cartridge and full facepiece.Hand protectionWear appropriate chemical resistant gloves.Skin protectionWear appropriate chemical resistant clothing. Use of an impervious apron is recommended.Skin protectionRespiratory protectionChemical respirator with organic vapor cartridge and full facepiece.	115-10-6) logical limit values ACGIH Biological Exposu Components Acetone (CAS 67-64-1) n-Hexane (CAS 110-54-3) * - For sampling details, ple osure guidelines US - California OELs: Skin n-Hexane (CAS 110-54 US ACGIH Threshold Lim	The Indices Value 50 mg/I 0.4 mg/I ase see the source d in designation 4-3) it Values: Skin design	Acetone 2,5-Hexanedio n, without hydrolysis ocument. Can be gnation	1 Specimen Urine Urine	Sampling Time * * * bugh the skin.
Skin protection Other Wear appropriate chemical resistant clothing. Use of an impervious apron is recommended. Skin protection Respiratory protection Chemical respirator with organic vapor cartridge and full facepiece.	115-10-6) logical limit values ACGIH Biological Exposu Components Acetone (CAS 67-64-1) n-Hexane (CAS 110-54-3) * - For sampling details, ple osure guidelines US - California OELs: Skin n-Hexane (CAS 110-54 US ACGIH Threshold Lim n-Hexane (CAS 110-54 Dropriate engineering	The Indices Value 50 mg/l 0.4 mg/l ase see the source d in designation 4-3) it Values: Skin design 4-3) Explosion-proof g changes per hou applicable, use p maintain airborne established, main	Acetone 2,5-Hexanedio n, without hydrolysis ocument. Can be general and local exha r) should be used. Ve process enclosures, lo e levels below recomm htain airborne levels to	1 Specimen Urine Urine Urine e absorbed thro aust ventilation ntilation rates s cal exhaust ve nended exposit o an acceptable	Sampling Time * * * bugh the skin. Dugh the skin Good general ventilation (typically 10 ai should be matched to conditions. If ntilation, or other engineering controls to ure limits. If exposure limits have not beer e level. Eye wash facilities and emergence
OtherWear appropriate chemical resistant clothing. Use of an impervious apron is recommended.Skin protectionChemical respirator with organic vapor cartridge and full facepiece.	115-10-6) logical limit values ACGIH Biological Exposu Components Acetone (CAS 67-64-1) n-Hexane (CAS 110-54-3) * - For sampling details, ple osure guidelines US - California OELs: Skin n-Hexane (CAS 110-54 US ACGIH Threshold Lim n-Hexane (CAS 110-54 US ACGIH Threshold Lim n-Hexane (CAS 110-54 oropriate engineering trols	are Indices Value 50 mg/l 0.4 mg/l ase see the source d n designation 4-3) it Values: Skin designation 4-3) Explosion-proof g changes per hou applicable, use p maintain airborne established, main shower must be	Acetone 2,5-Hexanedio n, without hydrolysis ocument. Can be general and local exha r) should be used. Ve general and local exha r) should be used. Ve rocess enclosures, lo e levels below recomm htain airborne levels to available when handli protective equipme	1 Specimen Urine Urine Urine e absorbed thro aust ventilation ntilation rates s cal exhaust ve nended exposu o an acceptable ng this product nt	Sampling Time * * * bugh the skin Good general ventilation (typically 10 ai should be matched to conditions. If ntilation, or other engineering controls to ure limits. If exposure limits have not beer e level. Eye wash facilities and emergence.
Skin protectionRespiratory protectionChemical respirator with organic vapor cartridge and full facepiece.	115-10-6) logical limit values ACGIH Biological Exposu Components Acetone (CAS 67-64-1) n-Hexane (CAS 110-54-3) * - For sampling details, ple osure guidelines US - California OELs: Skin n-Hexane (CAS 110-54 US ACGIH Threshold Lim n-Hexane (CAS 110-54 US ACGIH Threshold Lim n-Hexane (CAS 110-54 US ACGIH Threshold Lim show the second second second second trols	Image: see see the source d 50 mg/l 50 mg/l 0.4 mg/l ase see the source d n designation 4-3) it Values: Skin designation 4-3) Explosion-proof g changes per hou applicable, use p maintain airborne established, main shower must be es, such as personal Chemical respira	Acetone 2,5-Hexanedio n, without hydrolysis ocument. Can be general and local exha r) should be used. Ve process enclosures, lo e levels below recomm ntain airborne levels to available when handli protective equipme tor with organic vapor	1 Specimen Urine Urine Urine e absorbed thro aust ventilation ntilation rates s cal exhaust ve nended exposu o an acceptable ng this product nt r cartridge and	Sampling Time * * * bugh the skin Good general ventilation (typically 10 ai should be matched to conditions. If ntilation, or other engineering controls to ure limits. If exposure limits have not beer e level. Eye wash facilities and emergence.
Skin protectionRespiratory protectionChemical respirator with organic vapor cartridge and full facepiece.	115-10-6) logical limit values ACGIH Biological Exposu Components Acetone (CAS 67-64-1) n-Hexane (CAS 110-54-3) * - For sampling details, ple osure guidelines US - California OELs: Skin n-Hexane (CAS 110-54 US ACGIH Threshold Lim n-Hexane (CAS 110-54	Image: see see the source d 50 mg/l 50 mg/l 0.4 mg/l ase see the source d n designation 4-3) it Values: Skin designation 4-3) Explosion-proof g changes per hou applicable, use p maintain airborne established, main shower must be es, such as personal Chemical respira	Acetone 2,5-Hexanedio n, without hydrolysis ocument. Can be general and local exha r) should be used. Ve process enclosures, lo e levels below recomm ntain airborne levels to available when handli protective equipme tor with organic vapor	1 Specimen Urine Urine Urine e absorbed thro aust ventilation ntilation rates s cal exhaust ve nended exposu o an acceptable ng this product nt r cartridge and	Sampling Time * * * bugh the skin Good general ventilation (typically 10 ai should be matched to conditions. If ntilation, or other engineering controls to ure limits. If exposure limits have not beer e level. Eye wash facilities and emergence.
Respiratory protection Chemical respirator with organic vapor cartridge and full facepiece.	115-10-6) logical limit values ACGIH Biological Exposu Components Acetone (CAS 67-64-1) n-Hexane (CAS 110-54-3) * - For sampling details, ple osure guidelines US - California OELs: Skin n-Hexane (CAS 110-54 US ACGIH Threshold Lim n-Hexane (CAS 110-54 US ACGIH Threshold Lim n-Hexane (CAS 110-54 US ACGIH Threshold Lim n-Hexane (CAS 110-54 trols	are Indices Value 50 mg/l 0.4 mg/l ase see the source d n designation 4-3) it Values: Skin designation 4-3) Explosion-proof g changes per hou applicable, use p maintain airborne established, main shower must be est, such as personal Chemical respira Wear appropriate	Acetone 2,5-Hexanedio n, without hydrolysis ocument. Can be general and local exha r) should be used. Ve process enclosures, lo e levels below recomm ntain airborne levels to available when handli I protective equipme tor with organic vapor e chemical resistant gl	1 Specimen Urine Urine Urine e absorbed thro aust ventilation ntilation rates s cal exhaust ve nended exposu o an acceptable ng this product nt r cartridge and loves.	Sampling Time * * * bugh the skin Good general ventilation (typically 10 ai should be matched to conditions. If ntilation, or other engineering controls to are limits. If exposure limits have not beer e level. Eye wash facilities and emergence. full facepiece.
	115-10-6) logical limit values ACGIH Biological Exposu Components Acetone (CAS 67-64-1) n-Hexane (CAS 110-54-3) * - For sampling details, ple osure guidelines US - California OELs: Skin n-Hexane (CAS 110-54 US ACGIH Threshold Lim n-Hexane (CAS 110-54 US ACGIH Threshold Lim	are Indices Value 50 mg/l 0.4 mg/l ase see the source d n designation 4-3) it Values: Skin designation 4-3) Explosion-proof g changes per hou applicable, use p maintain airborne established, main shower must be est, such as personal Chemical respira Wear appropriate	Acetone 2,5-Hexanedio n, without hydrolysis ocument. Can be general and local exha r) should be used. Ve process enclosures, lo e levels below recomm ntain airborne levels to available when handli I protective equipme tor with organic vapor e chemical resistant gl	1 Specimen Urine Urine Urine e absorbed thro aust ventilation ntilation rates s cal exhaust ve nended exposu o an acceptable ng this product nt r cartridge and loves.	Sampling Time * * * bugh the skin Good general ventilation (typically 10 ai should be matched to conditions. If ntilation, or other engineering controls to are limits. If exposure limits have not beer e level. Eye wash facilities and emergence. full facepiece.
	115-10-6) logical limit values ACGIH Biological Exposu Components Acetone (CAS 67-64-1) n-Hexane (CAS 110-54-3) * - For sampling details, ple tosure guidelines US - California OELs: Skin n-Hexane (CAS 110-54 US ACGIH Threshold Lim n-Hexane (C	are Indices Value 50 mg/l 0.4 mg/l ase see the source d n designation 4-3) it Values: Skin designation 4-3) Explosion-proof g changes per hou applicable, use p maintain airborne established, main shower must be est, such as personal Chemical respira Wear appropriate Wear appropriate	Acetone 2,5-Hexanedio n, without hydrolysis ocument. Can be general and local exha r) should be used. Ve process enclosures, lo e levels below recomm ntain airborne levels to available when handli I protective equipme tor with organic vapor e chemical resistant gl	Specimen Urine Urine Urine e absorbed thro aust ventilation ntilation rates s cal exhaust ve nended exposu o an acceptable ng this product nt r cartridge and loves.	Sampling Time * * * bugh the skin. . Good general ventilation (typically 10 ai should be matched to conditions. If ntilation, or other engineering controls to are limits. If exposure limits have not beer e level. Eye wash facilities and emergence. full facepiece. an impervious apron is recommended.
	115-10-6) logical limit values ACGIH Biological Exposu Components Acetone (CAS 67-64-1) n-Hexane (CAS 110-54-3) * - For sampling details, ple tosure guidelines US - California OELs: Skin n-Hexane (CAS 110-54 US ACGIH Threshold Lim n-Hexane (C	Implication 50 mg/l 50 mg/l 0.4 mg/l ase see the source d n designation 4-3) It Values: Skin designation 4-3) Explosion-proof g changes per hou applicable, use p maintain airborne established, main shower must be est, such as personal Chemical respira Wear appropriate Wear appropriate Chemical respira	Acetone 2,5-Hexanedio n, without hydrolysis ocument. Can be general and local exha r) should be used. Ve process enclosures, lo e levels below recomm ntain airborne levels to available when handli I protective equipme tor with organic vapor e chemical resistant gl	Specimen Urine Urine Urine e absorbed thro aust ventilation ntilation rates s cal exhaust ve nended exposu o an acceptable ng this product nt r cartridge and loves.	Sampling Time * * * bugh the skin Good general ventilation (typically 10 ai should be matched to conditions. If ntilation, or other engineering controls to ure limits. If exposure limits have not beer e level. Eye wash facilities and emergence. full facepiece. full facepiece. full facepiece.

When using, do not eat, drink or smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

9. Physical and chemical properties

Appearance	
Physical state	Liquid.
Form	Aerosol.
Color	Not available.
Odor	Not available.
Odor threshold	Not available.
рН	Not available.
Melting point/freezing point	Not available.
Initial boiling point and boiling range	Not available.
Flash point	-156.0 °F (-104.4 °C) Propellant estimated
Evaporation rate	Not available.
Flammability (solid, gas)	Not available.
Upper/lower flammability or expl	losive limits
Flammability limit - lower (%)	1 % estimated
Flammability limit - upper (%)	18 % estimated
Explosive limit - lower (%)	Not available.
Explosive limit - upper (%)	Not available.
Vapor pressure	51.04 psig @70F estimated
Vapor density	Not available.
Relative density	Not available.
Solubility(ies)	
Solubility (water)	Not available.
Partition coefficient (n-octanol/water)	Not available.
Auto-ignition temperature	Not available.
Decomposition temperature	Not available.
Viscosity	Not available.
10. Stability and reactivity	
Reactivity	The product is stable and non-reactive under normal con
Chemical stability	Material is stable under normal conditions.

Reactivity	The product is stable and non-reactive under normal conditions of use, storage and transport.
Chemical stability	Material is stable under normal conditions.
Possibility of hazardous reactions	Hazardous polymerization does not occur.
Conditions to avoid	Avoid heat, sparks, open flames and other ignition sources. Avoid temperatures exceeding the flash point. Contact with incompatible materials.
Incompatible materials	Strong oxidizing agents.
Hazardous decomposition products	No hazardous decomposition products are known.

11. Toxicological information

Information on likely routes of exposure

Ingestion	Droplets of the product aspirated into the lungs through ingestion or vomiting may cause a serious chemical pneumonia. However, ingestion is not likely to be a primary route of occupational exposure. Smallest quantities reaching the lungs through swallowing or subsequent vomiting may result in lung edema or pneumonia.
Inhalation	May cause damage to organs through prolonged or repeated exposure by inhalation. May cause drowsiness and dizziness. Headache. Nausea, vomiting. Prolonged inhalation may be harmful.

Skin contact	Causes skin irritation.	
Eye contact	Causes serious eye irritation. If aspirated into lungs during swallowing or vomiting, may cause chemical pneumonia, pulmonar injury or death. Causes serious eye irritation. Irritation of nose and throat. Aspiration may cause pulmonary edema and pneumonitis. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Skin irritation. May cause redness and pain. Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting. May cause central nervous system effects.	
Symptoms related to the physical, chemical and toxicological characteristics		
Information on toxicological ef	fects	
Acute toxicity	May be fatal if swallowed and enters airways. Narcotic effects. Expected to be a low hazard usual industrial or commercial handling by trained personnel.	
Components	Species	Test Results
Acetone (CAS 67-64-1)		
Acute		
Dermal		
LD50	Guinea pig	> 7426 mg/kg, 24 Hours
		> 9.4 ml/kg, 24 Hours
	Rabbit	> 7426 mg/kg, 24 Hours
		> 9.4 ml/kg, 24 Hours
Inhalation		
LC50	Rat	55700 ppm, 3 Hours
		132 mg/l, 3 Hours
		50.1 mg/l
Oral		
LD50	Rat	5800 mg/kg
		2.2 ml/kg
Dimethyl Ether (CAS 115-10-6) Acute Inhalation		
NOEL Oral	Rat	2 ppm, 6 Hours
LD50	Rat	460 mg/kg
n-Hexane (CAS 110-54-3)		
Acute		
Dermal		
LD50	Rabbit	> 2000 mg/kg, 4 Hours
		> 5 ml/kg, 4 Hours
Inhalation		
LC50	Rat	> 5000 ppm, 24 Hours
		> 31.86 mg/l
		73860 ppm, 4 Hours
Oral		
LD50	Rat	24 ml/kg
		24 g/kg
	Wistar rat	49 g/kg
Propane (CAS 74-98-6)		
Acute		
Inhalation		
LC50	Mouse	1237 mg/l, 120 Minutes
		52 %, 120 Minutes
	Rat	1355 mg/l
		č

Components	Species	Test Results
		658 mg/l/4h
* Estimates for product may b	be based on additional componer	t data not shown.
Skin corrosion/irritation	Causes skin irritation.	
Serious eye damage/eye irritation	Causes serious eye irritation.	
Respiratory or skin sensitizatio	n	
Respiratory sensitization	Not a respiratory sensitizer.	
Skin sensitization	This product is not expected to	cause skin sensitization.
Germ cell mutagenicity	No data available to indicate p mutagenic or genotoxic.	roduct or any components present at greater than 0.1% are
Carcinogenicity	Risk of cancer cannot be excluded with prolonged exposure.	
OSHA Specifically Regulate Not listed.	ed Substances (29 CFR 1910.10	01-1050)
Reproductive toxicity	Suspected of damaging fertility	v or the unborn child.
Specific target organ toxicity - single exposure	Narcotic effects. May cause dr	owsiness and dizziness.
Specific target organ toxicity - repeated exposure	May cause damage to organs	through prolonged or repeated exposure.
Aspiration hazard	May be fatal if swallowed and	enters airways.
Chronic effects	Prolonged inhalation may be h damage to organs through pro	armful. Prolonged exposure may cause chronic effects. May cause longed or repeated exposure.

12. Ecological information

Ecotoxicity

Harmful to aquatic life with long lasting effects.

Components		Species	Test Results	
Acetone (CAS 67-64-1)			
Aquatic				
Crustacea	EC50	Water flea (Daphnia magna)	21.6 - 23.9 mg/l, 48 hours	
Fish LC50		Rainbow trout,donaldson trout (Oncorhynchus mykiss)	4740 - 6330 mg/l, 96 hours	
Dimethyl Ether (CAS 1	15-10-6)			
Aquatic				
Crustacea	EC50	Water flea (Daphnia pulex)	4.3 - 7.8 mg/l, 48 hours	
Fish	LC50	Striped bass (Morone saxatilis)	10.302 - 16.743 mg/l, 96 hours	
n-Hexane (CAS 110-5	4-3)			
Aquatic				
Fish	LC50	Fathead minnow (Pimephales promelas)	2.101 - 2.981 mg/l, 96 hours	

* Estimates for product may be based on additional component data not shown.

Persistence and degradability No data is available on the degradability of this product.

Bioaccumulative potential	No data available.
Partition coefficient n-octa	nol / water (log Kow)
2-Methylpentane	3.74
3-Methylpentane	3.6
Acetone	-0.24
Dimethyl Ether	0.1
n-Hexane	3.9
Propane	2.36
Mobility in soil	No data available.
Other adverse effects	No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

rei Biopodal contractation	
Disposal instructions	Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Contents under pressure. Do not puncture, incinerate or crush. Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose of contents/container in accordance with local/regional/national/international regulations.
Local disposal regulations	Dispose in accordance with all applicable regulations.
Hazardous waste code	The waste code should be assigned in discussion between the user, the producer and the waste disposal company.
US RCRA Hazardous Waste	U List: Reference
Acetone (CAS 67-64-1)	U002
Waste from residues / unused products	Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).
Contaminated packaging	Empty containers should be taken to an approved waste handling site for recycling or disposal. Since emptied containers may retain product residue, follow label warnings even after container is emptied. Do not re-use empty containers.

14. Transport information

DOT	
UN number	UN1950
UN proper shipping name	Aerosols, flammable
Transport hazard class(es)	
Class	2.1
Subsidiary risk	-
Label(s)	2.1
Packing group	Not applicable.
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.
Special provisions	N82
Packaging exceptions	306
Packaging non bulk	None
Packaging bulk	None

This product meets the exception requirements of section 173.306 as a limited quantity and may be shipped as a limited quantity. Until 12/31/2020, the "Consumer Commodity - ORM-D" marking may still be used in place of the new limited quantity diamond mark for packages of UN 1950 Aerosols. Limited quantities require the limited quantity diamond mark on cartons after 12/31/20 and may be used now in place of the "Consumer Commodity ORM-D" marking and both may be displayed concurrently.

ΙΑΤΑ

	A	
	UN number	UN1950
	UN proper shipping name	Aerosols, flammable
	Transport hazard class(es)	
	Class	2.1
	Subsidiary risk	-
	Label(s)	2.1
	Packing group	Not applicable.
	Environmental hazards	No.
	ERG Code	10L
	Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.
	Other information	
	Passenger and cargo aircraft	Allowed.
	Cargo aircraft only	Allowed.
	Packaging Exceptions	LTD QTY
IMD	G	
	UN number	UN1950
	UN proper shipping name	AEROSOLS
	Transport hazard class(es)	
	Class	2.1
	Subsidiary risk	-
	Label(s)	None
	Packing group	Not applicable.
		•••

Environmental hazardsNo.Marine pollutantNo.EmSNot available.Special precautions for userRead safety instructions, SDS and emergency procedures before handling.Packaging ExceptionsLTD QTYTransport in bulk according to
Annex II of MARPOL 73/78 andThis substance/mixture is not intended to be transported in bulk.





15. Regulatory information

S federal regulations	Standard, 2	29 CFR 1910.12		d by the OSHA Hazard ory List.	Communication
TSCA Section 12(b) Exp	ort Notification	(40 CFR 707, Sı	ubpt. D)		
Not regulated.					
CERCLA Hazardous Su	bstance List (40	CFR 302.4)			
Acetone (CAS 67-64 n-Hexane (CAS 110-			Listed. Listed.		
SARA 304 Emergency r	elease notification	on			
Not regulated. OSHA Specifically Regu Not listed.	lated Substance	es (29 CFR 1910).1001-1050)		
perfund Amendments and	d Reauthorizatio	n Act of 1986 (\$	SARA)		
Hazard categories	Delayed Ha Fire Hazard Pressure H	Hazard - Yes azard - Yes d - Yes lazard - Yes Hazard - No			
SARA 302 Extremely ha	zardous substa	nce			
Chemical name	CAS number	Reportable quantity	Threshold planning quantity	Threshold planning quantity, lower value	Threshold planning quantity, upper value
Vinyl Acetate	108-05-4	5000	1000 lbs		
SARA 311/312 Hazardou chemical	us No				

Product name: CAMIE 363 HIGH STRENGTH FAST TACK SPRAY ADHESIVE Product #: 1000002361 Version #: 01 Issue date: 07-16-2015

SARA 313 (TRI reporting) Chemical name		CAS number	% by wt.
n-Hexane Vinyl Acetate		110-54-3 108-05-4	10 - 20 0.01 - 0.1
ner federal regulations			
Clean Air Act (CAA) Section	n 112 Hazardous Air Polluta	nts (HAPs) List	
n-Hexane (CAS 110-54- Clean Air Act (CAA) Section	3)		68.130)
Dimethyl Ether (CAS 115 Propane (CAS 74-98-6)	5-10-6)		
Safe Drinking Water Act (SDWA)	Not regulated.		
Drug Enforcement Adn Chemical Code Numbe		sential Chemicals (2	21 CFR 1310.02(b) and 1310.04(f)(2) and
Acetone (CAS 67-64	-	6532	
-		-	Mixtures (21 CFR 1310.12(c))
Acetone (CAS 67-64 DEA Exempt Chemical	⁴⁻¹⁾ Mixtures Code Number	35 %WV	
Acetone (CAS 67-64	4-1)	6532	
state regulations			
US. Massachusetts RTK - S	Substance List		
2-Methylpentane (CAS 1			
3-Methylpentane (CAS 9 Acetone (CAS 67-64-1)	6-14-0)		
Dimethyl Ether (CAS 11	5-10-6)		
n-Hexane (CAS 110-54-			
Propane (CAS 74-98-6)			
US. New Jersey Worker and		/ Act	
2-Methylpentane (CAS 1	07-83-5)		
Acetone (CAS 67-64-1)	- 40.0		
Dimethyl Ether (CAS 118 n-Hexane (CAS 110-54-3			
Propane (CAS 74-98-6)	5)		
US. Pennsylvania Worker a	nd Community Right-to-Kno	ow Law	
2-Methylpentane (CAS 1			
3-Methylpentane (CAS 9			
Acetone (CAS 67-64-1)			
Dimethyl Ether (CAS 11	5-10-6)		
n-Hexane (CAS 110-54-	3)		
Propane (CAS 74-98-6)			
US. Rhode Island RTK			
Acetone (CAS 67-64-1)			
Dimethyl Ether (CAS 118 n-Hexane (CAS 110-54-3			
	0)		
Propane (CAS 74-98-6)			
1 (,	65		
US. California Proposition (California Safe Drinking			tion 65): This material is not known to contain
US. California Proposition (California Safe Drinking	Water and Toxic Enforcement		tion 65): This material is not known to contain
US. California Proposition California Safe Drinking any chemicals currently	Water and Toxic Enforcement		
US. California Proposition California Safe Drinking any chemicals currently ernational Inventories	Water and Toxic Enforcement listed as carcinogens or repro	ductive toxins.	On inventory (yes/no)*
US. California Proposition California Safe Drinking any chemicals currently ernational Inventories Country(s) or region	Water and Toxic Enforcement listed as carcinogens or repro Inventory name	ductive toxins. mical Substances (Al	On inventory (yes/no)*
US. California Proposition California Safe Drinking any chemicals currently ernational Inventories Country(s) or region Australia	Water and Toxic Enforcement listed as carcinogens or repro Inventory name Australian Inventory of Che	ductive toxins. emical Substances (Al (DSL)	On inventory (yes/no) ICS) No Yes
US. California Proposition California Safe Drinking any chemicals currently ernational Inventories Country(s) or region Australia Canada	Water and Toxic Enforcement listed as carcinogens or repro Inventory name Australian Inventory of Che Domestic Substances List	ductive toxins. emical Substances (Al (DSL) List (NDSL)	On inventory (yes/no)* ICS) No Yes No
US. California Proposition (California Safe Drinking any chemicals currently i ernational Inventories Country(s) or region Australia Canada Canada	Water and Toxic Enforcement listed as carcinogens or repro Inventory name Australian Inventory of Che Domestic Substances List Non-Domestic Substances	ductive toxins. mical Substances (Al (DSL) List (NDSL) ical Substances in Ch	On inventory (yes/no)* ICS) No Yes No hina (IECSC) No
US. California Proposition (California Safe Drinking) any chemicals currently f ernational Inventories Country(s) or region Australia Canada Canada China	Water and Toxic Enforcement listed as carcinogens or repro Inventory name Australian Inventory of Che Domestic Substances List Non-Domestic Substances Inventory of Existing Chem European Inventory of Exis	ductive toxins. mical Substances (Al (DSL) List (NDSL) ical Substances in Ch ting Commercial Che	On inventory (yes/no)* ICS) No Yes No nina (IECSC) No mical No

Country(s) or region	Inventory name	On inventory (yes/no)*
Korea	Existing Chemicals List (ECL)	No
New Zealand	New Zealand Inventory	No
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	No
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s) A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information, including date of preparation or last revision

Issue date	07-16-2015
Version #	01
Disclaimer	The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.