

Reka Glue Guns Pneumatic TR 700 Cartridge Gun

(855)437-7700
www.gluegun.com



Fig. TR 700

Made in Germany

The TR 700 cartridge gun applies hot-melt adhesives from 310 ml aluminium cartridges in dots, beads, or other standard nozzle forms.

The TR 700 lets you apply hot-melt adhesive as dots and lines.

The hot-melt adhesive is extruded through air pressure. Pneumatic glue guns increase work speed and simplify exact dosing of the glue.

The working-temperature of the glue applicator is controlled by a thermostat and set to 120 °C.

The TR 700 glue gun uses 310 ml aluminium hot-melt glue cartridges, which for instance can contain PUR-

hot-melt glue or POR-hot-melt adhesive. The cartridges can be swapped easily and hassle-free. The optional cartridge pre-heater KVG heats up the glue before use and increases the possible glue output per hour.

The number of possible application patterns is widely extended by the Reka nozzle range. Almost all of the offered nozzles can be used with every Reka glue gun in combination with a separate adapter.

(855)437-7700
www.gluegun.com

Technical Data

	TR 700	
Article Number	5385 (230 V)	5370 (120 V)
Weight	1400 g	
Power Supply	230 V / 50 Hz	120 V / 60 Hz
Power Consumption	400 Watt (230 V)	400 Watt (120 V)
Current Consumption	1,75 A	3,3 A
Degree of protection	IP 30	
Class of protection	I	
Temperature control	Thermostat	
Temperature limitation	Temperature monitor	
Operating temperature	120 °C	
Consistency of temperature	± 5 °C	
Heat-up time	approx. 3 – 10 min.	
Gross Tank Capacity	310 ml	
Conveying system	Air pressure	
Operating pressure	0,5 – 6 bar	
Length of electric cord	8,5 m	
Length of air tube	3 m	
Length of connection kit	3 m	
Recommended melts	310 ml hot-melt cartridges	

Accessories

- 1 # 3518 Footswitch
- 2 # 3746 Stationary equipment
- 3 # 5398 Cartridge Preheater
- 4 # 2770 Stand for storing
- 5 # 3544 Balancer
- 6 # 7099 Blank cartridge incl. piston
- 7 # 3466 Nozzle Set M10 Professional
- 8 Inquire about our nozzle range

(855)437-7700
www.gluegun.com

