

XP-233B

Thermal Barcode Printer

Xprinter® 芯焯
XINYE

- Various label width, can be 20mm-60mm
- Label paper auto detection
- Temperature control function
- Modularity design and meet with various applications
- Support QR CODE Printing and Bluetooth



Coffee Shop



Shopping




Mart



XP-233B

Thermal Barcode Printer



| MODEL | XP-233B |
|----------------------------|---|
| Resolution | Thermal barcode |
| Printing width | 56mm (Max) |
| Printing speed | Min 50.8mm/s, Max 101mm/s |
| Print head position sensor | Thermal sensitive resistance |
| Media type | Micro switch |
| Bar code | CODE128 / EAN128 / ITF / ITF25 / CODE39 / CODE39C / CODE39S / CODE93□ EAN13 / EAN13+2 / EAN13+5 / EAN8 / EAN8+2 / EAN8+5 / CODABAR / POSTNET / UPC-A / UPCA+2 / UPCA+5 / UPCE / UPCE+2 / UPCE+5 / MSI / MSIC / PLESSEY / ITF14 / EAN14 |
| QR CODE | PDF417、QR CODE、Data Matrix |
| Paper diameter | 100mm(max) |
| Paper off type | Tear off |
| Internal font | FONT 0 to FONT 8; Commonly used in single-byte fonts |
| Enlargement & rotation | 1to10 times enlargement in both directions; 0°, 90°, 180°, 270°, 360° rotation |
| Gross weight | 1.18 kg |
| Dimension | 210 x 136 x 156mm (D*W*H) |
| Work | 5~45°C, 20—80%RH |
| Storage | -40~55°C, ≤93%RH(40°C) |
| Drivers | Win XP/Win Vista/Win 7/Win 8/Win 8.1/ Win10 /Linux |
| Input | DC12V, 3A |
| Paper exists detection | Photoelectric sensor |
| Interface | USB / USB+Serial / USB+Bluetooth |
| Memory | DRAM: 64K; FLASH: 4M |
| Image | Monochromatic PCX, BMP image files can be load to FLASH, DRAM |



Scan QR code to checkout Xprinter website for more update information.
Phone: (+86 756) 3895 852
Http://www.xprintertech.com
Email: overseas@xprinter.net

