

Mobile Receipt & Label Printer

XP-P210



Key features

- Print speed: Min 50.8mm/s, Max. 101mm/s
- Print width: 48mm
- Max. roll diameter: 50mm
- Support thermal paper / thermal adhesive paper

Applications



Shopping



Mart



Restaurant



Hospital




Coffee Shop



Ticketing

XP-P210

Mobile Receipt & Label Printer



Printing Features		Label print mode	Receipt print mode
Printing method	Direct thermal		
Resolution	203 DPI		
Print width	Max.48 mm		
Print speed	Min. 50.8 mm/s, Max. 101 mm/s		90 mm/s Max.
Media			
Media type	Thermal paper roll /Thermal adhesive paper		Thermal paper
Media width	20mm ~ 60mm		58 mm
Media external diameter	50 mm		
Paper out method	Tearing-off		
Performance Features			
Print head temperature detection	Thermistor		
Cover open detection	Micro Switch		
Media detection	Photoelectric Sensors		
Interface	USB/USB+Bluetooth		
Storage	Flash 576 kb		
Fonts/Graphics/Symbologies			
Character size	Font 0 to Font8		Font A: 12x24,Font B: 9x17, CHN: 24*24
1D bar code	CODE128、EAN128、ITF、CODE25、CODE39、CODE39C、CODE39S、CODE93、EAN13、EAN13+2、EAN13+5、EAN8、EAN8+2、EAN8+5、CODABAR、POSTNET、UPC-A、UPCA+2、UPCA+5、UPCE、UPCE+2、UPCE+5、MSI、MSIC、PLESSEY、ITF14、EAN14		UPC-A/UPC-E/JAN13 (EAN13) / JAN8(EAN8)/CODE39/ITF/CODABAR/CODE93/CODE128
2D bar code	QR CODE		
Rotation	0°、90°、180°、270°		
Physical Features			
Gross weight	122.28*93.99*60.07mm (L*W*H)		
Dimensions	0.343 kg		
Software			
Systems	Windows/Android/iOS		
Power supply			
Battery	DC 7.2V/2500 mAh		
Charging input	Standard USB cable charging: 5V / 2A Optional DC adapter charging: 9V / 2A		
Environmental Conditions			
Work environment	0 ~ 45℃, 10 ~ 80%RH no condensing		
Storage environment	-10 ~ 60 °C, ≤93% RH (40℃) no condensing		



Scan QR code to checkout Xprinter website for more update information.
Phone: (+86 756) 3895 852
Http://www.xprinter.com
Email: overseas@xprinter.net

