

XP-235B

Thermal Barcode Printer

Key features

- Various label width, can be 20mm-60mm
- Label paper auto detection
- Overheating protection
- Modularity design and meet with various applications
- Support QR CODE Printing and Bluetooth



POS Printer

Specifications

Model	XP-235B
Printing method	Direct Thermal
Resolution	203 dpi
Printing width	20~60mm
Printing speed	Min 50.8mm/s, Max 101mm/s
Print head temperature sensor	Thermal sensitive resistance
Print head position sensor	Micro switch
Media type	Paper roll, sticker, label fold, etc.
Bar code	CODE128、EAN128、ITF、ITF25、CODE39、CODE39C、CODE39S、CODE93、EAN13、EAN13+2、EAN13+5、EAN8、EAN8+2、EAN8+5、CODABAR、POSTNET、UPC-A、UPCA+2、UPCA+5、UPCE、UPCE+2、UPCE+5、MSI、MSIC、PLESSEY、ITF14、EAN14 UPC-A/UPC-E/JAN13 (EAN13) / JAN8(EAN8)/CODE39/ITF/CODABAR/CODE93/CODE128
2D Code	QR CODE, PDF417, Data Matrix
Paper roll diameter	100mm(max)
Paper off type	Tear off
Internal font	FONT 0 to FONT 8; Commonly used in single-byte fonts
Enlargement & rotation	1to10 times enlargement in both directions; 0°, 90°, 180°, 270°, 360° rotation
Gross weight	1.08 kg
Dimension	206(D) x 136(W) x 148(H)mm
Work	5~45°C, 20~80%RH
Storage	-40~55°C, ≤93%RH(40°C)
Drivers	Win 9X/Win ME/Win 2000/Win 2003/Win NT/Win 7/Windows 8/Windows 10/Linux/IOS/Android
Input	DC12V, 3A
Paper exists detection	Photoelectric sensor
Interface	USB / USB+Bluetooth
Memory	DRAM: 64K; FLASH: 4M
Image	Monochromatic PCX, BMP image files can be load to FLASH, DRAM