

EcoTank ET-M3140



With this 4-in-1 ink tank system, benefit from 11,000 pages' worth of ink in the box, a three-year warranty and minimal user intervention.

A new mono EcoTank printer for business, with an extremely low TCO in a user-friendly, stylish and compact design. Print up to an amazing 11,000 pages with the included ink that comes in two bottles for mess-free, easy refills. USB connectivity, a 20ppm print speed and duplex printing all help to keep productivity high.

Save money

A high ink yield combined with Epson's economical inkjet technology delivers a low TCO and a competitive cost per page.

Save time

This reliable cartridge-free printer features an enhanced ink filling system and easy-to-use ink bottles, keeping intervention to a minimum. Thanks to the ink tank being positioned at the front of the printer with a clear view of the ink levels, this new design is compact and provides easy access for refilling. Its fast First Page Out Time (FPOT) of six seconds from sleep, and 20ppm print speed, mean you won't be waiting around for jobs.

Save energy

Unlike a laser, our inkjet technology doesn't need any heat during the printing process, helping to keep energy use low and reduce electricity bills.

Business features

Benefit from a 600dpi print resolution, a high scan resolution and double-sided printing. USB connectivity and a compact footprint mean that it's easy to place on a desktop and connect to a user's PC or laptop.

DATASHEET / BROCHURE



KEY FEATURES

- **Low TCO**
Keep your printing costs extremely low
- **High ink yields**
Print up to 11,000 pages with the included ink
- **Save time**
Fast FPOT
- **Low energy use**
Due to inkjet technology
- **4-in-1**
Print, scan, copy and fax

PRODUCT SPECIFICATIONS

TECHNOLOGY

Printing Method	PrecisionCore™ TFP print head
Nozzle Configuration	400 Nozzles black
Minimum Droplet Size	2.8 pl
Ink Technology	Pigment ink
Application	Home Office, Office Desktop, Office Workgroup
All-in-One Functions	Print, Scan, Copy, Fax

PRINT

First Page Out from Ready	Monochrome 6 Seconds
Printing Speed ISO/IEC 24734	20 pages/min Monochrome
Duplex Printing Speed ISO/IEC 24734	9 A4 pages/min Monochrome
Printing Speed ISO/IEC 24734 (A3)	20 pages/min Monochrome
Maximum Printing Speed	39 pages/min Monochrome (plain paper)
Printing Resolution	1,200 x 2,400 dpi
Max Duty cycle	5,000 pages per month The maximum number of printed pages per month based on the performance capabilities of the printer, including ISO rated print speeds and paper handling capabilities.
Recommended Duty Cycle	200 - 800 pages per month
Colours	Black

For detailed information on printing speeds please visit <http://www.epson.eu/testing>.

SCAN

Scanning Speed (new)	12 ipm (Monochrome, 200 dpi; 27 ipm (Colour, 200 dpi;
Scanning Resolution	1,200 dpi x 2,400 dpi (Horizontal x Vertical)
Optical Resolution (ADF)	1,200 dpi x 2,400 dpi (Horizontal x Vertical)
Output formats	BMP, JPEG, PICT, TIFF, PDF, PNG
Scanner type	Contact image sensor (CIS)

FAX

Type of fax	Walk-up black and white and colour fax capability
Fax Transmission Speed	upto 33.6kbps / Approx. 3 sec/page
Error correction mode	CCITU/ITU Group3 fax with Error Correction Mode
Fax speed dials (max)	100 names and numbers
Page memory	upto 180 pages (ITU-T No.1 chart)
Fax Functions	PC Fax, Auto Redial, Address Book, Broadcast Fax

COPY

Copy Speed	up to 17 ipm Black *Simplex ADF 600 x 600 dpi (ISO/ IEC 24735)
Copy resolution (dpi)	600 x 1200
Reduction / Enlargement	25 % - 400 %
Maximum number of copies	99
Maximum Copy Size	A4

CONNECTIVITY

Interfaces	Hi-Speed USB - compatible with USB 2.0 specification
------------	--

EcoTank ET-M3140

WHAT'S IN THE BOX

- Printer

PRODUCT SPECIFICATIONS

PAPER / MEDIA HANDLING

Paper Formats	A4, Legal
Automatic Document Feeder	35 pages
Compatible Paper Thickness	64 mm - 95 mm
Compatible Paper Weight	64 g/m ² - 90 g/m ²
Duplex	Yes
Standard Paper input	250 Sheets Standard, 1 Sheets MP tray
Output Tray Capacity	100 Sheets
Paper Tray Capacity	250 Sheets Standard
Standard paper tray(s)	1-Sheet paper tray, 250-sheet paper tray
Maximum paper input	251
Rear paper path (special media)	Yes
Number of paper trays	2

GENERAL

Recommended number of users	From 1 to 3
Product dimensions	375 x 347 x 346 mm (Width x Depth x Height)
Product weight	7.2 kg
Noise Level	6.9 B (A) according to ISO 7779 pattern with Epson Premium Glossy Photo Paper / Photo RPM mode - 56 dB (A) according to ISO 9296
Compatible Operating Systems	Mac OS 10.10.x, Mac OS 10.7.x, Mac OS 10.8.x, Mac OS 10.9.x, Mac OS X 10.11.x, Mac OS X 10.12.x, Mac OS X 10.6.8, Windows 10, Windows 7, Windows 8, Windows 8.1, Windows Server 2003 R2 x64, Windows Server 2008 (32/64bit), Windows Server 2008 R2, Windows Server 2012 (64bit), Windows Server 2012 R2, Windows Server 2016, Windows Vista, Windows XP SP3, Windows XP Professional x64 Edition SP2
Sound Power	Operation: 6.9 B (A)
Sound Pressure	Operation: 56 dB (A)
Power Supply	220V, 240V

ADDITIONAL FEATURES

Memory	2 MB included
LCD screen	Diagonal: 6.1 cm
Media Handling	ADF 2-sided copy (A4, plain paper)

OTHER FEATURES

Emulations	GDI
------------	-----

OTHER

Warranty	12 months Carry in, 100,000 pages Optional warranty extension available
----------	--

SUPPLIES

● EcoTank ET-MX1XX Series Black Bottle XL	C13T03M140 6,000 pages
● Maintenance Box	C13T04D100

LOGISTICS INFORMATION

SKU	C11CG91402BY
EAN code	8715946655086

EcoTank ET-M3140

INK YIELD DATA

T03M1

● 6,000 pages*

* Approx. page yield based on ISO/IEC 24711/24712 or ISO/IEC 29102/29103. Actual yield will vary depending on images printed and usage conditions. For more information visit <http://www.epson.eu/pageyield>

For more information please contact:

Home users: 0343 90 37766
Business users*: 0871 42 37766
Republic of Ireland: 01 436 7742
Or visit us at <https://www.epson.co.uk/contactus>
* 10p per minute plus network extras.

Web: www.epson.co.uk
www.epson.ie

Trademarks and registered trademarks are the property of Seiko Epson Corporation or their respective owners.
Product information is subject to change without prior notice.
Last extracted: 2019-01-07

EPSON[®]