



I  
13PCS

J  
26PCS

K  
1 3P CS

## Assembly Instructions

WE RECOMMEND INSTALLATION OF THIS LIGHTING FIXTURE BE DONE BY A LICENSED ELECTRICIAN.

WARNING \*\*\* SWITCH OFF THE MAIN ELECTRICAL SUPPLY FROM THE MAIN FUSE BOX/CIRCUIT BREAKER BEFORE INSTALLATION.

- Carefully remove all parts from the box
- Remove the mounting bracket (B) from the canopy (D) by loosening the screws (A)
- Taking off the open ring (F) and use the dimensions of the fixture as a guide, shorten the chain (E) as needed using a pair of chain pliers.
- Use the open ring (F) to link the chain (E) and the loop (G), then put the cable(H) and naked earth cable (I) through the chain(E) in every 3-4 rings until through the ceiling loop (J).
- INSURE THE ELECTRICITY SUPPLY IS TURNED OFF
- Affix the mounting bracket (B) on the outlet box
- Wrap both safety cable with nipples (C) , push the cable into the outlet box.
- Attach the canopy (D) to the mounting bracket (B) and secure with lock collar (A)
- Install the resin rods (I)(J)(K)(NOTE: (I)(J)(K)(J) in a group)on the lamp body as shown in the picture.
- Install the bulbs on the sockets
- Installation is complete , turn on power at fuse or circuit breaker.

\*\*\*Clean with a dry, soft cloth only. Use no harsh abrasives or chemical agents\*\*\*

