

**PARTNER**

CARE . TRUST . RESPONSIBILITY

**POS**

**151D**

La solución Entry Level definitiva





# Potencia con estilo

## Potente y robusto

POS 151D ofrece toda la potencia necesaria para cualquier negocio de Retail y Restauración. Su procesador J3455 o Intel i3 con 4GB Ram de serie ampliable a 8GB y su SSD 120GB permite trabajar agilmente en cualquier comercio

### IMPORTANTES CARACTERISTICAS



## Estilo y Rugerización


Pantalla Bezel Free plana 15"  
Resolución 1024 x 768  
10-point PCAP touch  
Cobertura rugerizada ante golpes líquidos y suciedad

## Potencia

Procesador Intel® Celeron®  
Quad Core J3455 o Intel i3  
Diseño Fanless  
SSD 120GB  
4 GB DDR3L RAM ampliables

## Amplia configurabilidad

VESA 100x100 y que permite ser adaptado en pared, en Soportes articulados o con otras diversas configuraciones




# Datos Técnicos 151D

- Pantalla Bezel-Free 10-point PCAP touch
- Procesador Intel® Celeron® J3455 o Intel® i3
- Finalizado rugerizado para soportar golpes, líquido y suciedad
- Diseño sin ventilador (Fanless)
- Soporta Windows 10 y Linux Ubuntu



Diseño Fanless  
(sin ventilador)

MODELL		POS-1511C
Display	Max Resolution	1024 x 768
	Size	15"
	Brightness	220 nits
	Colors	16.7M
	Contrast	400:1
	Response Time	8 ms
	Viewing Angle	Right 70° Left 70° / Upper 70° Lower 70°
	Technology	LCD with LED backlight
	Touch	10-point PCAP touch
System	CPU (fanless)	
	RAM	1 x DDR3L 1333 MHz SO-DIMM, standard 4 GB, up to 8 GB
	Storage	1 x 2.5" SATA II (3.0 Gbit/s), HDD or SSD storage 1 x mSATA
	OS	Support Windows 7, POS Ready 7, Windows 8.1, Windows 10, Linux (Ubuntu)
I/O Interface	Serial	3 x Serial ports, RS232 (DB9), DCD/5V/12V (COM1) & DCD/5V (COM2, COM3) selection on board
	LAN	1 x RJ45, IEEE 802.3 10/100/1000 Mbps Ethernet
	USB	3 x USB 2.0 1 x USB 3.0
	Cash Drawer	n/a
	DC in	1 x DC 12 V input power-jack
	Audio	1 x Line-out 3.5mm Jack 1 x Mic-in 3.5mm Jack
	Video	1 x VGA (up to 1920 x 1080)
	PS/2	Keyboard only
Optional Configuration	Attached peripherals	1 x MSR 1 x 24 key side keypad + MSR
Expansion Slot	Internal	1 x Mini-PCle
Speaker	Power	1 x 6 Watts



# Datos Técnicos

## 151D

MODELL		POS-1511C
Others	Colors	Charcoal Black
	VESA Mounting	100 x 100
	Material	Aluminum for main body and stand, ABS for "C" sharp housing
Power	Power Adapter	AC-In 100~240V / DC-Out 12 V 5 A, 60 W
Dimensions	w/o stand	374.2 mm (W) x 288.6 mm (H) x 64.5 mm (D)
	with stand	374.2 mm (W) x 308.7 mm (H) x 205.3 mm (D)
Weight	w/o stand	4.0 kg
	with stand	4.5 kg
Environment	Operating Temperature	0°C ~ 40°C
	Storage Temperature	-15°C ~ 55°C
	Operating Humidity	10% ~ 85%
	Storage Humidity	15% ~ 80%

\*Specification is subject of change without prior notice.  
Subject to alterations July 2018



# GRACIAS

¿Desea Contactar con nosotros?



Polo Sur, 19 – 28850 Torrejón de Ardoz – Madrid – España



+34 913 120 632



comercial@partner-tech.eu



www.partner-tech.eu



Descubra Partner Tech, Descargue nuestra APP ahora!

## Taiwan Headquarter

sales@partner.com.tw

## USA

sales@partnertechcorp.com

## EUROPE

info@partner-tech.eu

## UK

sales@partnertechuk.com

## Morocco

sales@partnertechna.com

## South Africa

sales@partnertech.co.za

## Middle East

info@partnertechme.com

## China

sales@partnertech.com.cn

## Australia

sales@partner-tech.com.au

## Japan

sales-jp@partner.com.tw

## South East Asia

ptse@partner.com.tw

Offices

## ALEMANIA HQ

Fasanenweg 25

22145 Hamburg

Germany

## ESPAÑA

Polo Sur 19

28850 Torrejón de

Ardoz

Madrid, Spain

## ESLOVENIA

Blatnica 10

1236 Trzin

Slovenia

## UK

Unit 11, Berkeley Court, Manor Park

WA7 ITQ Runcorn, Cheshire

United Kingdom

Europa