

CABINETS TO GO

SAVE MORE ON YOUR DREAM KITCHEN AND FLOOR

PRODUCT SPECIFICATION

Style	XRP1 4.2mm SPC
Construction	SPC (Stone Polymer Composite)
Wear Layer Thickness	6 mil
Overall Thickness	4.2mm (3.2 mm Core / 1 mm EVA Pad)
Attached Cushion	1mm EVA Ethylene Vinyl Acetate
Installation	Floating Uni-Click
FEATURES	
Bevel	Square
Texture	Standard
Plank Size	6" x 48"
Planks Per Carton	12
Sq. Ft. Per Carton	23.64
Carton Per Pallet	60
Sq. Ft. Per Pallet	1418.4
TESTING	
Slip Resistance / ASTM D 2047	Neolite Dry 0.91/Wet 0.56 - Leather Dry 0.82/ Wet 0.78
Dimensional Stability / ASTM F2199	Passes Less than 0.020" /ft.
Residual Indentation / ASTM F1914	Passes
Static Load Limit / ASTM F970	Passes
Flexibility / ASTM F 137	Passes 75mm Mandrel
Resistance to Heat / ASTM F 1514	Passes
Resistance to Light / ASTM 1515	Passes <8.0 Delta E specified Criteria
Resistance to Chemicals / ASTM F 925	Passes
Radiant Flux / ASTM 648	Meets or Exceeds Class 1 as specified in NFPA Life Safeth Code 101
Smoke Density / ASTM E 662 Flaming	Passes 450 or less
Smoke Density / ASTM E 662 Non-Flaming	Passes 450 or less
WARRANTY	10 Year Residential
ENVIRONMENTAL	
Indoor Air Quality	FloorScore© certified

01.01.2020