

# CABINETS TO GO

SAVE MORE  
ON YOUR  
DREAM KITCHEN  
AND FLOOR

## PRODUCT SPECIFICATION

---

Style	<b>XRP2 5mm SPC Tile</b>
Construction	<b>SPC (Stone Polymer Composite)</b>
Wear Layer Finish	<b>Urethane with Double UV Coating</b>
Wear Layer Thickness	<b>12 mil</b>
Overall Thickness	<b>5mm</b>
Attached Cushion	<b>EVA</b>
Installation	<b>Floating</b>

### FEATURES

Bevel	<b>Painted Bevel</b>
	<b>Standard Emboss</b>
Vinyl Layer	<b>100% Virgin, Phthalate Free</b>
Tile Size	<b>12" wide x 24" long</b>
Density	<b>2000+ kg/m<sup>3</sup></b>

### TESTING

Impact Sound Conduction / ASTM E492-09	<b>IIC 60</b>
Sound Transmission Class /ASTM E90-09	<b>STC 53</b>
Slip Resistance / ASTM D 2047	<b>0.088 Dry / 1.03 Wet</b>
Dimensional Stability / ASTM F2199	<b>Passes</b>
Short Term Indentation / ASTM F1914	<b>Passes</b>
Static Load Limit / ASTM F970	<b>Passes</b>
Flexibility / ASTM F 137	<b>Passes 75mm Mandrel</b>
Resistance to Heat / ASTM F 1514	<b>Passes</b>
Resistance to Light / ASTM 1515	<b>Passes</b>
Resistance to Chemicals / ASTM F 925	<b>5 Min Passes / 24 Hr. Passes</b>
Radiant Flux / ASTM 648	<b>&gt;0.45 watts/cm<sup>2</sup>, NFPA Class I</b>
Smoke Density / ASTM E 662	<b>Passes &lt;450</b>

### WARRANTY

**10 Year Residential**

### ENVIRONMENTAL

Indoor Air Quality **FloorScore® certified**