

CABINETS TO GO

SAVE MORE ON YOUR DREAM KITCHEN AND FLOOR

PRODUCT SPECIFICATION

Style	XRP3 8mm WPC
Construction	Class III High Performance LVP
Wear Layer Finish	Urethane with Double UV Coating
Wear Layer Thickness	20 mil (0.50 mm)
Overall Thickness	8mm (5mm core/1.5mm IXPE/1.5mm vinyl top)
Attached Cushion	1.5mm IXPE Cross Linked Polyethylene
Installation	Floating

FEATURES

Bevel	Micro Bevel
Texture	Standard Embossing
Vinyl Layer	100% Virgin, Phthalate Free
Plank Size	6" X 48"
Density	900 kgm/m ³

TESTING

Impact Sound Conduction / ASTM E492-09	IIC 62db
Sound Transmission Class /ASTM E90-09	STC 52
Slip Resistance / ASTM D 2047	>0.6
Dimensional Stability / ASTM F2199	Passes, Less than 0.020"/ft.
Short Term Indentation / ASTM F1914	Passes
Long Term Indentation / ASTM F970	Passes
Flexibility / ASTM F 137	Passes, 6mm Mandrel
Resistance to Heat / ASTM F 1514	Passes
Resistance to Light / ASTM 1515	Passes
Resistance to Chemicals / ASTM F 925	5 min = Passes, 24 hr = Passes
Radiant Flux / ASTM 648	>0.45 watts/cm ² , NFPA Class I
Smoke Density / ASTM E 662	Passes, <450

WARRANTY

50 Year Residential
10 Year Commercial

ENVIRONMENTAL

Indoor Air Quality FloorScore© certified

01.01.2020