

# CABINETS TO GO

SAVE MORE  
ON YOUR  
DREAM KITCHEN  
AND FLOOR

## PRODUCT SPECIFICATION

Style	XRP4- 8mm WPC
Construction	Class III High Performance LVP
Wear Layer Finish	Urethane with Double UV Coating
Wear Layer Thickness	20 mil (0.50 mm)
Overall Thickness	8mm (4.5mm core/1.5 IXPE/ 2mm Vinyl top)
Attached Cushion	1.5mm IXPE Cross Linked Polyethylene
Installation	Floating

### FEATURES

Bevel	V Groove Painted Design
Texture	EIR (Embossed in Register)
Vinyl Layer	100% Virgin, Phthalate Free
Plank Size	9" x 60"
Density	900 kg/m <sup>3</sup>

### TESTING

Impact Sound Conduction / ASTM E492-09	IIC 62db
Sound Transmission Class /ASTM E90-09	STC 52
Slip Resistance / ASTM D 2047	>0.6
Dimensional Stability / ASTM F2199	Passes, Less than 0.020"/ft.
Residual Indentation / ASTM F1914	Passes
Static Load Limit / ASTM F970	Passes
Flexibility / ASTM F 137	Passes, 6mm Mandrel
Resistance to Heat / ASTM F 1514	Passes
Resistance to Light / ASTM 1515	Passes
Resistance to Chemicals / ASTM F 925	5 min = Passes, 24 hr = Passes
Radiant Flux / ASTM 648	>0.45 watts/cm <sup>2</sup> , NFPA Class I
Smoke Density / ASTM E 662	Passes, <450

### WARRANTY

50 Year Residential  
10 Year Commercial

### ENVIRONMENTAL

Indoor Air Quality FloorScore® certified

1.1.2020