

CABINETS TO GO

SAVE MORE
ON YOUR
DREAM KITCHEN
AND FLOOR

PRODUCT SPECIFICATION

Style Number	XRP6	
Construction	SPC	
Wear Layer Finish	Urethane with Double UV Coating	
Wear Layer Thickness	20 mil (0.50 mm)	
Overall Thickness	6mm	
Attached Cushion	1 mm IXPE	
Installation	Floating	
FEATURES		
Bevel	Pressed	
Texture	EIR (Embossed in Register)	
Plank Size	9" x 60"	
Density		900 kg/m³
TESTING		
Impact Sound Conduction / ASTM E492-09	60 IIC	
Sound Transmission Class / ASTM E90-09	53 STC	
Slip Resistance / ASTM D 2047	Dry 0.76 / Wet 0.84	
Dimensional Stability / ASTM F2199	Pass	
Residual Indentation / ASTM F1914	Pass	
Static Load Limit / ASTM F970	Pass	
Resistance to Heat / ASTM F 1514	< 8.0 Delta E Meets specific criteria	
Resistance to Light / ASTM 1515	< 8.0 Delta E Meets specific criteria	
Resistance to Chemicals / ASTM F 925	Pass no change (0)	
Radiant Flux / ASTM 648	Meets class 1 rating as specified	
Smoke Density / ASTM E 662 Flaming	Passes 450 or less	
Smoke Density / ASTM E 662 Non-Flame	Passes 450 or less	
WARRANTY		
	50 YEAR RESIDENTIAL	
	10 YEAR COMMERCIAL	
ENVIRONMENTAL		
Indoor Air Quality	FloorScore® certified	

3/12/2020