

CABINETS TO GO

SAVE MORE ON YOUR DREAM KITCHEN AND FLOOR

PRODUCT SPECIFICATION

Style	XRP8- Composite Core
Construction	Class III High Performance LVP
Wear Layer Finish	Urethane with Double UV Coating
Wear Layer Thickness	20 mil
Overall Thickness	8mm (5mm WPC/1.5 IXPE/1.5mm Vinyl top)
Attached Cushion	1.5mm IXPE Cross Linked Polyethelene

FEATURES

Plank Edge	V Groove Painted Bevel
Texture	EIR (Embossed in Register)
Plank Size	Mixed Width 4.88" / 6.85" / 8.86" Mixed Length 19.45" / 39.29" / 59.05"
Installation	Floating

TESTING

Impact Sound Conduction / ASTM E492-09	IIC 62
Sound Transmission Class /ASTM E90-09	STC 52
Slip Resistance / ASTM D2047	0.92 Dry / 0.97 Wet
Dimensional Stability / ASTM F2199	Pass
Residual Indentation / ASTM F1914	Pass
Static Load Limit / ASTM F970	Pass
Resistance to Heat / ASTM F1514	Pass
Resistance to Light / ASTM F1515	Pass
Resistance to Chemicals / ASTM F925	Pass
Radiant Flux / ASTM E648	>0.45 watts/cm², NFPA Class I
Smoke Density / ASTM E662	Pass, <450

WARRANTY

Lifetime Residential
10 Year Commercial

ENVIRONMENTAL

Indoor Air Quality **FloorScore© certified**

12.10.2020