

Car Cover

Installation/Removal Instructions

The EVANNEX car cover has been designed specifically for Tesla Model S and may be used for both indoor and outdoor applications. We've created an **Installation (and Removal) Video** that can be viewed at www.evannex.com.

Quick Start Installation Steps:

Note: The front of the car cover can be identified by the black mesh openings that allow air to circulate into the front air dam grille and across the driver and passenger side wheels.



Step 1. Place the car cover at the center of the rear hatch. Unfold the car cover from rear to front along the longitudinal centerline of the Model S.

Step 2. Unfold the car cover laterally until it covers the hood, roof and rear hatch loosely. The soft cotton lining of the Car Cover should be in direct contact with the surface of your Model S.





Step 3. Starting at the side view mirror locations, cover the passenger and driver side view mirrors with the corresponding mirror sleeves (covers) sewn into the Car Cover.

Step 4. Pull the front of the Car Cover over the nose of the Model S using the elastic bottom to anchor it under the front fascia.

Step 5. Pull the rear of the Car Cover over the rear end of the Model S using the elastic bottom to anchor it under the rear bumper area.

Step 7 (optional). If you park in a particularly windy area, the car cover can be fastened with a bungee cord (not provided) by hooking the cord to grommets located midway along the base of the cover on both driver and passenger sides.

Quick Start Removal Steps:

Step 1. Loosen the front and rear of the car cover by pulling the elastic over the front fascia and rear end of the Model S.

Step 2. Fold the car cover from its base at the rocker panels upward to the longitudinal centerline of the Model S. Do this on both the driver and passenger sides, so that the car cover now covers the hood, roof and rear hatch.

Step 3. Fold again toward the longitudinal centerline of the Model S until the folded cover is no more that 18 – 24 inches in width.

Step 4. Beginning at the FRONT of the Model S, fold tightly (think: folding a sheet) in ~16 inch segments. Pull the car cover toward you as you fold it up so that all of your work is on the hood (frunk).

Step 5. Place the car cover in its carrying bag.

