

| General Specifications | |
|--|--|
| Power requirements | 220-240 V, 50/60 Hz |
| Energy consumption * | 1: 20, 2: 36, 3: 54, 4: 74, 5: 105, 6: 135 Watt; Standby: <1 Watt |
| Dimensions (without / with packaging) | H 71 x W 38 x D 41 cm / carton 1: H 84 x W 43 x D 45 cm; carton 2: H 32 x W 33 x D 33 cm |
| Weight (without / with packaging) | 20 kg / 25 kg |
| Air delivery (incl. filters) * | 1: 50, 2: 90, 3: 150, 4: 220, 5: 280, 6: 400 m ³ /h |
| Sound pressure/power level ** | L _p 1: 22, 2: 33, 3: 41, 4: 47, 5: 52, 6: 57 dB(A); L _w 1: 32, 2: 43, 3: 51, 4: 57, 5: 62, 6: 67 dB(A) |
| Fan motor | centrifugal, backward curved, with thermal protector, non-stop use approved |
| Control panel | 4-key touch-pad with 16 character 2-line LCD display |
| Air intake | dual arches at base of unit |
| Air outlet | 320° EvenFlow™ diffuser |
| Colour of main housing / locking arms | light grey / blue |
| Housing material | non off-gassing, impact-resistant, UV-stabilized ABS |
| Performance | |
| Total system efficiency (certified) | ≥ 99% for particles ≥ 0.3 µm (individually tested at highest fan speed) |
| Air delivery (certified) | yes (individually tested with all filters fitted) |
| Leak tested | yes |
| Filter Configuration | |
| Pre-filter | <p>GC HEPA Pre-Filter H11 (S)</p> <p>Purpose: control of coarse, fine & ultra-fine dust particles; protection of subsequent filters</p> <p>Media: non-woven glass microfiber HEPA filter</p> <p>Efficiency: ≥99% at ≥ 0.3 µm (class H11)</p> <p>Surface area: approx. 3.0 m²</p> |
| Gas & odour filter | <p>GC Filter Cartridge Set</p> <p>Purpose: control of a wide range or specific chemical substances and odours</p> <p>Media: granular activated carbon & impregnated alumina (AC/4 + IA/4)</p> <p>Weight: approx. 5.4 kg</p> |
| Post-filter | <p>GC Post-Filter Sleeve Set</p> <p>Purpose: control of fine & ultra-fine particulate matter</p> <p>Media type: electrostatically charged fiber</p> <p>Surface area: approx. 0.5 m²</p> |
| Features | |
| Display languages | 4 user-selectable languages: English, French, German, Italian (or Spanish) |
| Fan speed settings | 6 |
| Intelligent filter life monitor | yes (monitors actual usage of each individual filter) |
| Filter life status LEDs | 3 |
| Advanced timer | yes (allows programming of operating hours and weekdays) |
| Advanced fan speed selection | yes (allows programming of different fan speeds for 2 different time periods) |
| Adjustable filter load indices | 3 (large dust, chemicals and fine dust) |
| Supplied accessories | remote control (incl. battery), power cord with plug, deluxe casters, certificate of performance |
| Optional accessories | VMF wall-mount bracket, PF40 coarse dust pre-filter, InFlow , VM InFlow & OutFlow duct connections, FlexVac & VM FlexVac mobile & wall-mounted source capture kits, SMC side-mounted control panel |
| Electrical safety certification | IEC/IECEE (CB-Scheme), CE, SEV, KTL, EAC |

* per fan speed measured at 230V, 50Hz; tolerance ± 10% (± 10 m³/h); ** tolerance: ± 3 dB(A); All technical specifications are subject to change without prior notice.