

USAGE INFORMATION

TILE APPLICATIONS	RESIDENTIAL	LIGHT COMMERCIAL	COMMERCIAL
Floors			
Walls/Backsplashes			
Countertops			
Exterior			
PLEASE NOTE: Not recommended for ramp	os or floor areas exposed to water or heav	vy grease accumulation.	

TECHNICAL INFORMATION

TEST	RESULTS	ANSI STANDARDS	ASTM #
Abrasion Resistance (PEI)	Class IV/III	Class 0-V	ASTM C1027
Chemical Resistance	Resistant	As Reported	ASTM C650
Bonding Strength (psi)	>50 psi	≥50 psi	ASTM C482
Dynamic Coefficient of Friction (DCOF)*	>0.42	As Reported	ANSI A 137.1-2012
Scratch Hardness	8.0	MOHS 1-10	MOHS Scale
Water Absorption	<3.0%	3.0% - 7.0%	ASTM C373
Breaking Strength	>400 lbf.	>250 lbf.	ASTM C648
Frost Resistance	Resistant	As Reported	ASTM C1026
Stain Resistance	Resistant	As Reported	ASTM C1378
Crazing Resistance	Resistant	As Reported	ASTM C424
Thermal Shock	Resistant	As Reported	ASTM C484

*It is important to note that Dynamic Coefficient of Friction results can vary after installation due to the presence of foreign materials, such as water, oil and other materials the length of the human stride at the time of slip; type of floor finish and condition of shoe sole.









AMALFI STONE

Interceramic CRAFTED FOR LIFE

AMALFI STONE High Density Glazed Ceramic Floor Tile





















PEI III













Bianco Scala



Crema Vasari





PELIV



Noce Domenico

DECORATIVE ACCENTS



11½"x11½" (2"x4") Bricklay Mosaic






11½"x11½" (2"x4") Bricklay Mosaic



11½"x11½" (2"x4") Bricklay Mosaic

SIZES

TRIM (Available in all colors)







PELIV



Variation Rating: SUBSTANTIAL Substantial shade and texture variation with in each carton.









