

## USAGE INFORMATION

RESIDENTIAL	LIGHT COMMERCIAL	COMMERCIA
	0	

## TECHNICAL INFORMATION

TEST	RESULTS	ANSI STANDARDS	ASTM #
Abrasion Resistance (PEI)	Class IV/III	Class 0-V	ASTM C1027
Chemical Resistance	Resistant	As Reported	ASTM C650
Bonding Strength (psi)	>50 psi	≥50 psi	ASTM C482
Dynamic Coefficient of Friction (DCOF)*	>0.42	As Reported	ANSI A 137.1-2012
Scratch Hardness	6.5	MOHS 1-10	MOHS Scale
Water Absorption	<3.0%	3.0% - 7.0%	ASTM C373
Breaking Strength	>450 lbf.	>250 lbf.	ASTM C648
Frost Resistance	Resistant	As Reported	ASTM C1026
Stain Resistance	Resistant	As Reported	ASTM C1378
Crazing Resistance	Resistant	As Reported	ASTM C424
Thermal Shock	Resistant	As Reported	ASTM C484

\*It is important to note that Dynamic Coefficient of Friction results can vary after installation due to the presence of foreign materials, such as water, oil and other materials; the length of the human stride at the time of slip; type of floor finish and condition of shoe sole.















High Density Glazed Ceramic Floor Tile























PEI III









PEI III

LUMEN STATES UNITOUS EXTEROSORY

EXTEROSORY

EXTEROSORY

EXTEROSORY

SECTION OF THE CONTROL OF T



Grigio Belfiore





DECORATIVE ACCENTS

Bianco Valetta



12"x13" (2"x4") Victorian Mosaic



12"x13" (2"x4") Victorian Mosaic

Sabbia Mezzo



PEI IV



12"x13" (2"x4") Victorian Mosaic



12"x13" (2"x4") Victorian Mosaic

SIZES

TRIM (Available in all colors)







**PEI IV** 











