



Oak SW485



146 Tapestry




508 Armory



514 Drawbridge



519 Hearth




524 Tower



5022 Palisade (SW485)




533 Arrow



986 Trestle



1010 Chatelaine



5031 Baroque

Hickory SW486



993 Coat of Arms



7018 Romanesque (SW486)

CASTLEWOOD



Style Number	SW485	SW486
Construction	Engineered	Engineered
Thickness	9/16"	9/16"
Width	7½"	7½"
Species	White Oak	Hickory
Texture	Wire Brushed	Wire Brushed
Gloss Level	10%	10%
Janka Hardness Rating	1360	1926
Edge Description	Microbeveled	Microbeveled
End Description	Microbeveled	Microbeveled
SF per carton	31.09	31.09
SF per pallet	1,243.60	1,243.60
Installation	Nail, Staple, Glue, Float	Nail, Staple, Glue, Float
All measurements are nominal		Cartons may include random lengths

Features

- Wire brushing and matte finish recreates the look of vintage European oil-rubbed floors without the expensive maintenance
- Wide width and longer length planks showcase a vast range of character, knots, mineral streaks, and color tones
- High variation should be expected

Suggested Adhesive


Style #	Style Name	Coverage	Moisture	Additional Features
ADHESIVES				
HS105	35MC — Urethane	35 SF / gal for moisture 60 SF / gal as adhesive	No Moisture test required Up to 5 lbs. or 85% RH	Sound & crack suppressant
111SA	3-in-1 Ultra - MS	35 SF per gal. for moisture 70 SF per gal. as adhesive	No Moisture test required Up to 5 lbs. or 85% RH	Sound & crack suppressant
HS304	DMC140 — Urethane	35 SF / gal for moisture	No Moisture test required	
SWADH	UreBond Plus	35 SF / gal for moisture 60 SF / gal	Up to 8 lbs. or 85% RH Up to 5 lbs. or 85% RH	

We recommend that you use Shaw's adhesives to prolong the life, durability and performance of your beautiful new engineered floor.

Trim Pieces length: 78" (*Overlap Reducer and Overlap Stairnose are designed for floating installations only. These items are non-stocking — but are available through a quick-ship program. Delivery should take approximately 2 to 3 weeks.)



SRH12
Flush
Reducer



SORH2
*Overlap
Reducer



SSH12
Flush
Stairnose



SOSH2
*Overlap
Stairnose



SCH12
Threshold |
Carpet Reducer



TMH78
T-Molding



QTR96
Quarter
Round

Benefits



Filled knots and splits are to be expected in this distinctive product. These are not defects and are considered acceptable additions to the rustic charm and character of these products. While these characteristics are to be expected, it is entirely possible to also receive extremely clean planks with little to no distinct character.

