



STADIUM PLUS STADIUM PLUS XL

Classification	ASTM F-3261-17 Resilient flooring in modular format with Rigid Polymeric Core	
Size*	7" x 48" / 180mm x 1220mm (Plus) 9"x 60" / 235mm x 1522mm (Plus XL)	
Overall Thickness*	0.24" / 6.0 mm	
Wear Layer	20 mil / 0.50 mm featuring Cliff Shield finish	
Edge	Painted Beveled	
Standard Colors	4 standard colors (Plus) 8 Standard colors (Plus XL)	
Installation Method	Click	
Backing	1mm IXPE Backing	
Wear Limited Warranty	Lifetime Residential / 30-Year Commercial	
Recycled Content	This product contains no recycled content. 100 % recyclable post use.	
Packaging	PLANK (Plus) 7" X 48" 14.18 ft ² (1.32 m ²) per carton 6 pieces per carton 60 cartons per pallet 22 pallets per 20' container	PLANK (Plus XL) 9"X60" 19.25 ft ² (1.79 m ²) per carton 5 pieces per carton 56 cartons per pallet 17 pallets per 20' container
Weight Per Carton	30.14 lbs / 13.67 kg	40.41 lbs / 18.33 kg



Blitz - STX 6903

Chemical Resistance	ASTM F 925	Passed
Critical Radiant Flux	ASTM E 648-17	Class I, CRF ≥ 0.45
Dimensional Stability	ISO 23999	Passed
Residual Indentation	ASTM F 1914	Passed
Resistance to Heat	ASTM F 1514	Passed
Resistance to Light	ASTM F 1515	Passed
Smoke Density	ASTM E 662-15A	Passed
Static Load Limit	ASTM F 970	Passed
Thickness	ASTM F 387	Passed
STC Sound Testing	ASTM E 413-16	STC 62
IIC Sound Testing	ASTM E 989-06	IIC 70




Prevail STP 6701 (EIR)



Unstoppable STP 6703 (EIR)



Downfield STX 6901 XL (EIR)



Gridiron STX 6904 XL (EIR)



Victory STX 6906 XL (EIR)




Tailgate STX 6908 XL (EIR)



Unity STP 6702 (EIR)



Homecoming STP 6704 (EIR)



Blitz STX 6903 XL (EIR)



Glory STX 6905 XL (EIR)



Lateral Pass STX 6907 XL (EIR)



Championship STX 6910 XL (EIR)

*All measurements are nominal. + Sound Testing will vary depending on the specific floor/ceiling assembly.
Please visit www.earthwerks.com for full warranty details and installation guidelines. All specifications and offerings subject to change without notice.