



BRIGHTON®

Classification	ASTM F 1700-04 Class III, type A or B Solid Vinyl Floor Tile
Size*	7" x 48" / 177.8mm x 1219.2mm
Overall Thickness*	1/8" / 3.0mm
Wearlayer	6 mil / 0.15mm - Featuring Tuff Shield finish
Edge	Square
Standard Colors	6 standard colors
Installation Method	Glue Down
Wear Limited Warranty	20-Year Residential / 10-Year Light Commercial
Recycled Content	Contains a minimum of 50% recycled content. 100% recyclable post-use
Packaging	35 ft ² (3.25 m ²) per carton 15 pieces per carton 60 cartons per pallet 16 pallets per 20' container
Weight Per Carton	37.48 lbs / 17 kg



Winter Gates-BNP 7654


Chemical Resistance	ASTM F 925	Passed
Critical Radiant Flux	ASTM E 648-06	Class I, CRF \geq 0.45
Dimensional Stability	ASTM F 2199	Passed
+STC Sound Testing	ASTM E 492-09	+STC 61
+IIC Sound Testing	ASTM E 989-06	+IIC 67
Flexibility	ASTM F 137	Passed
Resistance to Heat	ASTM F 1514	Passed
Resistance to Light	ASTM F 1515	Passed
Smoke Density	ASTM E 662-06	Passed
Static Load Limit	ASTM F 970	Passed
Thickness	ASTM F 386	Passed



Winter Gates - BNP 7654



Cosmopolitan - BNP 7655



Gotham - BNP 7656



Soho Loft - BNP 7657



North Hampton - BNP 7658



Pismo Dunes - BNP 7659

*All measurements are nominal. +Sound Testing will vary depending on the specific floor/ ceiling assembly.

Please visit www.earthwerks.com for full warranty details and installation guidelines. All specifications and offerings subject to change without notice.