



DERBY®

Classification	ASTM F 1700-04 Class III, type A or B Solid Vinyl Floor Tile
Size*	6" x 36" / 152.4mm x 914.4mm
Overall Thickness*	.080" / 2.0mm
Wearlayer	8 mil / 0.20mm - PVC
Edge	Square
Standard Colors	6 standard colors
Installation Method	Glue Down
Wear Limited Warranty	20-Year Residential / 10-Year Light Commercial
Recycled Content	Contains a minimum of 50% recycled content. 100% recyclable post-use
Packaging	27 ft ² (2.51 m ²) per carton 18 pieces per carton 108 cartons per pallet 18 pallets per 20' container
Weight Per Carton	20.95 lbs / 9.5 kg



Evening Shadow-DRB 922


Chemical Resistance	ASTM F 925	Passed
Critical Radiant Flux	ASTM E 648-06	Class I, CRF ≥0.45
Dimensional Stability	ASTM F 2199	Passed
+STC Sound Testing	ASTM E 492-09	+STC 61
+IIC Sound Testing	ASTM E 989-06	+IIC 64
Flexibility	ASTM F 137	Passed
Resistance to Heat	ASTM F 1514	Passed
Resistance to Light	ASTM F 1515	Passed
Smoke Density	ASTM E 662-06	Passed
Static Load Limit	ASTM F 970	Passed
Thickness	ASTM F 386	Passed



Hidden Cove DRB 921



Evening Shadow DRB 922




Rambutan DRB 923



Hatteras DRB 924



Hope Chest DRB 925



Chocolate Mandolin DRB 926

*All measurements are nominal. +Sound Testing will vary depending on the specific floor/ ceiling assembly.

Please visit www.earthwerks.com for full warranty details and installation guidelines. All specifications and offerings subject to change without notice.