



PARKHILL® Plank

PARKHILL® EIR Plank

Classification	ASTM F 1700-04 Class III, type A or B Solid Vinyl Floor Tile
Size*	7" x 48" / 177.8mm x 1219.2mm
Overall Thickness*	0.25" / 6mm
Wearlayer	20 mil / 0.50mm, featuring Tuff Shields finish
Edge	Beveled
Standard Colors	6 standard planks / 6 EIR planks
Installation Method	2G Fold Down Click
Wear Limited Warranty	Lifetime Residential / 30-Year Commercial
Recycled Content	This product contains no recycled content. 100% recyclable post-use
Packaging	23.64 ft ² (2.20 m ²) per carton 10 pieces per carton 60 cartons per pallet 17 pallets per 20' container
Weight Per Carton	37.00 lbs / 16.78 kg



Parkhill® EIR - PKH 352

Chemical Resistance	ASTM F 925	Passed
Critical Radiant Flux	ASTM E 648-06	Class I, CRF ≥0.91
Dimensional Stability	ASTM F 2199	Passed
*STC Sound Testing	ASTM E 492-09	*STC 62
*IIC Sound Testing	ASTM E 989-06	*IIC 66
Flexibility	ASTM F 137	Passed
Resistance to Heat	ASTM F 1514	Passed
Resistance to Light	ASTM F 1515	Passed
Smoke Density	ASTM E 662-06	Passed
Static Load Limit	ASTM F 970	Passed
Thickness	ASTM F 386	Passed



Sequoia PKH 341



Sawmill PKH 342




CrossTimber PKH 343



DryWash PKH 344



Cocoon PKH 345



Bespoke PKH 346



Copperbrooke PKH 347 (EIR)




Stafford PKH 348 (EIR)



Smithwick PKH 349 (EIR)



Junction PKH 350 (EIR)



Grove Park PKH 351 (EIR)



Lakepoint PKH 352 (EIR)



*Sound Testing will vary depending on the specific floor/ ceiling assembly.

Please visit www.earthwerks.com for full warranty details and installation guidelines. All specifications and offerings subject to change without notice.