



SHERBROOKE® Plank

Classification	ASTM F 1700-04 Class III, type A or B Solid Vinyl Floor Tile
Size*	7" x 48" / 177.8mm x 1219.2mm
Overall Thickness*	0.25" / 5.5mm
Wearlayer	12 mil / 0.30mm, featuring Tuff Shields finish
Edge	Beveled
Standard Colors	12 standard planks
Installation Method	2G Fold Down Click
Wear Limited Warranty	30-Year Residential / 20-Year Light Commercial
Recycled Content	This product contains no recycled content. 100% recyclable post-use
Packaging	23.64 ft ² (2.20 m ²) per carton 10 pieces per carton 65 cartons per pallet 17 pallets per 20' container
Weight Per Carton	34.26 lbs / 15.54 kg



Sherbrooke® - SHB 2178


Chemical Resistance	ASTM F 925	Passed
Critical Radiant Flux	ASTM E 648-06	Class I, CRF ≥0.91
Dimensional Stability	ASTM F 2199	Passed
*STC Sound Testing	ASTM E 492-09	*STC 62
*IIC Sound Testing	ASTM E 989-06	*IIC 66
Flexability	ASTM F 137	Passed
Resistance to Heat	ASTM F 1514	Passed
Resistance to Light	ASTM F 1515	Passed
Smoke Density	ASTM E 662-06	Passed
Static Load Limit	ASTM F 970	Passed
Thickness	ASTM F 386	Passed




Natural SHB 2171




Chestnut SHB 2172



Newport SHB 2173



Esperanza SHB 2174



Shadow SHB 2175



Mineral SHB 2176



Bellevue SHB 2177



Estrie SHB 2178



Township SHB 2179



Gristmill SHB 2180



Hatley SHB 2181



Brompton SHB 2182

*Sound Testing will vary depending on the specific floor/ ceiling assembly.

Please visit www.earthwerks.com for full warranty details and installation guidelines. All specifications and offerings subject to change without notice.