




UPTON®

Classification	ASTM F 1700-04 Class III, type A or B Solid Vinyl Floor Tile
Size*	7" x 48" / 177.8mm x 1219.2mm
Overall Thickness*	1/8" / 3.0mm
Wearlayer	20 mil / 0.50mm - Featuring Tuff Shield finish
Edge	Square
Standard Colors	6 standard colors
Installation Method	Glue Down
Wear Limited Warranty	Lifetime Residential / 30-Year Commercial
Recycled Content	Contains a minimum of 50% recycled content. 100% recyclable post-use
Packaging	35 ft ² (3.25 m ²) per carton 15 pieces per carton 60 cartons per pallet 16 pallets per 20' container
Weight Per Carton	37.48 lbs / 17 kg




Winter Gates-UPP 7121

Chemical Resistance	ASTM F 925	Passed
Critical Radiant Flux	ASTM E 648-06	Class I, CRF \geq 0.45
Dimensional Stability	ASTM F 2199	Passed
+STC Sound Testing	ASTM E 492-09	+STC 61
+IIC Sound Testing	ASTM E 989-06	+IIC 67
Flexibility	ASTM F 137	Passed
Resistance to Heat	ASTM F 1514	Passed
Resistance to Light	ASTM F 1515	Passed
Smoke Density	ASTM E 662-06	Passed
Static Load Limit	ASTM F 970	Passed
Thickness	ASTM F 386	Passed



Winter Gates - UPP 7121



Cosmopolitan - UPP 7122



Gotham - UPP 7123



Soho Loft - UPP 7124



North Hampton - UPP 7125



Pismo Dunes - UPP 7126

*All measurements are nominal. +Sound Testing will vary depending on the specific floor/ ceiling assembly.

Please visit www.earthwerks.com for full warranty details and installation guidelines. All specifications and offerings subject to change without notice.