Wood Classic Plank

Classification	ASTM F 1700-04 Class III, type A or B Solid Vinyl Floor Tile
Size*	7.24" x 37.4" / 184mm x 950mm
Overall Thickness*	1/8"/ 3.0mm
Wearlayer	20 mil / 0.50mm - Protected by urethane coating (PU)
Construction	Layered plank consisting of wearlayer, film and backing.
Edge	Square
Standard Colors	7.24" x 37.4": 6 standard colors
Installation Method	Glue Down
Wear Limited Warranty	Lifetime Residential/ 30-Year Commercial
Recycled Content	This product contains 50% recycled content.100% recyclable post-use.
Packaging	7.24" x 37.4": 35.74 ft² (3.32 m²) per carton 19 pieces per carton 50 cartons per pallet 18 pallets per 20' container
Weight Per Carton	43.78lbs / 19.86kg

Product Testing

Chemical Resistance	ASTM F 925	Passed
Critical Radiant Flux	ASTM E 648-06	Class I, CRF ≥0.45
Dimensional Stability	ASTM F 2199	Passed
Flexibility	ASTM F 137	Passed
Resistance to Heat	ASTM F 1514	Passed
Resistance to Light	ASTM F 1515	Passed
Smoke Density	ASTM E 662-06	Passed
Static Load Limit	ASTM F 970	Passed
Thickness	ASTM F 386	Passed

WE ARE LVT™
STYLE SERVICE AVAILABILITY

*All measurements are nominal.

Please visit www.earthwerks.com for full warranty details and adhesive/application recommendations.

floor score
by SCScertified.