



FREMONT HICKORY



Style Number	SW592
Construction	Epic Plus
Thickness	3/8" (8.2mm)
Width	5"
Species	Hickory
Texture	Heavy Scraped
Gloss Level	20%
Janka Hardness Rating	2584
Edge Description	Pillowed
End Description	Pillowed
SF per carton	23.66
SF per pallet	1,419.60
Installation	Nail, Staple, Glue, Float
All measurements are nominal	Cartons may include random lengths

Features

- Beautifully scraped texture accentuates and highlights the natural grain, knots, and rustic character of this hickory hardwood floor
- A strong color palette that lends itself to both classic and contemporary decor


Suggested Recommendations

Style #	Style Name	Coverage	Moisture	Additional Features
ADHESIVES				
HS105	35MC – Urethane	35 SF / gal for moisture 60 SF / gal as adhesive	No Moisture test required Up to 5 lbs. or 85% RH	Sound & crack suppressant
111SA	3-in-1 Ultra - MS	35 SF per gal. for moisture 70 SF per gal. as adhesive	No Moisture test required Up to 5 lbs. or 85% RH	Sound & crack suppressant
HS304	DMC140 – Urethane	35 SF / gal for moisture	No Moisture test required	
SWADH	UreBond Plus	35 SF / gal for moisture 60 SF / gal	Up to 8 lbs. or 85% RH Up to 5 lbs. or 85% RH	

Trim Pieces length: 78" (*Overlap Reducer and Overlap Stairnose are designed for floating installations only. These items are non-stocking – but are available through a quick-ship program. Delivery should take approximately 2 to 3 weeks.)



SRH38
Flush
Reducer



SORH8
*Overlap
Reducer



SSH38
Flush
Stairnose



SOSH8
*Overlap
Stairnose



SCH38
Threshold |
Carpet Reducer



TMH78
T-Molding



QTR96
Quarter
Round

Benefits

