



PARKHILL® Tile

Classification	ASTM F 1700-04 Class III, type A or B Solid Vinyl Floor Tile
Size*	12" x 24" / 304.8mm x 609.6mm
Overall Thickness*	0.25" / 6mm
Wearlayer	20 mil / 0.50mm, featuring Tuff Shields finish
Edge	Beveled
Standard Colors	6 standard colors
Installation Method	2G Click
Wear Limited Warranty	Lifetime Residential / 30-Year Commercial
Recycled Content	This product contains no recycled content. 100% recyclable post-use
Packaging	23.56 ft ² (2.19 m ²) per carton 12 pieces per carton 60 cartons per pallet 17 pallets per 20' container
Weight Per Carton	37.00 lbs / 16.78 kg



Chemical Resistance	ASTM F 925	Passed
Critical Radiant Flux	ASTM E 648-06	Class I, CRF ≥0.91
Dimensional Stability	ASTM F 2199	Passed
Flexibility	ASTM F 137	Passed
Resistance to Heat	ASTM F 1514	Passed
Resistance to Light	ASTM F 1515	Passed
Smoke Density	ASTM E 662-06	Passed
Static Load Limit	ASTM F 970	Passed
Thickness	ASTM F 386	Passed



Gabbro
PKT 370



Strata
PKT 371



Montecelio
PKT 372



Terrace
PKT 373



Apatite
PKT 374



Sandstone
PKT 375

Please visit www.earthwerks.com for full warranty details and installation guidelines. All specifications and offerings subject to change without notice.