## **RIVERSTONE**









shawfloors.com 05.10.2017

## RIVERSTONE



FI OORS

Style Number	SW593
Construction	EPIC Plus
Thickness	Nominal 3/8"
Width	6¾″
Species	Hickory
Texture	Heavy Scraped
Gloss Level	20%
Janka Hardness Rating	2584
Edge Description	Pillowed
End Description	Pillowed
SF per carton	30.48
SF per pallet	1,371.60
Installation	Nail, Staple, Glue, Float
All measurements are nominal	Cartons may include random lengths

## **Features**

Suggested Recommendations

- Scraped hickory in a low gloss color palette that ranges from cool to warm
- The chattered and scraped surface accentuates the naturally wide range of character found in the hickory hardwood species
- High variation in color, scrape and texture should be expected from plank to plank

Style #	Riverstone	Coverage	Moisture	Additional Features		
ADHESIVES						
HS105	35MC — Urethane	35 SF / gal for moisture	No Moisture test required	Sound & crack suppressant		
		60 SF / gal as adhesive	Up to 5 lbs. or 85% RH			
111SA	3-in-1 Ultra - MS	35 SF per gal. for moisture	No Moisture test required	Sound & crack suppressant		
		70 SF per gal. as adhesive	Up to 5 lbs. or 85% RH			
HS304	DMC140 — Urethane	35 SF / gal for moisture	No Moisture test required			
SWADH	UreBond Plus	35 SF / gal for moisture	Up to 8 lbs. or 85% RH			
		60 SF / gal	Up to 5 lbs. or 85% RH			

**Trim Pieces** length: 78" (\*Overlap Reducer and Overlap Stairnose are designed for floating installations only. These items are nonstocking — but are available through a quick-ship program. Delivery should take approximately 2 to 3 weeks.)



shawfloors.com 05.10.2017