




Riverside

SPC Click



Willamette RVS 1705



Merrimack RVS 1706




Rogue RVS 1707



Platte RVS 1708



Duncan RVS 1709



Washita RVS 1710

Size*

7" x 48" / 180mm x 1220mm

Overall Thickness*

5mm / 1mm Attached Pad

Wearlayer

0.15 (6mil) Superior Coating

Locking

I4F

Edge

Square

Wear Limited Warranty

20-Year Residential / 10-Year Light Commercial

Packaging

18.91 ft² per carton / 1.75 sm²

8 pieces per carton

60 cartons per pallet / 19 pallets per container

32.43 lb per carton / 14.71 kg per carton

Weight Per Carton

32.43 lb per carton / 14.71 kg per carton

1,134.60 SQFT/Pallet

Sound Rating

STC: 62

IIC: 70

IXPE Underlayment

- Closed cell structure will not absorb moisture or promote mildew growth as compared to other natural underlayments
- Hypo allergenic
- Comfortable under foot
- Superior sound deadening qualities
- Approved over radiant heat
- Can go over all types of sub floors and existing hard surface flooring



SWIFF-TRAIN
C O M P A N Y

*All measurements are nominal. | Please visit www.swiff-train.com for full warranty details and installation guidelines. All specifications and offerings subject to change without notice.

