SEQUOIA HICKORY

engineered





Shaw FLOORS

SEQUOIA HICKORY



FLOORS

Style Number	SW539	SW545	SW546	
Construction	Epic Plus	Epic Plus	Epic Plus	
Thickness	3/8" (8.2mm)	3/8" (8.2mm)	3/8" (8.2mm)	
Width	5″	6¾″	3¼", 5, 6¾" mixed - packaged together	
Species	Hickory	Hickory	Hickory	
Texture	Heavy Scraped	Heavy Scraped	Heavy Scraped	
Gloss Level	20%	20%	20%	
Janka Hardness Rating	2584	2584	2584	
Edge Description	Pillowed	Pillowed	Pillowed	
End Description	Pillowed	Pillowed	Pillowed	
SF per carton	23.66	30.48	34.69	
SF per pallet	1,419.60	1,371.60	1,561.05	
Installation	Nail, Staple, Glue, Float	Nail, Staple, Glue, Float	Nail, Staple, Glue, Float	
All measurements are nominal		Cartons may include random lengths		

Features

- Heavy scraping creates a rustic, time-worn visual
- Pillowed edges and ends give each plank a pronounced sculpted look
- Multiple width options allow you to choose from a single width installation or a unique mixed width floor

Sundry Recommendations

Sundry Recommendations						
Style #	Style Name	Coverage	Moisture Test			
ADHESIVES						
HS105	35MC — Urethane	35 SF / gal for moisture	No Moisture test required	Sound control & crack suppressant		
		60 SF / gal as adhesive	Up to 5 lbs. or 85% RH			
111SA	3-in-1 Ultra — MS	35 SF / gal for moisture	No Moisture test required	Sound control & crack suppressant		
		70 SF / gal as adhesive	Up to 5 lbs. or 85% RH			
HS304	DMC140 — Urethane	35 SF / gal for moisture	No Moisture test required			
SWADH	UreBond Plus	35 SF / gal for moisture	Up to 8 lbs. or 85% RH			
		60 SF / gal	Up to 5 lbs. or 85% RH			

Trim Pieces length: 78" (*Overlap Reducer and Overlap Stairnose are designed for floating installations only. These items are non-stocking — but are available through a quick-ship program. **Delivery should take approximately 2 to 3 weeks**.)



