

### tile specifications

style name	wired tile	
style number	54492	
construction	textured loop	
fiber	eco solution q® nylon	
dye method	100% solution dyed	
	<b>english</b>	<b>metric</b>
	.....	
pattern repeat	none	
tufted weight	14.0	474.68 g/m <sup>2</sup>
gauge	1/10	39.37 per 10 cm
stitches per inch	8.5	33.46 per 10 cm
finished pile thickness	0.094	2.39 mm
total thickness	0.246	6.25 mm
average density	5362	9.98 kilotex
product size	24" x 24"	61 cm x 61 cm
primary backing	synthetic	
secondary backing	ecoworx® tile	
protective treatments	ssp protective treatments	
gsa approved product	yes	


### testing

radiant panel	class I
nbs smoke	less than 450
electrostatic propensity	less than 3.5 kv

### warranties

lifetime commercial limited

### installation method



### coordinating products

54491 | hook up tile

Specifications are subject to nominal manufacturing variances. Material supply and/or manufacturing processes may necessitate specification changes without notice. This carpet is an exclusive design and may not be duplicated in any manner. Use of this design in the creation of another carpet design is also strictly prohibited. Visit [phillyqueencommercial.com/Html/PerformanceTesting](http://phillyqueencommercial.com/Html/PerformanceTesting) for more information.

