



Skipdash Type II Traffic Paint

Fast Dry Supreme

Acrylic Waterborne Traffic Paint

User friendly, complies with all V.O.C. emissions and E.P.A. standards.

GENERAL: Skipdash Type II Pavement Paint meets Federal Specifications TT-P-1925E, Type I and II dries very fast, made for traffic areas and runways. No traffic pickup in less than ten minutes when applied properly under normal conditions or can be dried in one to two minutes when heated to 140 degrees (60°C) to 150 degrees (66°C) and conforms to current VOC regulations

- ❖ Meets Federal Spec. TT-P-1925E
- ❖ Very fast drying time
- ❖ Superior quality
- ❖ Good for Roadways and Airports
- ❖ Concrete or Asphaltic Surfaces

SURFACE

PREPARATION: Surface should be clean and free from dirt, dust, debris, and oil. Concrete surfaces should be etched prior to use.

APPLICATION: Mix Paint well prior to painting pavement or surface. Use brush, roller or spray to apply. Best application results will occur for spray applications if the paint is strained. Lower temperatures and higher humidity will require longer drying time. Reflective glass beads may be added to improve reflectivity.

COVERAGE: 400 to 450 linear feet of 4" stripe per gallon (@ 12.0 mil. wet film)

CAUTION: KEEP FROM FREEZING. Do not stripe when rain is in forecast, on wet surfaces, or when temperature is below 45°F. Wash tools in water. Use a suitable paint thinner if material has dried. Do not store in direct sunlight. Container should be closed when not in use. Because of alkali inherent in concrete surfaces there is no product guarantee on these. Keep out of the reach of children.

PACKAGING: 5 gallon pails, 55 gallon drums and 275 gallon tote tanks.

PRODUCT INFORMATION

MATERIAL SPECIFICATIONS:

REQUIREMENTS:

Weight per gallon, ASTM D1010 (lbs).....	13.30 – 14.00
Viscosity @ 77°F, ASTM D562 (Kreb's Stormer Unit) for ambient application.....	75 – 80 KU
	for heat application.....
	85 – 100 KU
% Weight solids.....	74.00 ± 2.00
% Volume solids.....	58.00 ± 2.00
Dry Time (15 mil. – wet) @ 77°F & 50% R.H. Dry to no pick-up.....	10 – 15 min
VOC, grams/liter.....	150
Dry opacity, White & colors.....	0.92
Fineness of dispersion, Hegman.....	3.0
Directional reflectance of white paint, %.....	85
Bleeding ratio.....	0.95

This information is to assist customers in determining if this product is suitable for the proposed application, and to satisfy themselves as to the suitability of the contents. Nothing herein shall constitute a warranty, express or implied, including any warranty of merchantability or fitness, nor is protection from any law or patent implied. 12/8/05