

MR360 Machine Control Receiver



Increase construction productivity...

The optimum in time saving for all grader, dozer, bobcat or scraper operations. Full 360° reception and in-cab display for easy construction and site preparation.

- 360° reception range
- Magnetic or screw clamp
- In-cab display
- Large 250mm pick-up board
- Fits to all machines and detects from all red beam lasers



**2YR
WARRANTY**

Specifications

Machine control receiver	012-401515
Accuracy fine	+/-3mm to +/-12mm
Accuracy course	+/-5mm to +/-25mm
Rechargeable Batteries	7.2v Ni/Mh
Operating time	40hr
Charge time	10hr
Operating temp	-20°C to +50°C
Pick-up length	250mm
In-cab display	with 5m cable
Waterproof, Dust proof	IP66

SECTION 2
Laser Leveling

LAR28/LAR32 Auto-level Range



Combining an all steel, fully sealed housing for all weather protection and high magnification. IMEX LAR 28 and LAR32 are the most robust auto-levels available. A magnetic damping compensator ensure better stability and reliability in all conditions.

**BEST
SELLER!**



- Steel, fully sealed housing
- Magnetic damping compensator
- 28x or 32x magnification

	012-IOLAR28	012-IOLAR32
Standard deviation 1km double run	1.5mm	1.0mm
Magnification	28x	32x
Horizontal circle	360° graduations	360° graduations
Compensator	Magnetic Damping	Magnetic Damping
Objective Aperture	34mm	34mm
Weight	1.8kg	1.8kg

**2YR
WARRANTY**