



MATERIALS:

Connector: BNC (M) and BNC (F)

Body: Tarnish Resistant Plating, Center Contact: Female - Gold Plated Beryllium Copper, Male - Gold Plated Brass

Solder Turret Terminal Screws: Steel

Shielded Housing: Die cast aluminum alloy A380 or A384

Finish: Blue baked enamel per Federal Standard 595 #25109 over Phosphoric Etch per MIL-C-15328

Marking: "Pomona Electronics Calif."

Cover: 1.02(.040) thick aluminum #1100-H14 anodized

Marking "Pomona 2401"

Screws: Steel 4 ea. #2-32 x 1/4" Pan Head self-tapping

RATINGS:

Operating Voltage: Inner conductor/Shield: 500 VRMS Max.

Operating Temperature: -55°C to +150°C

Nominal Impedance: 50 Ohms

ORDERING INFORMATION: Model 2401

All dimensions are in inches. Tolerances (except noted): .xx = ±.02" (.51 mm), .xxx = ±.005" (.127 mm).

All specifications are to the latest revisions. Specifications are subject to change without notice.

Registered trademarks are the property of their respective companies. Made in USA

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[Pomona:](#)

[2401](#)