

# How do you install a set of Buffalo Straps?

Read the procedure below or watch the video through our website. [Click link](#) or go to [www.TemboTusk.com](http://www.TemboTusk.com) click the products page and click on the Buffalo Straps side bar link.

1. Using the short end with the buckle, tread the loop through the top of the fridge handle.
2. Thread the buckle down through the loop.
3. Pull the buckle tight. The strap should look like it has a neck tie.
4. Using the long loose end, thread the loop through the anchor point.
5. Thread the end of the long strap through the loop.
6. Pull the strap tight. The strap should look like it has a neck tie.
7. Thread the end of the long strap through the buckle and snug tight.
8. The Buffalo Strap is now attached.
9. Complete the installation by attaching all four straps.

**If the Buffalo Strap is installed correctly; a downward pull on the strap should tighten the strap.**

Should you have any issues or question with our Buffalo Straps, please don't hesitate to call or email.

Thank you,

Jerry L'Ecuyer  
TemboTusk, Llc.  
714 396-4549  
[info@TemboTusk.com](mailto:info@TemboTusk.com)  
[www.TemboTusk.com](http://www.TemboTusk.com)



## How to install a set of Buffalo Straps



Using the short end of the buckle, thread the loop through the top of the fridge handle. Thread the buckle down through the loop.




Pull the buckle tight. The strap should look like a neck tie.



Using the long loose end, thread the loop through the anchor point and thread the end of the strap through the loop.



Pull the strap tight, it should look like a neck tie.



Thread the long end of the strap through the buckle and pull tight.



The installed Buffalo Strap should look this this.



Complete the installation by attaching all four straps.



If the straps are too long, cross them at the fridge handle & attach them to the opposite corners. The crossed straps should look like the last picture. Tightened the straps equally.