One-Man Eveook Ladder Installation Basic Harness Setup Right Side – Lanyard w/Goblin Left Side – Lanyard w/C+C+2N+G*

Eveook Ladder System Setup, With One Person: Ladder w/Line Guides, Ladder

Line-Thrower, Cube, Rope, Blackbird, Tape, Cones, 2 Eveooks, Giant Adjustable Lifeline, Prusik, Hp Measure

Eveook System Install with Ladders, One Person:

Line, Line Thrower, Ears Line, Line Thrower, Line Line, Line Thrower, Ears

Tie, Tie, Untie, Attach Blackbird, Eveook, Eveook, Blackbird, Eveook, Tape, Rope, Tail Pull Rope + 2, Up 3.5, Mule Goblin, Pull, Giant, Mule Lifeline, Prusik, Hp

*C=Carabiners, N=Nanobiner, G=Glove, Hp = House protection (tape & rope guards)

(Proceed to top right of page)

Tie - Tie rope on first side
Tie - Tie rope on second side
Untie - Untie rope on first side
Attach - Attach personal Goblin to rope, first side

Blackbird - Attach Blackbird to harness Eveook - Put Eveook on shoulder Eveook - Put Eveook on roof Blackbird - Tape Blackbird to roof Eveook - Set Eveook on Blackbird

Tape - Remove tape from BlackbirdRope - Position rope along the side of EveookTail - Attach Blackbird tail to ladder

Translation summary of card:

Basic Harness Setup includes long lanyard with Goblin from ventral D-ring, stored on right-side gear loop. Short lanyard from ventral D-ring stored on left-side gear loop, next to extra carabiner, 2 nanobiners and a glove on a nanobiner if chosen.

Installation gear includes 2 - 28' extension ladders, one or both with line guides; line-thrower, throwline cube, anchor-line rope, Blackbird, tape, safety cones, 2 Eveooks, adjustable lifeline and Hp (tape & roof/rope guards)

Measure distance over house.

Installation Summary First Side: Line - Setup lines on first side prior to launching line. Line Thrower - Get line thrower. Ears - Put on hearing protection.

Line - Place line in line guide. Line Thrower - Launch throwline across roof. Line - Remove line from line guide.

Line - Untie line from side of ladder Line Thrower - Put away line-thrower Ears - Put away hearing protection (Proceed below, to the left.)

Pull Rope + 2 - Pull rope to light tension + 2'
Up 3.5 - Raise rope 3.5'
Mule - Tie Mule Overhand, check first side, untie

Goblin - Attach personal Goblin to anchor line Pull - Tension line from first side Giant - Attach Eveook to anchor line with Giant Mule - Tie mule overhand knot at Giant

Lifeline - Attach adjustable lifeline to anchor line Prusik - Attach Prusik or Prusiks Hp - Protect house and rope with roof/rope guards and tape