

## Rim User Manual: Chart Summary: Older Model Years:

Mtn 26"									
	Frequency i19 26"	TCS	Cross Country	Condition 3	Disc	559 x 19C	559	19	24
	Frequency i23 26"	TCS	Trail/All Mountain	Condition 4	Disc	559 x 23C	559	23	28
	Laser TCS XC	TCS	Cross Country	Condition 3	Disc	559 x 19C	559	19	24
	Laser TCS Trail	TCS	Trail	Condition 4	Disc	559 x 21C	559	21	26
	Laser TCS All Mountain Race	TCS	All Mountain	Condition 4	Disc	559 x 23C	559	23	28
	Laser TCS Freeride	TCS	Freeride	Condition 4	Disc	559 x 23C	559	23	28
	Laser TCS Downhill	TCS	Downhill	Condition 4	Disc	559 x 27C	559	27	32
Mountain 29"									
	Frequency i19 29"	TCS	Cross Country	Condition 3	Disc	622 x 19C	622	19	24
	Frequency i23 29"	TCS	Trail/All Mountain	Condition 4	Disc	622 x 23C	622	23	28
	Laser TCS XC 29"	TCS	Cross Country	Condition 3	Disc	622 x 19C	622	19	24
	Laser TCS Trail 29"	TCS	Trail	Condition 4	Disc	622 x 21C	622	21	26
	Laser TCS All Mountain Race 29'	TCS	All Mountain	Condition 4	Disc	622 x 23C	622	23	28

Bicycle Type	WTB Rim Name	WTB Rim Standard	Industry Standard Name for Intended Use	ASTM Intended Use Classification	Brake Type	ISO / ETRTO Rim Size Designation	Rim Bead Seat Diameter (in mm)	Inner Rim Width (in mm)	TCS Rim Tape Width (in mm)
Mountain 26"									
	Laser TCS Cross Country	TCS	Cross Country	Condition 3	Disc	559 x 19C	559	19	24
	Laser TCS Trail	TCS	Trail/All Mountain	Condition 4	Disc	559 x 21C	559	21	26
	Laser TCS All Mountain Race	TCS	All Mountain	Condition 4	Disc	559 x 23C	559	23	28
	Laser TCS Freeride	TCS	Freeride	Condition 4	Disc	559 x 23C	559	23	28
Mountain 29"									
	Laser TCS Trail 29"	TCS	Trail/All Mountain	Condition 4	Disc	622 x 21C	622	21	26

Bicycle Type	WTB Rim Name	WTB Rim Standard	Industry Standard Name for Intended Use	ASTM Indended Use Classification	Brake Type	ISO / ETRTO Rim Size Designation	Rim Bead Seat Diameter	Inner Rim Width (in mm)	TCS Rim Tape Width (in mm)
<b>Mountain 26"</b>									
	Frequency Team i19 26"	TCS	Cross Country	Condition 3	Disc	559 x 19c	559	19	24
	Frequency Team i23 26"	TCS	Trail / All Mountain	Condition 4	Disc	559 x 23c	559	23	28
	Frequency Race i19 26"	TCS	Cross County	Condition 3	Disc	559 x 19c	559	19	24
	Frequency Race i23 26"	TCS	Trail / All Mountain	Condition 4	Disc	559 x 23c	559	23	28
	ST i19 26"	TCS	Cross Country	Condition 3	Disc	559 x 19c	559	19	24
	ST i23 26"	TCS	Trail / All Mountain	Condition 4	Disc	559 x 23c	559	23	28
<b>Mountain 29"</b>									
	Frequency Team i19 29"	TCS	Cross Country	Condition 3	Disc	622 x 19c	622	19	24
	Frequency Team i23 29"	TCS	Trail / All Mountain	Condition 4	Disc	622 x 23c	622	23	28
	Frequency Race i19 29"	TCS	Cross Country	Condition 3	Disc	622 x 19c	622	19	24
	Frequency Race i23 29"	TCS	Trail / All Mountain	Condition 4	Disc	622 x 23c	622	23	28

## Model Year 2013

### Model Year 2014

Bicycle Type	WTB Rim Name	WTB Rim Standard	Industry Standard Name for Intended Use	ASTM Indended Use Classification	Brake Type	ISO / ETRTO Rim Size Designation	Rim Bead Seat Diameter	Inner Rim Width (in mm)	TCS Rim Tape Width (in mm)
<b>Mountain 26"</b>									
	Frequency Team i19 26"	TCS	Cross Country	Condition 3	Disc	559 x 19c	559	19	24

	Frequency Team i23 26"	TCS	Trail / All Mountain	Condition 4	Disc	559 x 23c	559	23	28
	Frequency Race i19 26"	TCS	Cross Country	Condition 3	Disc	559 x 19c	559	19	24
	Frequency Race i23 26"	TCS	Trail / All Mountain	Condition 4	Disc	559 x 23c	559	23	28
	ST i19 26"	TCS	Cross Country	Condition 3	Disc	559 x 19c	559	19	24
	ST i23 26"	TCS	Trail / All Mountain	Condition 4	Disc	559 x 23c	559	23	28
<b>Mountain 27.5" / 650b</b>									
	Frequency Team i19 27.5" / 650b	TCS	Cross Country	Condition 3	Disc	584 x 19c	584	19	24
	Frequency Team i23 27.5" / 650b	TCS	Trail / All Mountain	Condition 4	Disc	584 x 23c	584	23	28
	Frequency Race i19 27.5" / 650b	TCS	Cross Country	Condition 3	Disc	584 x 19c	584	19	24
	Frequency Race i23 27.5" / 650b	TCS	Trail / All Mountain	Condition 4	Disc	584 x 23c	584	23	28
	ST i19 27.5" / 650b	TCS	Cross Country	Condition 3	Disc	584 x 19c	584	19	24
	ST i23 27.5" / 650b	TCS	Trail / All Mountain	Condition 4	Disc	584 x 23c	584	23	28
<b>Mountain 29"</b>									
	Frequency Team i19 29"	TCS	Cross Country	Condition 3	Disc	622 x 19c	622	19	24
	Frequency Team i23 29"	TCS	Trail / All Mountain	Condition 4	Disc	622 x 23c	622	23	28
	Frequency Race i19 29"	TCS	Cross Country	Condition 3	Disc	622 x 19c	622	19	24
	Frequency Race i23 29"	TCS	Trail / All Mountain	Condition 4	Disc	622 x 23c	622	23	28

	ST i19 29"	TCS	Cross Country	Condition 3	Disc	622 x 19c	622	19	24
	ST i23 29"	TCS	Trail / All Mountain	Condition 4	Disc	622 x 23c	622	23	28
<b>Cyclocross 700c</b>									
	Frequency CX Team i19 700c	TCS	Cyclocross	Condition 3	Disc	622 x 19c	622	19	24
	ChrisCross i19 700c	TCS	Cyclocross	Condition 3	Rim	622 x 19c	622	19	24

## Model Year 2015

Bicycle Type	WTB Rim Name	WTB Rim Standard	Industry Standard Name for Intended Use	ASTM Indended Use Classification	Brake Type	ISO / ETRTO Rim Size Designation	Rim Bead Seat Diameter	Inner Rim Width (in mm)	TCS Rim Tape Width (in mm)
<b>Mountain 26"</b>									
	KOM i23 26"	TCS	Cross Country / All Mountain	Condition 4	Disc	559 x 23c	559	23	28
	KOM i25 26"	TCS	All Mountain / Enduro	Condition 4	Disc	559 x 25c	559	25	30
	Frequency Team i19 26"	TCS	Cross Country	Condition 3	Disc	559 x 19c	559	19	24
	Frequency Team i23 26"	TCS	Trail / All Mountain	Condition 4	Disc	559 x 23c	559	23	28
	Frequency Team i25 26"	TCS	Enduro / Downhill	Condition 4	Disc	559 x 25c	559	25	30
	Frequency Race i19 26"	TCS	Cross County	Condition 3	Disc	559 x 19c	559	19	24
	Frequency Race i23 26"	TCS	Trail / All Mountain	Condition 4	Disc	559 x 23c	559	23	28
	Frequency Race i25 26"	TCS	Enduro / Downhill	Condition 4	Disc	559 x 25c	559	25	30
	ST i19 26"	TCS	Cross Country	Condition 3	Disc	559 x 19c	559	19	24
	ST i23 26"	TCS	Trail / All Mountain	Condition 4	Disc	559 x 23c	559	23	28



	Scraper i45 29"	TCS	Bikepacking / Plus Sized / Trail	Condition 4	Disc	622 x 45c	622	45	50
	KOM i21 29"	TCS	Cross Country	Condition 3	Disc	622 x 21c	622	21	26
	KOM i23 29"	TCS	Cross Country / All Mountain	Condition 4	Disc	622 x 23c	622	23	28
	KOM i25 29"	TCS	All Mountain / Enduro	Condition 4	Disc	622 x 25c	622	25	30
	Frequency Team i19 29"	TCS	Cross Country	Condition 3	Disc	622 x 19c	622	19	24
	Frequency Team i23 29"	TCS	Trail / All Mountain	Condition 4	Disc	622 x 23c	622	23	28
	Frequency Team i25 29"	TCS	All Mountain / Enduro	Condition 4	Disc	622 x 25c	622	25	30
	Frequency Race i19 29"	TCS	Cross County	Condition 3	Disc	622 x 19c	622	19	24
	Frequency Race i23 29"	TCS	Trail / All Mountain	Condition 4	Disc	622 x 23c	622	23	28
	Frequency Race i25 29"	TCS	All Mountain / Enduro	Condition 4	Disc	622 x 25c	622	25	30
	ST i19 29"	TCS	Cross Country	Condition 3	Disc	622 x 19c	622	19	24
	ST i23 29"	TCS	Trail / All Mountain	Condition 4	Disc	622 x 23c	622	23	28
	ST i25 29"	TCS	All Mountain / Enduro	Condition 4	Disc	622 x 25	622	25	30
	<b>Cyclocross 700c</b>								
	Frequency CX Team i19 700c	TCS	Cyclocross	Condition 3	Disc	622 x 19c	622	19	24
	ChrisCross i19 700c	TCS	Cyclocross	Condition 3	Rim	622 x 19c	622	19	24

**Model Year 2016**

Bicycle Type	WTB Rim Name	WTB Rim Standard	Industry Standard Name for Intended Use	ASTM Indended Use Classification	Brake Type	ISO / ETRTO Rim Size Designation	Rim Bead Seat Diameter	Inner Rim Width (in mm)	TCS Rim Tape Width (in mm)
<b>Mountain 26"</b>									
	KOM i21 26"	TCS	Cross Country	Condition 3	Disc	559 x 21c	559	21	26
	KOM i23 26"	TCS	Cross Country / All Mountain	Condition 4	Disc	559 x 23c	559	23	28
	KOM i25 26"	TCS	All Mountain / Enduro	Condition 4	Disc	559 x 25c	559	25	30
	Frequency Team i19 26"	TCS	Cross Country	Condition 3	Disc	559 x 19c	559	19	24
	Frequency Team i23 26"	TCS	Trail / All Mountain	Condition 4	Disc	559 x 23c	559	23	28
	Frequency Team i25 26"	TCS	Enduro / Downhill	Condition 4	Disc	559 x 25c	559	25	30
	Frequency Race i19 26"	TCS	Cross Country	Condition 3	Disc	559 x 19c	559	19	24
	Frequency Race i23 26"	TCS	Trail / All Mountain	Condition 4	Disc	559 x 23c	559	23	28
	Frequency Race i25 26"	TCS	Enduro / Downhill	Condition 4	Disc	559 x 25c	559	25	30
	ST Sleeved i19 26"	TCS	Cross Country	Condition 3	Disc	559 x 19c	559	19	24
	ST Sleeved i23 26"	TCS	Trail / All Mountain	Condition 4	Disc	559 x 23c	559	23	28
	ST Pinned i19 26"	TCS	Cross Country	Condition 3	Disc	559 x 19c	559	19	24
	ST Pinned i23 26"	TCS	Trail / All Mountain	Condition 4	Disc	559 x 23c	559	23	28
	ST Pinned i25 26"	TCS	All Mountain / Enduro	Condition 4	Disc	559 x 25c	559	25	30

Mountain 27.5" / 650b									
	Ci24 27.5" / 650b	TCS	Cross Country / All Mountain	Condition 4	Disc	584 x 24c	584	24	29
	Scraper i45 27.5" / 650b	TCS	Bikepacking / Plus Sized / Trail	Condition 4	Disc	584 x 45c	584	45	50
	KOM i21 27.5" / 650b	TCS	Cross Country	Condition 3	Disc	584 x 21c	584	21	26
	KOM i23 27.5" / 650b	TCS	Cross Country / All Mountain	Condition 4	Disc	584 x 23c	584	23	28
	KOM i25 27.5" / 650b	TCS	All Mountain / Enduro	Condition 4	Disc	584 x 25c	584	25	30
	Asym i19 27.5 / 650b	TCS	Cross Country	Condition 3	Disc	584 x 19c	584	19	24
	Asym i23 27.5" / 650b	TCS	Cross Country / All Mountain	Condition 4	Disc	584 x 23c	584	23	28
	Asym i29 27.5" / 650b	TCS	All Mountain / Enduro	Condition 4	Disc	584 x 29c	584	29	34
	Asym i35 27.5" / 650b	TCS	All Mountain / Enduro	Condition 4	Disc	584 x 35c	584	35	40
	Frequency Team i19 27.5" / 650b	TCS	Cross Country	Condition 3	Disc	584 x 19c	584	19	24
	Frequency Team i23 27.5" / 650b	TCS	Trail / All Mountain	Condition 4	Disc	584 x 23c	584	23	28
	Frequency Team i25 27.5" / 650b	TCS	Enduro / Downhill	Condition 4	Disc	584 x 25c	584	25	30



	Frequency Race i19 27.5" / 650b	TCS	Cross Country	Condition 3	Disc	584 x 19c	584	19	24
	Frequency Race i23 27.5" / 650b	TCS	Trail / All Mountain	Condition 4	Disc	584 x 23c	584	23	28
	Frequency Race i25 27.5" / 650b	TCS	Enduro / Downhill	Condition 4	Disc	584 x 25c	584	25	30
	ST Sleeved i19 27.5" / 650b	TCS	Cross Country	Condition 3	Disc	584 x 19	584	19	24
	ST Sleeved i23 27.5" / 650b	TCS	Trail / All Mountain	Condition 4	Disc	584 x 23c	584	23	28
	ST Pinned i19 27.5" / 650b	TCS	Cross Country	Condition 3	Disc	584 x 19c	584	19	24
	ST Pinned i23 27.5" / 650b	TCS	Trail / All Mountain	Condition 4	Disc	584 x 23c	584	23	28
	ST Pinned i25 27.5" / 650b	TCS	All Mountain / Enduro	Condition 4	Disc	584 x 25c	584	25	30
<b>Mountain 29"</b>									
	Ci24 29"	TCS	Cross Country / All Mountain	Condition 4	Disc	622 x 24c	622	24	29
	Scraper i45 29"	TCS	Bikepacking / Plus Sized / Trail	Condition 4	Disc	622 x 45c	622	45	50
	KOM i21 29"	TCS	Cross Country	Condition 3	Disc	622 x 21c	622	21	26
	KOM i23 29"	TCS	Cross Country / All Mountain	Condition 4	Disc	622 x 23c	622	23	28
	KOM i25 29"	TCS	All Mountain / Enduro	Condition 4	Disc	622 x 25c	622	25	30

	Asym i19 29"	TCS	Cross Country	Condition 3	Disc	622 x 19c	622	19	24
	Asym i23 29"	TCS	Cross Country / All Mountain	Condition 4	Disc	622 x 23c	622	23	28
	Asym i29 29"	TCS	All Mountain / Enduro	Condition 4	Disc	622 x 29c	622	29	34
	Asym i35 29"	TCS	All Mountain / Enduro	Condition 4	Disc	622 x 35c	622	35	40
	Frequency Team i19 29"	TCS	Cross Country	Condition 3	Disc	622 x 19c	622	19	24
	Frequency Team i23 29"	TCS	Trail / All Mountain	Condition 4	Disc	622 x 23c	622	23	28
	Frequency Team i25 29"	TCS	All Mountain / Enduro	Condition 4	Disc	622 x 25c	622	25	30
	Frequency Race i19 29"	TCS	Cross Country	Condition 3	Disc	622 x 19c	622	19	24
	Frequency Race i23 29"	TCS	Trail / All Mountain	Condition 4	Disc	622 x 23c	622	23	28
	Frequency Race i25 29"	TCS	All Mountain / Enduro	Condition 4	Disc	622 x 25c	622	25	30
	ST Sleeved i19 29"	TCS	Cross Country	Condition 3	Disc	622 x 19c	622	19	24
	ST Sleeved i23 29"	TCS	Trail / All Mountain	Condition 4	Disc	622 x 23c	622	23	28
	ST Pinned i19 29"	TCS	Cross Country	Condition 3	Disc	622 x 19c	622	19	24
	ST Pinned i23 29"	TCS	Trail / All Mountain	Condition 4	Disc	622 x 23c	622	23	28
	ST Pinned i25 29"	TCS	All Mountain / Enduro	Condition 4	Disc	622 x 25c	622	25	30
<b>Cyclocross 700c</b>									
	Frequency CX Team i19 700c	TCS	Cyclocross	Condition 3	Disc	622 x 19c	622	19	24

	ChrisCross i19 700c	TCS	Cyclocross	Condition 3	Rim	622 x 19c	622	19	24
--	------------------------	-----	------------	-------------	-----	-----------	-----	----	----