



*Because your life is on the line!*

626 Thirteenth Street • Franklin, PA 16323 • Toll Free: 877.228.9327 • 814.437.1808

fax: 814.437.2544 • [fcv@velocity.net](mailto:fcv@velocity.net) • [www.frenchcreekproduction.com](http://www.frenchcreekproduction.com)

Proudly Made in the U.S.A.

DATE: July 10, 2013

SUBJECT: Use of 1715 on a metal roof

Dear FrenchCreek Customer,

The 1715 roof anchor was designed to be used at the peak of the roof; however should the need arise, this anchor can be used on a flat roof. The roof anchor location MUST be capable of supporting at least 5000 lbs or provide a 2:1 safety factor. The anchor must be attached over decking into the structure of the roof, such as a truss or purlin. One tek screw in every hole is required. The screw must be of an equivalent size and strength of the nails provided. Failure to properly secure the anchor to the roof joist will not provide the strength required to arrest a fall and the anchor could be pulled from the roof.

Should you have any further questions please contact me at your earliest convenience.

Thank you,

Aaron Hicks  
Tech Support  
French Creek Production  
[www.frenchcreekproduction.com](http://www.frenchcreekproduction.com)  
Toll free: 877-228-9327  
Fax: 814-437-2544